

Titus Group
Technical Catalogue
and Manual



Furniture Fittings Systems

2017

Important Information

Technical information

While every effort has been made in the production of this catalogue to ensure the accuracy of information, our products are continually being revised and users should confirm the up to date specification before ordering. Due to constant improvement of products presented in the catalogue, we can make changes at any time and without notice.

Responsibility

It is the responsibility of the user to ensure the fitness of hardware for the intended purpose. We recommend assessment by appropriate testing in the application and by technical enquiry to our representatives.

Intellectual property

Titus Group owns the intellectual property rights in its products worldwide whether as trademarks, patents, intellectual, copyright, designs, illustrations, drawings and the 'know how' contained in their design and production. Titus Group respects the equivalent rights in competitors and all other relevant product design rights. To our knowledge our products do not infringe any intellectual property rights of competitors or other parties. Titus Group takes infringements of its rights seriously and will rigorously defend these rights to the full extent of the law.

*Non preferred articles

All Item numbers in the catalogue marked with * are for non preferred items available on extended delivery times.

Trademarks

Titus and Titusonic are registered trademarks of Titus International Ltd. Lama is a registered trademark of Titus d.o.o. Dekani, WoodWelding is a registered trademark of WW SA.

Contents

1

2

3

4

5

Connectors	1.1
- System 1	1.7
- System 2	1.11
- System 3	1.15
- System 4	1.17
- System 5	1.23
- System 6	1.45
- System 7	1.57
Soft Closing Systems	2.1
- Information	2.3
- Glissando add-on hinge soft closing system	2.15
- Glissando stand-alone soft closing system	2.19
- Titusoft for drawers	2.21
- Titusoft for sliding doors	2.27
Concealed Hinges	3.1
- Information	3.3
- T-type Glissando, T-type	3.27
- S-type-i plus, S-type-i, S-type plus, S-type	3.57
- B-type-i, B-type	3.105
- Special hinges	3.145
- Push latch	3.149
Other Functional Fittings	4.1
The Titus Group Profile	5.1

Connectors

Connectors

Product Guide

Page

System 1

Fittings for rigid assembly systems

a highly cost-effective
and rigid assembly system
for factory, consumer
and home assembly

1.7

System 2

Fittings for face-boring applications

face boring applications that
provide a tolerant efficient
assembly

1.11

System 3

Fittings for face and edge boring

two component rigid face
and edge drilling fastening

1.15

System 4

Fittings for face-boring only

a range of low-cost one-piece
fittings for high volume home
assembly applications

1.17

System 5

Cams and dowels

a comprehensive range
of cam and dowel connecting
fittings for all cabinet
applications

1.23

System 6

Quickfit-Expano connectors

face boring expanding
connectors for all cabinet
applications

1.45

System 7

Heavy duty cams and dowels

high quality fittings for offices
and public furniture

1.57

Connectors

Information

Why Choose Titus?

Titus connectors add value to furniture and to furniture manufacturing

Titus connectors improve the quality of furniture and lower the cost of manufacturing and assembly while ensuring a high degree of customer satisfaction.

The most advanced range of connectors available on the market

Precise and efficient product design. The broadest possible range of drilling tolerances ensures reliable assembly and consistently strong joints. 'Klix' locking feature, the engagement of interlocking teeth on cam and dowel, to prevent joint loosening in service or transit. Expanding function provides degrees of variation in out-of-tolerance drillings ensuring stronger joints and improved quality of furniture. Twinstart thread for faster and more stable insertion. Depth stop collar prevents over-insertion. Firm tightening for greater confidence in use. Cam locks at 230° assuring smooth tightening action and greater dowel pull-up.

Quickfit for hand dowel insertion. Quickfit TL5, new generation steel dowel with quickfit expando technology for insertion in Ø5mm dowel holes.

Quickfit TL2, TL4 with the built-in self adjustment feature for higher drilling tolerances.

Quickloc one piece fitting for faster assembly with integrated expanding cam and dowel.

Zinc+steel dowel for optimal strength and performance.

Precise dowel manufacturing high precision of zinc and strength of steel assures 100% dimensional accuracy.

Easy and quick consumer friendly self-assembly of furniture

Self-assembly furniture offers consumers good value and instant availability of products.

With the aim of providing consumer with simpler instructions, fewer parts and an easier assembly process, Titus has significantly reduced and simplified the number of fittings traditionally required in furniture production.

Titus connectors provide consumers with easy assembly and furniture producers with increased productivity:

- reduced number of assembly parts
- easy assembly instructions
- security of packed parts during transit

CAF  **Quick & Easy**

Consumer Assembly Friendliness

Connectors

Information

Easy and Quick Furniture Assembly

CAF formula

CAF=Consumer Assembly Friendliness

Titus CAF formula provides a comparative measure for customer satisfaction. By using it manufacturers are able to evaluate their products internally or against those of their competitors.

While offering consumers easier and faster assembly, there are obvious advantages also for furniture manufacturers – buying, counting, bagging and stocking of fittings can be greatly reduced.

$$\text{Total quantity of parts} + \text{Actions to assemble} \times \text{Number of types of parts}$$


$$(T+A)N = CAF$$

Minimise the numbers in the
Titus CAF™ formula
to achieve:

- High customer satisfaction
- Improved productivity
- Higher profits

How does it work?

Comparative CAF scores to assemble a hand held demonstrator



	T	A	N	CAF
Connecting screw (traditional assembly)	4	38	3	126
Cam & dowel with single start thread	6	21	4	108
Cam & dowel with twinstart thread	6	15	4	84
Cam & TL2 dowel (self-assembly)	6	7	4	52
Cam & TL2 dowel (factory pre-inserted)	2	3	2	10
Quickloc	2	3	1	5
Fully assembled demonstrator	1	0	1	1

System 1

Fittings for Rigid Assembly Systems

System Features

Double locking carcase screw

- Zinc diecast for precision
- Titus Double locking carcase screw makes an almost invisible connection
- Collar under the head to pull panels together
- 2nd ‘lower’ thread pulls against a ‘faster’ thread to provide maximum connection force and prevents overdriving of fastener
- Almost invisible in position
- Head can be ‘fastcapped’ or filled

Hi-Lo™ carcase construction screw

The Hi-Lo™ carcase construction screw (CCS) offers a strong, tolerant and cost effective connection with minimal panel preparation.

The combination effect of the elements of a Hi-Lo™ screw means

- A greater differential between drive torque and strip torque in fibrous and particle materials to ensure a reliable and repeatable fixing
- Hi-Lo™ threads provide minimum bursting forces
- ‘Hi’ thread gives low bursting component force from the sharp 30 degree angle thread
- ‘Lo’ thread at 60 degree angle uses the vertical force component to press fibrous and particle components of panels onto the ‘Hi’ thread and are contained by their greater height
- The very small shank on a Hi-Lo™ screw means less material displacement than conventional threads and enables minimum or partial drilling of pilot holes for quicker panel processing

Barrel nut (plastic)

- Used with Titus Hi-Lo™ screws
- Titus barrel nuts provide maximum strip torque for reasonable drive torque
- Capable of multiple reconnection repeatability

Cover caps


- Available in multiple colours
- All recess and head types offered
- High quality engineering polymers used in their construction
- Uniformity of holding with good tolerance
- Wide range of application and use conditions

System 1

Fittings for Rigid Assembly Systems

Double Locking Carcase Screw

- High performance from widely spaced primary thread
- Finer secondary thread provides additional holding power and positive stop (no override)
- Increased support for vertical panel is gained from the funnel head with collar at its base
- One-piece fitting






Technical and mounting details


Screw 6x42

Item number


00180 → 885




1. Insert screw to shoulder in face board



2. Screw into Ø5mm hole



3. Board joint pulled up by collar on screw



4. Board locked in place by screw



1000 Pcs


Made of zinc

System 1

Fittings for Rigid Assembly Systems




Hi-Lo™ Screw and Barrel Nut

- Hi-Lo™ screws have a twin thread for faster insertion
- 'Hi' threads and 'Lo' threads combine to give excellent pull out in chipboard
- Funnel head design means no countersinking
- Steel is case hardened for extra strength



Technical and mounting details


Hi-Lo™ screw



10000 Pcs (00062)
9000 Pcs (00068)
7000 Pcs (00071)
4000 Pcs (00077, 00171, 06074)
3000 Pcs (00172, 06077, 06080)

Made of steel


Barrel nut



10000 Pcs


Made of plastic

Screw cap



10000 Pcs (01042)
5000 Pcs (01020)

Made of plastic



Screw diameter	B	L	Drive type	Item number	Black	Phosphate	White				
					Total length						
4		24		*00062 →	852						
4		28		*00068 →	852						
4		33		00071 →	852						
4	32	45		00177 →	852						
4	32	45		*00171 →	852						
4	32	55		00072 →	852						
4		38		06074 →	852						
4	32	50		*06077 →	852						
5	32	50		*06080 →	852						
Drive type				*American market only							
		hexagonal drive									
		cross slot									
				01056 →	835		877				







Other colours on request

pozi, philips drive	01020 →	835		877
hexagonal drive	01042 →	835		877
Other colours on request				

System 1

Connecting Screws

- Screws with crosshead PZ2 screwdriver or allen key slot
- Decorative cover caps are available in different colours

	Technical and mounting details	Item number	Zinc plated	Ochre	White
Crosshead screwdriver slot	  	827-6202 →	040		
Allen-key slot	  	827-6201 →	040		
Cover caps for connecting screws	  	827-4013 → 827-4130 →	330 330	350 350	
1000 Pcs (827-4130) 2000 Pcs (827-4013)	Made of plastic				


System 2

Fittings for Face-boring Applications

System Features

A family of face boring only concealed fittings and rail fasteners with wide tolerances and the enormous clamping power of an angled screw.

- Factory or site component installation
- Wide tolerances
- Face boring only
- Cover caps for concealment
- For kitchen, furniture storage, office and store fixture applications
- Non twist rail fastener versions
- Multi use 'pocket screw' replacement



System 2

Fittings for Face-boring Applications

Concealed Fittings





- Combination of hi-thread screw and nylon insert allows a high clamping force improving cabinet rigidity
- Unlimited stacking height due to flush housing
- Provides a strong, secure fitting which eliminates the need for edge boring
- +/-1mm tolerance absorbs drilling inaccuracies improving consumer confidence in use

	Technical and mounting details	Item number	Brown beige	Black	White	Zinc plated
Housing assembly		02046 →	835	877		
	2500 Pcs	Made of plastic, steel				
Housing (no nose)		*02985 →			877	
			*European market only			
	2500 Pcs	Made of plastic	01709 →			883
Screw panhead No 8 x 17.6						
	15000 Pcs	Made of steel	01732 →	806	877	
Cover cap				Other colours on request		
	7000 Pcs	Made of plastic	→ see page 1.62			
Inserts Made of plastic						

System 2

Fittings for Face-boring Applications

- Range of fixing blocks for multiple applications
- Face drilling only required
- Durable plastic material is flexible providing greater holding power
- Choose screw fastening or hammer insertion

	Technical and mounting details	Item number	Dark brown	Light brown	Ivory	White
Rail fastener	  	02075 →	831	867		877
 2000 Pcs	Made of plastic					
Housing (no nose)	  	02077 →			875	877
 2000 Pcs	Made of plastic					
Modesty block	 	*06073 →		867		877
 1500 Pcs	Made of plastic	*European market only				


System 3

Fittings for Face and Edge Boring

System Features

Titus System 3 is a two component rigid face and edge drilled fastening with half turn to fasten. System 3 offers almost full concealment and wide tolerances in use.

- Automatic or in-factory placement
- Pre-location pin ensures ease of assembly
- Less than one turn of a screwdriver to fasten
- Shelf edge installation of pin means maximum shelf cut size tolerance
- Can be used on 12mm shelf panels
- No loose parts for maximum convenience in RTA
- Drawer front fixing, cabinet construction




System 3

Fittings for Face and Edge Boring

Concealed Housing

- One turn locking system reduces assembly time, both in the factory and home
- Pre-assembly feature for consumer convenience
- Choice of dowels to suit drilling
- Hi-Lo screw feature for faster insertion

	C	D	D2	Drilling length for dowel	Drilling depth	Drilling diameter for dowel thread	Item number	Black	Zinc plated	Yellow passivate	White
Housing assembly											
											
Technical and mounting details											
	X	Y	Z	Ø25 x D			03118 →	835			877
							03121 →	835			
X, Y - depends on board thickness <i>Other colours on request</i>											
 2500 Pcs	Made of plastic or zinc, plastic						03168 →		883		
Screw dowel Ø5											
	X	Y	Z	Ø5 x 30							
X, Y - depends on board thickness											
 1000 Pcs	Made of steel										
Screw dowel Ø3											
	X	Y	Z	ØD2 x C			03181 →		881		
							03180 →		881		
							*03090 →	883			
X, Y - depends on board thickness <i>*American market only</i>											
 5000 Pcs (03180) 4000 Pcs (03181) 1000 Pcs (03190)	Made of steel										
Cover cap							03150 →	835			877
											
 15000 Pcs	Made of plastic										

System 4

Fittings for

Face-boring Only

System Features

Cost effective one piece fittings with face boring benefits

- Flush and block components
- Face-boring only
- Good tolerances
- One piece connectors
- Angledriv versions fastening with maximum driving power and flexibility
- Quickloc™ versions need only one turn to tighten for fast assembly
- Foolproof consumer home insertion


Quickloc™ One-piece connector

The integrated housing and dowel make Quickloc™ the most user-friendly and tolerant product available.


- High degree of drilling tolerance
- Push-in design
- Tool-free insertion
- Integrated expanding housing and dowel provide consistently stronger joints
- 'Klix' locking system

Quickloc™ Assembly


1. Press Quickloc into the face board



2. Assemble the panels



3. Tighten in less than one turn





System 4

Quickloc™

One Piece Expanding Connector

- An innovative, one-piece connector, capable of hand insertion
- Is highly tolerant and tightens in less than one turn
- Is a face-bored product
- Offers a high degree of drilling tolerance and is the only connector of its type to provide pull-up of cabinet panels when tightened

		Item number	Dark brown	Black	White
	Technical and mounting details	06803 →	831	835	877
Quickloc Ø20 flanged 2500 Pcs	Made of zinc, plastic	06806 →	831	835	877
	Technical and mounting details	06813 →	831	835	877
Quickloc Ø25 flanged 2500 Pcs	Made of zinc, plastic	06839 →	831	835	877
	Technical and mounting details				
Quickloc Ø25 flush 1500 Pcs	Made of zinc, plastic				

System 4

Fittings for Face-boring Only

Flushbloc™ / Flushfix™

- The Angeldriv screw provides high level of tolerance
- Face drilling only required
- Corner joint and shelf fixing options

	Technical and mounting details	Item number	Brown beige	Black	Silver	White	Zinc
Flushfix™	<p>Technical drawing showing dimensions: height 27.5, width 10, thickness 10, hole diameter Ø5x13, base thickness 4.5, and side thickness 12.</p>	02161 →	806	861	877		
	Other colours on request						
2500 Pcs	Made of plastic						
Flushbloc™ with screw	<p>Technical drawing showing dimensions: height 27.5, width 10, thickness 10, hole diameter Ø5x13, base thickness 4.5, and side thickness 12.</p>	02193 →		835		877	
	Other colours on request						
2000 Pcs	Made of zinc and plastic						
Flushbloc™ assembly	<p>Technical drawing showing dimensions: height 27.5, width 10, thickness 10, hole diameter Ø5x13, base thickness 4.5, and side thickness 12.</p>	*02190 →		835		877	
	* American market only Other colours on request						
2500 Pcs	Made of plastic						
Angeldriv screw for use with Flushfix™	<p>Technical drawing showing dimensions: head diameter Ø10, shank diameter Ø6, shank length 14.5, and total length 19.</p>	round head 00021 →					885
	flat head 00022 →						885
2000 Pcs (00021) 4000 Pcs (00022)	Made of zinc						


System 4

Fittings for

Face-boring Only

Minibloc™ / Twinbloc™

- One-piece connector range
 - Face drilling only required
 - Easy to use, foolproof home insertion
 - Angeldriv screw tolerates good levels of inaccurate drilling increasing consumer confidence






Technical and mounting details

Angledriv screw → see page 1.19

System 4

Fittings for Face-boring Only

Knock-down Fittings


			Zinc plated	White	Brown
Fitting	Item number	278-4129	350	370	
 					
 5000 Pcs Made of plastic					
Screw	Item number	825-7561	040		
					
 5000 Pcs Made of steel					

System 4

Fittings for Face-boring Only



Cambloc

- Screw-on and knock-in versions are available
- Plastic housings are available in different colours
- Quick and intuitive assembly when fittings are pre-mounted on furniture



Technical and mounting details



Screw-on



1000 Pcs

Made of plastic, zinc cam

Knock-in



500 Pcs

Made of plastic, zinc cam

	Zinc plated + white housing	Zinc plated + brown housing	Zinc plated + black housing	
Item number	279-9187 ↗	960	970	980

System 5 Cams and Dowels

System Features

The most advanced cam and dowel range

Titus System 5 is a comprehensive range of cam and dowel connecting fittings with 'Klix' and Quickfit features for all cabinet applications: panel-to-panel, panel-to-hollow profile, back-to-back

Dowels

- **Quickfit TL5, 'Full metal jacket'**
Tool-free insertion technology for Ø5mm dowel holes
- **Quickfit TL2, TL4, TL5 dowels**
a unique solution for factory pre-insertion, high level of drilling tolerances

- **Quickfit dowels**
quick hand insertion, easy assembly

- **Diecast dowels (zinc)**
precise manufacturing, optimal shape and design


- **Turned dowels (steel)**
'traditional' design, smooth surface, best strength performance

- **Combi dowels (zinc and steel)**
high precision of zinc, strength of steel, 100% dimensional accuracy and optimal performance

Titus 'Klix'™


Titus 'Klix' locking system ensures the engagement of the interlocking teeth on cam and dowel providing:
· vibration-proof joint
· rigid construction that will not loosen in service or transit

Dowel insertion time comparison




2 o'clock lock Smooth closing

Linear cam profile assures smooth, firm tightening action and greater pull-up. The cam always locks at 2 o'clock lock (230°), enabling greater consumer confidence in use while improving furniture quality.




Drilling tolerances



Zinc/Combi dowel




Optimal performance and perfect joint even with inaccurate drillings.




Quickfit TL5 dowel,
Quickfit TL2 dowel



Quickfit TL4 dowel




ETHC=Edge To Hole Center



Dowels for factory insertion

Quickfit TL5, Quickfit TL2 and Quickfit TL4 are the only available dowels that allow for factory preinsertion

- Easier packing
- Less damages in handling
- Perfect for the RTA market



System 5

Cams and Dowels


Cam5000

Universal cam

New Cam5000 works with all Titus parallel neck dowels enabling simple stock management and greater confidence in use.

Highly resistant central shape

Shape of the cam body is redesigned to prevent the cam toroidal deformation or breakage in panel while tightening. The Cam5000 high resistance enables strong and reliable joint.



Linear cam profile


Linear cam profile ensures:

- Smooth tightening action
- Greater dowel pull-up




Optimised cam profile

Optimised cam profile ensures smooth and tight joint with no gap between panels.



2 o'clock lock

The cam always locks at 2 o'clock (230°), enabling greater consumer confidence in use while improving furniture quality.



Cam retaining pips

Cam retaining pips assures:


- The cam is held in position prior to assembly
- Secure cam positioning during transport and handling
- Accurate factory insertion



Zinc+steel Combi Dowels


**Zinc+steel
technology for
optimal strength
and performance**

The Combi dowel combines steel and a small amount of zinc to ensure high precision and dimensional accuracy, essential to provide furniture manufacturers with the broadest possible range of drilling tolerances.




The steel neck and head provide better resistance to torsion and pull-out enabling a high performance joint

Zinc body:
Positive stop collar ensures correct insertion depth
Twinstart for faster and more stable insertion



The toroidal dowel head form transfers the forces between cam and dowel more effectively resulting in a small cam bursting force.



100% dimensional accuracy assured

System 5 Cams and Dowels


Quickfit Connectors

It is the fastest assembly system on the market. The Quickfit™ dowel may be inserted by hand, using only finger pressure. This eliminates the labour intensive process of screw-in assembly and the potential panel damage.


The Quickfit™ range of dowels has been extended to provide a complete family of fittings available in diameters of 5mm, 8mm and 10mm and lengths of 24mm and 34mm. These dowels are compatible with the range of Titus Ø15mm cams.

Assembly


1. Press the cam into face board




2. Insert the dowel into side panel




3. Assemble the panels



4. Tighten the cam to lock dowel



5. Assembled panels



Quickfit TL Connectors

Quickfit-TL™ dowel offers furniture manufacturers a fast assembly system providing high drilling tolerances. It has a built-in self-adjustment feature, which enables common drilling inaccuracies to be overcome.

For the self-assembly furniture consumer, Titus Quickfit-TL™ is the most consumer friendly fitting on the market. Apart from the benefit of fully tightened joints and easy locking into the same position, Quickfit-TL™ provides an exceptionally smooth action when tightened, requiring very little effort.

Drilling tolerances

Marginal inconsistencies of drilling and the problems associated with the natural movement of wood panels, no longer present problems.


Quickfit-TL™ provides a tolerance of +1/-1mm on drilling operation while ensuring that the final result is a perfectly precise and aligned joint. No other assembly fittings system can offer such tolerances and still maintain a perfect joint.

Assembly


1. Press the cam into face board




2a. Either push dowel into edge hole or...




2b. Insert the dowel into side panel



3. Assemble the panels



4. Tighten cam to lock dowel



System 5 Cams and Dowels

Quickfit TL5


'Full metal jacket'

Quickfit TL5 with expanding steel sleeve is the new generation of Titus Quickfit TL dowels. It expands the Titus Quickfit tool-free insertion technology to widely used Ø5mm dowel holes.

Tool-free insertion for Ø5mm dowel holes


Unique at the market

- Easy to push in
- Works without wooden dowels



Expanding steel sleeve

Expanding steel sleeve assures high resistance to torsion and pull-out.



High drilling tolerances

Extended dowel head form works as a positive stop against cam and provides tolerances of $-/+1\text{mm}$ on drilling operation.



ETHC-Edge To Hole Center


Shape of dowel sleeve

- Acts as a positive stop when face inserted
- Ensures correct insertion depth




50% less time to assemble the cabinet with factory insertion

Quickfit TL5 dowel is inserted into the panel by simply pushing the head of the dowel into the edge hole until it engages with the cam. It remains in this position until the cam is rotated to lock the boards together.



For a maximum efficiency the insertion process can be automated using the Titus proprietary Lama FastFit machine.



Functions with multiple wooden materials

- Functions with multiple wooden materials: chipboard, MDF, solid wood
- Improved performance in low density boards
- Assures strong and reliable joint

System 5

Quickfit TL5




'Full Metal Jacket'

- Tool-free insertion technology for Ø5mm dowel holes
- To be used with Cam5000 only
- Drilling tolerances of +1/-1mm when edge or face inserted
- Expanding steel sleeve assures a strong joint, highly resistant to pull-out
- Functions in multiple wooden materials (chipboard, MDF, solid wood)

A		Zinc corrosion
Drilling distance	Item number	
34	09652 →	897
24	09651 →	897

Technical details

Quickfit TL5 dowel

Tolerance range



2000 Pcs





Made of steel

System 5

Cams and Dowels

Quickfit TL Dowels

- Available in Ø5mm and Ø8mm for panel-to-panel applications
- Suitable for use with all Ø15mm Cam2000, Cam3000 and Cam5000 products
- 'Klix' locking feature provides a strong, vibration proof joint
- Highly tolerant in edge-inserted, TL4 also in face-inserted applications





	A	D2			
	Drilling distance	Drilling diameter for dowel thread	Item number	Black	Dark grey
Quickfit TL2					
					
D2=Ø5mm					
					
D2=Ø8mm					
					
					
	Tolerance range				
 2000 Pcs					
1000 Pcs (05474)	Made of zinc, plastic				
Quickfit TL4					
					
					
					
	Tolerance range				
 2000 Pcs					
Made of zinc, plastic					

System 5

Cams and Dowels

Quickfit Dowels

- Available in Ø5mm, Ø8mm and Ø10mm for panel-to-panel applications
- Suitable for use with all Ø15mm Cam2000, Cam3000 and Cam5000 products
- 'Klix' locking feature provides a strong, vibration proof joint
- Depth stop collar for accurate insertion


		A		
		Drilling distance	Item number	Dark grey
	Technical and mounting details			
Quickfit dowel Ø5mm		24	05714 →	880
		34	05685 →	880
				
 2000 Pcs	Made of zinc, plastic			
Quickfit dowel Ø8mm		20	05556 →	880
		24	05563 →	880
		28	05552 →	880
		34	05554 →	880
 1000 Pcs (05556,05552) 2000 Pcs (05563, 05554)	Made of zinc, plastic			
Quickfit dowel Ø10mm		24	05137 →	880
 1500 Pcs (05129) 2000 Pcs (05570)	Made of zinc, plastic	24	*05570 →	880
		34	05129 →	880

System 5

Cams and Dowels



Quickfit P2F Dowels

- The only product to enable standard panel drilling and connection of panel and hollow profile
- Available in Ø8mm for panel-to-hollow profile applications
- Suitable for use with all Ø15mm Cam2000, Cam3000 and Cam5000 products
- 'Klix' locking feature provides a strong, vibration proof joint



Technical and mounting details

Quickfit P2F






A	Drilling distance	Item number	Black
24	05414 →	835	

System 5

Cams and Dowels

Combi Dowel

- High quality zinc-steel dowel with greater resistance to torsion and pull-out
- Suitable for use with all Ø12mm and Ø15mm Cam2000, Cam3000 and Cam5000 products
- 'Klix' locking feature provides a strong, vibration proof joint
- Twiststart thread for faster and reliable insertion

	A	N	X		
	Drilling distance	Drilling depth	Thread length	Item number	Zinc
					
Technical and mounting details					
				34	12
				11	09435 →
				28	10
				9.5	09588 →
				24	12
				11	09443 →
				24	9
				8.5	09583 →
				34	12
				11	*09424 →
				24	12
				11	*09423 →
				34	9
				8.5	*09456 →
 1000 Pcs					
 *2000 Pcs					
Made of steel and zinc					
				34	8
				10.5	09592 →
				34	10.5
				09594 →	885
 1000 Pcs					
Made of steel and zinc					



→ see page 1.61







→ see page 1.62

System 5

Cams and Dowels

Combi Dowel



	S	L	A	Drilling distance	Item number	Zinc	
Combi dowel Ø5 Full body							
  	PZ2 head		20.6	34.5	24	09597 →	885
 2000 Pcs	Made of steel and zinc						
Combi dowel Ø7							
  	Philips PH2 head		20	09430 →	885		
 1000 Pcs	Made of steel and zinc						
 Inserts	Made of plastic	→ see page 1.62					

System 5

Cams and Dowels

Double-ended Dowel

- Available in Ø7mm
- Suitable for use with all Ø12mm and Ø15mm Cam2000, Cam3000 and Cam5000 products
- No circlip for increased tolerance
- Available in a variety of lengths to suit most panel-to-panel applications


S	L	A	B		Zinc plated																														
				Drilling distance	Panel thickness																														
				Item number																															
41	47.4	24	0*	05929 →	883																														
61	67.4	34	0*	05757 →	883																														
77	83.4	34	16	05858 →	883																														
79	85.4	34	18	05859 →	883																														
80	86.4	34	19	05753 →	883																														
56	62.4	24	15	05592 →	883																														
57	63.4	24	16	05857 →	883																														
59	65.4	24	18	05380 →	883																														
60	66.4	24	19	05778 →	883																														
*B=0 → no panel required																																			
 250 Pcs (05753) 500 Pcs 1000 Pcs (05929, 05857) Made of steel																																			
Dowel with circlip																																			
 <div style="display: flex; align-items: center;"> <div style="margin-right: 20px;">  </div> <table border="1"> <tr> <td>77</td> <td>83.4</td> <td>34</td> <td>16</td> <td>05752 →</td> <td>883</td> </tr> <tr> <td>79</td> <td>85.4</td> <td>34</td> <td>18</td> <td>05772 →</td> <td>883</td> </tr> <tr> <td>80</td> <td>86.4</td> <td>34</td> <td>19</td> <td>05751 →</td> <td>883</td> </tr> <tr> <td>57</td> <td>63.4</td> <td>24</td> <td>16</td> <td>05775 →</td> <td>883</td> </tr> <tr> <td>60</td> <td>66.4</td> <td>24</td> <td>19</td> <td>05774 →</td> <td>883</td> </tr> </table> </div>						77	83.4	34	16	05752 →	883	79	85.4	34	18	05772 →	883	80	86.4	34	19	05751 →	883	57	63.4	24	16	05775 →	883	60	66.4	24	19	05774 →	883
77	83.4	34	16	05752 →	883																														
79	85.4	34	18	05772 →	883																														
80	86.4	34	19	05751 →	883																														
57	63.4	24	16	05775 →	883																														
60	66.4	24	19	05774 →	883																														
 <div style="display: flex; align-items: center;"> <div style="margin-right: 20px;">  </div> </div>																																			
 250 Pcs 500 Pcs (05775, 05774) Made of steel																																			

System 5

Cams and Dowels

Angled Dowels

- Suitable for applications requiring angled joints
- Suitable for use with all Ø12mm and Ø15mm Cam2000, Cam3000 and Cam5000 products
- Adjustable angle from 90° to 180°



Technical and mounting details


Angled dowel

Item number

Zinc plated

05860 →

883



Distance x in mm

	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	67,5°	70°	75°	80°	85°
--	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-------	-----	-----	-----	-----

A	13	61.9	57.9	55.3	53.5	51.7	50.5	49.5	48.6	47.8	47	46.7	46.4	45.7	45.1	44.6
	15	64.6	60.1	57	54.7	52.9	51.5	50.3	49.3	48.3	47.5	47.1	46.7	46	45.3	44.7
	16	66	61.2	57.9	55.4	53.5	52	50.7	49.6	48.6	47.7	47.3	46.9	46.1	45.4	44.7
B	18	68.8	63.3	59.6	56.9	54.7	53	51.6	50.3	49.2	48.2	47.7	47.3	46.4	45.6	44.8
	19	70.1	64.4	60.5	57.6	55.3	53.5	52	50.7	49.5	48.4	47.9	47.5	46.5	45.7	44.8
	22	74.2	67.6	63.1	59.7	57.1	55	53.2	51.7	50.4	49.1	48.6	48	46.9	45.9	45
	23	75.6	68.7	63.9	60.4	57.7	55.5	53.6	52.1	50.6	49.4	48.8	48.2	47.1	46	45

x








Made of steel

System 5

Cams and Dowels

End Dowels

- Available in a variety of head and length combinations to suit most end panel applications
- Suitable for use with all Ø12mm and Ø15mm Cam2000, Cam3000 and Cam5000 products
- 'Klix' locking feature provides a strong, vibration proof joint
- Both 'mushroom' and countersunk headed versions available


	A	B	S	L		Zinc
	Drilling distance	Panel thickness	Length	Total length	Item number	
Mushroom dowel						
						
						
500 Pcs (05610, 05611) 1000 Pcs (05608, 05609)	Made of zinc					
Countersunk dowel						
						
						
1000 Pcs	Made of zinc					

System 5

Cams and Dowels

Ø15mm Cam5000



- Improved central shape for highly resistant cam
- Suitable for use with Steel Quickfit TL5 dowels and all other parallel neck dowels
- 'Klix' locking feature provides a strong, vibration proof joint
- Cam retaining pips ensure that cam is held in panel position prior to assembly



Technical and mounting details

Cam5000
cross drive

PZ2 drive





1000 Pcs

Made of zinc

Cam5000
hexagonal drive

combined drive with HEX



1000 Pcs

Made of zinc

	B	D	e	h			
	Panel thickness	Drilling depth	Drilling for dowel	Cam height	Item number		Zinc
Cam5000 cross drive	12/13	10.5	6 min	9.9	09695 →		885
	15/16	12.5	7.5-8	11.9	09690 →		885

Use standard cover caps with pin=Ø4mm


Black available upon request

System 5

Cams and Dowels


Ø15mm Cam3000

- Its optimised shape provides a more efficient cam profile with smooth tightening action and greater dowel pull-up
- Suitable for use with Combi dowels, forged steel dowels, Quickfit dowels and Quickfit TL dowels
- 'Klix' locking feature provides a strong, vibration proof joint
- Cam-retaining pips ensure that a cam is held in panel position prior to assembly



Technical and mounting details

Cam3000
cross drive



B	D	e	h			Zinc
Panel thickness	Drilling depth	Drilling for dowel	Cam height	Item number		
12/13	10.5	6 min	9.9	09495 →		885
15/16	12.5	7.5-8	11.9	09533 →		885

Black available upon request



Made of zinc

Cam3000
hexagonal drive



combined drive with HEX



15/16	12.5	7.5-8	11.9	09537 →	885
18/19	14	9-9.5	13.2	09536 →	885

Use standard cover caps with pin=Ø4mm

Black available upon request









Made of zinc

System 5

Cams and Dowels

Ø15mm Cam3000 S

- Innovative design offers optimal performance with maximum cost effectiveness
- Suitable for use with Combi dowels, forged steel dowels and Quickfit dowels
- 'Klix' locking feature provides a strong, vibration proof joint
- Cam-retaining pips ensure that a cam is held in panel position prior to assembly


Technical and mounting details		B	D	e			Zinc	Zinc corrosi
		Panel thickness	Drilling depth	Drilling for dowel	Item number			
Cam3000 S/15	PZ2 drive	15/16	12.5	7.5-8	09491 →	885	897	
								
1000 Pcs	Made of zinc							
Cam3000 S/12	PZ2 drive	12 min	9.5 min	6 min	*09406 →	885	897	
								* European market only
2000 Pcs	Made of zinc							
Cam3000 S/12	Philips PH2 drive	12 min	9.5 min	6 min	*09631 →	885		
								* American market only
1000 Pcs	Made of zinc							
Cover caps Made of plastic		09630						

System 5

Cams and Dowels


Ø15mm Cam2000

- Available in a variety of head, drive recess and board thickness versions to suit most applications
- Suitable for use with all Titus dowels
- 'Klix' locking feature provides a strong, vibration proof joint
- Linear cam profile results in smooth, easy cam rotation and dowel pull-up



Technical and mounting details

Cam2000
Ø15



Panel thickness	B	D	e		Nickel	Zinc
12/13	10min	6-6.5		*05587 →	847	885
12/13	10.9	6-6.5		05653 →	847	885
15/16	12.7	7.5-8		05644 →	847	885
15/16	12.7	7.5-8		05654 →	847	885
18/19	14	9-9.5		05656 →	847	885
22/23	16	11-11.5		05657 →	847	885
25/26	17.9	12.5-13		05676 →	847	885
28/29	19.4	14-15.5		05678 →	847	885

Other finishes on request


*Ultraflat - specially designed for thin panels
(does not work with TL dowels)



500 Pcs (05676, 05678)
1000 Pcs

Made of zinc

Cam2000
Ø15 headed



	B	D	e		Nickel	Zinc
12	10min	6		*05586 →	847	885
13	10.9min	6.5		05652 →	847	885
16	12.9	8		05658 →	847	885
19	13	9.5		05659 →	847	885
23	14.5	11.5		05675 →	847	885
26	16.5	13		05677 →	847	885
29	19.4	14.5		05679 →	847	885

Other finishes on request

*Ultraflat - specially designed for thin panels
(does not work with TL dowels)



500 Pcs (05675, 05677, 05679)
1000 Pcs

Made of zinc



Cover caps for Ø15 cams

→ see page 1.63

Made of plastic

System 5

Cams and Dowels

Ø12mm Cam2000

- Suitable for all Titus screw-in dowels
- Available in a variety of head, drive recess and board thickness versions to suit most applications
- Particularly suited to drawer front attachment applications
- 'Klix' locking feature provides a strong, vibration proof joint
- Linear cam profile results in smooth, easy cam rotation and dowel pull-up

Technical and mounting details		B	D	e	Panel thickness	Drilling depth	Drilling for dowel	Item number	Black painting plate	Nickel plated	Zinc	Corrosion zinc
Cam2000 Ø12		12/13	10 min	6-6.5	05575 →	838	847	885	897			
		15/16	12	7.5-8	05578 →				885			
		18/19	13 min	9-9.5	05580 →				885			
<i>Other finishes on request</i>												
						2000 Pcs	Made of zinc					
Cam2000 Ø12 headed		12	9.2 min	5.25	05574 →		838	847	885	897		
		12	10 min	6	05576 →				885			
		16	12.5	8	05579 →				885			
<i>Other finishes on request</i>												
						1000 Pcs 2000 Pcs (05576)	Made of zinc					
	Cover caps for Ø12 cams Made of plastic		→ see page 1.63									

System 6

Quickfit-Expano

Connectors

System Features

A face boring connector family for 32mm system drilling with full range of panel and application variants for all cabinet manufacturing applications

- Minimum drilling requirements
- Linear cam design for constant tightening loads when driving
- Angledriv feature on cam for maximum driving comfort
- Interchangeable pins for wood, plastic and steel applications
- Pins with twinstart drive for fast insertion
- Interchangeable Quickfit pin fastenings available
- Toolless fastening capable versions
- Back-to-back fastenings for common vertical panel fixing of shelves

System 6 consists of a range of 20mm and 25mm diameter housings, Quickfit™ and conventional dowels, end dowels and double ended dowels.

Housings are made from high grade plastic or zinc, with zinc cams.

Wedgefix-6 connector is a special fastener without cam, simply to snap onto a pre-inserted dowel.

Applications



Titus System 6 is ideal for use in high volume production of case goods, closet and garage storage systems. Because no

edge boring is required, it is an excellent choice for manufacturing environments with limited drilling capacity.

Side-entry Drop-on


Side-entry insertion of shelf panel: from the side or from the top

Drop-on insertion of shelf panel: only from the top
Using drop-on connections allows for one-man installation




Angledriv feature

The angledriv feature on the cam allows for the angled position of the screwdriver with the locking action creating a tight and secure joint.




Outrigger/ Non outrigger

Outrigger





Non outrigger




Expando function

Expanding housings and dowels provide a tight joint.




Assembly


1. Press the housing into face board




2. Press the dowel into side panel



3. Assemble the panels



4. Tighten the joint



System 6

Quickfit-Expano

Expanding Dowels

- Available in Ø5mm, Ø8mm and Ø10mm for panel-to-panel, panel-to-hollow profile and back-to-back applications
- Suitable for applications with all Titus Ø20 and/or Ø25mm Expando-6 housings
- 'Klix' locking feature provides a strong, vibration proof connection
- Depth stop collar for accurate insertion






Technical and mounting details		D2	Drilling diameter for dowel thread	Item number	Dark grey	Black
Dowel		5	ØD2 x 12.5	06408 →	880	
	D2= Ø5mm	8	ØD2 x 12.5	06410 →	880	
	D2= Ø8mm					
 5000 Pcs	Made of zinc, plastic			06479 →	880	
Dowel Ø5 x 7.5 back-to-back applications						
 5000 Pcs	Made of zinc, plastic					

System 6

Quickfit-Expano

Dowels

- Available in various Ø3mm and/or Ø5mm thread forms for screw-in, knock-in and/or 'spiked' hole applications
- Suitable for applications with all Titus Ø20mm and/or Ø25mm Expano-6 housings
- 'Klix' locking feature provides a strong, vibration proof connection
- Dowels feature an integral skirt which acts as a positive stop during insertion

		C	Drilling depth for dowel thread	Item number	Zinc	Zinc plated
		Technical and mounting details				
Dowel Ø5	 		9	06401 →	885	
			8	06402 →	885	883
			11.5	06406 →	885	883
 2000 Pcs		Made of zinc or steel				
Dowel Ø5 x 11 knock-in				06403 →	885	
 2000 Pcs		Made of zinc				
Dowel M4 x 7	 			06405 →		883
 4500 Pcs		Made of steel				
Dowel Ø3 x 11.5	 			06495 →		883
 12500 Pcs		Made of steel				

 Inserts
Made of plastic


→ see page 1.62

System 6

Quickfit-Expano



Double-ended Dowels

- For 16mm, 18mm and 19mm board
- Suitable for applications with all Titus Ø20mm and/or Ø25mm Expano-6 housings
- 'Klix' locking feature provides a strong, vibration proof connection



Technical and mounting details

Double-ended dowel



B		Zinc
Panel thickness	Item number	
16	06414 →	885
18	06413 →	885
19	06416 →	885



2500 Pcs


Made of zinc

System 6

Quickfit-Expano



End Dowels

- For 16mm, 18mm and 19mm board
- Suitable for applications with all Titus Ø20mm and/or Ø25mm Expano-6 housings
- 'Klix' locking feature provides a strong, vibration proof connection



Technical and mounting details

End dowel



B	Panel thickness	Item number	Zinc
16	06412 →	885	
18	06411 →	885	
19	06415 →	885	



2500 Pcs
1000 PCS (06411)













Made of zinc

System 6

Quickfit-Expano

20mm Expanding Housing Non-outrigger

- Available in 15mm/16mm and 18mm/19mm versions for drop-on and/or side-entry applications
- Available in all-metal or plastic/metal options
- 'Klix' locking feature provides a strong vibration proof connection
- Compatible with all screw-in and Quickfit-6 dowels







e	B	D		Panel thickness	Drilling depth	Item number	Dark brown plastic	Nickel plated	Silver plastic	White plastic
Technical and mounting details										
Side-entry				7.75	15/16	12.5	06451 →		847	
				9.25	18/19	14	06453 →		847	
 500 Pcs	Made of zinc									
Side-entry				7.75	15/16	12.5	06435 →	831		861 877
				9.25	18/19	14	06437 →	831		861 877
 2500 Pcs	Made of plastic									
Drop-on				7.75	15/16	12.5	06447 →		847	
				9.25	18/19	14	06449 →		847	
 500 Pcs	Made of zinc									
Drop-on				7.75	15/16	12.5	06431 →	831		861 877
				9.25	18/19	14	06433 →	831		861 877
 2500 Pcs	Made of plastic									
<i>Other colours on request</i>										

System 6

Quickfit-Expano

20mm Expanding Housing Outrigger

- Available in 15mm/16mm and 18mm/19mm versions for drop-on and/or side-entry applications
- Available in all-metal or plastic/metal options
- 'Klix' locking feature provides a strong vibration proof connection
- Compatible with all screw-in and Quickfit-6 dowels




				e	B	D		Dark brown plastic	Black plastic	Nickel plated	White plastic
					Panel thickness	Drilling depth	Item number				
Technical and mounting details											
Side-entry											
				7.75	15/16	12.5	06459 →			847	
				9.25	18/19	14	06461 →			847	
 500 Pcs	Made of zinc										
Side-entry											
				7.75	15/16	12.5	06443 →			877	
				9.25	18/19	14	06445 →	831	835	877	
 1250 Pcs	Made of plastic			9.25	18/19	14	*06395 →	835	835	877	
Drop-on											
				7.75	15/16	12.5	06455 →			847	
				9.25	18/19	14	06457 →			847	
 500 Pcs	Made of zinc										
Drop-on											
				7.75	15/16	12.5	06439 →			835	
				9.25	18/19	14	06441 →	831	835	877	
 1250 Pcs	Made of plastic			9.25	18/19	14	*06397 →	835	835	877	
				Other colours on request *American market only							

System 6

Quickfit-Expano

Expanding Wedgefix Housing (no Inner Cam)


- Available in 12mm, 15mm/16mm and/or 18mm/19mm versions for Quickfit-6 and/or Standard Dowel applications
- Available in a variety of plastic colours
- Wedgefix-6 housing allows easy customer hand-assembly or factory automated insertion
- When used with Quickfit-6 dowels this provides a true toolless fastening system

		e	B	D							
					Panel thickness	Drilling depth	Item number	White	Black	Dark brown	Silver
											
Technical and mounting details											
For use with screw-in dowels											
											
											
		6	12	10	06470	→	877				861
		7.75	15/16	12.5	06473	→	877	835	831		861
		9.25	18/19	14	06465	→	877	835	831		861
		11	22	16	06464	→					861
Other colours on request											
 2500 Pcs		Made of plastic									
											
For use with Quickfit dowels											
											
											
		7.75	15/16	12.5	06471	→	877	835	831	861	
		9.25	18/19	14	06472	→	877	835	831	861	
Other colours on request											
 2500 Pcs		Made of plastic									

System 6



20mm Knock-in Housing Non-outrigger

- Available in 15mm/16mm and 18mm/19mm versions for drop-on and/or side-entry applications
- Available in all-metal or plastic/metal options
- 'Klix' locking feature provides a strong vibration proof connection
- Compatible with all screw-in and Quickfit-6 dowels



Technical and mounting details

Side-entry



	e	B	D			
	Panel thickness		Drilling depth	Item number	Silver plastic	White plastic
Side-entry	7.75	15/16	12.5	06381 ↗	861	877
	9.25	18/19	14	06385 ↗	861	877



Product available on American and Asian market only

Other colours on request

2500 Pcs

Made of plastic

Drop-on



7.75	15/16	12.5	06383 ↗	861	877
9.25	18/19	14	06387 ↗	861	877

Product available on American and Asian market only

Other colours on request

2500 Pcs

Made of plastic



Cover cap 06463






Made of plastic

System 6

Quickfit-Expano

25mm Heavy Duty Expanding Housing Non-outrigger

- Suitable for 12mm, 15mm/16mm and 18mm/19mm board for drop-on and/or side-entry applications
- All-metal
- 'Klix' locking feature provides a strong vibration proof connection
- Compatible with all System 6 Quickfit dowels

Technical and mounting details				D	e		
				Drilling depth	Drilling for dowel	Item number	Nickel plated
Side-entry				11	5	06953 ↗	847
							
							
Drop-on				11	5	06949 ↗	847
							
							




Dowels ↗ see page 1.47



System 6



Quickfit-Expando

25mm Heavy Duty Expanding Housing Outrigger

- Suitable for 12mm, 15mm/16mm and 18mm/19mm board for drop-on and/or side-entry applications
- Available in all-metal
- 'Klix' locking feature provides a strong vibration proof connection
- Compatible with all System 6 Quickfit dowels

Technical and mounting details		D	e			Nickel plated
Side-entry		Drilling depth	Drilling for dowel	Item number		
		11	5	06951 →	847	

			11	5	06951 →	847
--	--	---	----	---	---------	-----

			11	5	06947 →	847
---	---	---	----	---	---------	-----

	500 Pcs	Made of zinc				
---	---------	--------------	--	--	--	--


Dowels → see page 1.47


System 7

Heavy Duty Ø20mm Cam and Dowel

- Dowel available with Ø10mm eurothread and cam available in Ø20mm for a variety of panel thicknesses
- 'Klix' locking feature provides strong, vibration proof joint
- High strength product that eliminates the need for time consuming metal inserts

	B		
	Panel thickness	Item number	Zinc
Cam Ø20	18	05409 →	885

			
500 Pcs	Made of zinc	18 min	05410 → 885

			
500 Pcs	Made of zinc	18 min	05410 → 885







System 7

Heavy Duty Ø25mm Cam and Dowel



Cam not compatible with other dowels

- For 13mm and thicker panels
 - Cam drilling distance is 34mm
 - A flat slot screwdriver must be used for cam tightening
 - Decorative cover caps are available in different colours
 - Dowel for direct installation in 5mm holes

			Zinc plated blue
	Technical and mounting details	Item number 275-3096 →	Raw 600
	 		
 1000 Pcs	Made of zinc		
	 	275-2209 →	040
 1000 Pcs	Made of steel		
	 	275-2030 →	040
 1000 Pcs	Made of steel	275-4058 x=11 275-4035 x=13	



Cover cap
Made of plastic

→ see page 1.63



Inserts
Made of plastic

→ see page 1.62

System 7

Heavy Duty Dowels






Heavy duty only. Can't be used with other cams.

Technical and mounting details					Zinc plated blue	Brass plated black
	L	A	B	Item number		
End dowel	Overall length 52-B	Drilling distance A	Panel thickness B	275-2146 ↗	040	*085
Made of steel						
Dowel with circlip	76	34	20	275-0103 ↗	040	
	73	34	17	275-0106 ↗	040	
Made of steel						
Dowel without circlip	74	34	20	275-2057 ↗	040	
	76	34	18	275-2058 ↗	040	
Made of steel						

System 7











High Strength Connectors Contract Fix™ System

- High performance fastener
- Thread design gives repeatability
- Multi-drive recess
- Higher than average pull up


	Technical and mounting details	Item number	Zinc plated	Zinc
M6 Dowel 7x34		05971 →	883	
 1000 Pcs	Made of steel			
Housing cylinder 15x12		05960 →		885
 1000 Pcs	Made of zinc			
Grub screw		05917 →		885
 2500 Pcs	Made of zinc			
Inserts Made of zinc	→ see page 1.61			

Accessories for Connectors

Inserts

Technical and mounting details			Item number	Raw
$\varnothing 8 \times 9$	  	408-3166 →	600	
 100 Pcs	Made of zinc			
$\varnothing 9 \times 13$	  	408-3391 →	600	
 1000 Pcs	Made of zinc			
$\varnothing 9.5 \times 18$	  	408-3423 →	600	
 1000 Pcs	Made of zinc			
$\varnothing 12 \times 15$	  	408-3424 →	600	
 1000 Pcs	Made of zinc			

- Available in both zinc and plastic for use in various applications
- Suitable for use with various threaded dowels
- Suitable for use with various panel thicknesses
- Knock-in and screw-in versions available







	C	Drilling length for insert	Item number	Natural white	Natural
Ø10 x 13/M6 nut					
	20000 Pcs (275-4035)		275-4035 →	200	
	30000 Pcs (275-4058)	Made of plastic	275-4058 →	200	
Ø8 x 10/M4 nut			276-4036 →	200	
	50000 Pcs	Made of plastic			
Euro thread	twinstart thread		02182 →		846
	10000 Pcs	Made of plastic			

Accessories for Connectors

Cover Caps

- Available in a variety of colours
- Suitable for use with both pozi and hex cam drive features
- Suitable for use with various diameter cams
- Both domed and flat versions available

	X	Item number	Dark brown	Black	Light brown	Light grey															
																					
Cover cap Ø17																					
																					
 1000 Pcs	Made of plastic																				
Cover cap Ø17																					
																					
 1000 Pcs	Made of plastic																				
Cover cap Ø29.5																					
																					
 500 Pcs	Made of plastic																				
<p style="text-align: center;">X</p> <table border="1"> <thead> <tr> <th>Item number</th> <th>Dark brown</th> <th>Black</th> <th>Light brown</th> <th>Light grey</th> </tr> </thead> <tbody> <tr> <td>3.3 *01029 →</td> <td>834</td> <td>835</td> <td>867</td> <td>882</td> </tr> <tr> <td>2.5 277-4355 →</td> <td>370</td> <td>390</td> <td>330</td> <td>380</td> </tr> </tbody> </table>							Item number	Dark brown	Black	Light brown	Light grey	3.3 *01029 →	834	835	867	882	2.5 277-4355 →	370	390	330	380
Item number	Dark brown	Black	Light brown	Light grey																	
3.3 *01029 →	834	835	867	882																	
2.5 277-4355 →	370	390	330	380																	
<p><i>*American market only Other colours on request</i></p> <p><i>Suitable for cams with Pozi 2 recess</i></p>																					
<p>277-4225 → 370 390 330 380</p> <p><i>Other colours on request</i></p> <p><i>Suitable for cams with Hex recess</i></p>																					
<p>275-4034 → 370 390 330 380</p> <p><i>Other colours on request</i></p>																					

Glissando Soft Closing Systems

Glissando

Product Guide


Page

Glissando for Concealed Hinges

Add-on hinge soft closing solution

2.15

Glissando TL
Glissando TL 170




- effortless silent and safe door closing
- fits the hinge's standard drilling patterns
- easy retrofit installation
- adjustable to different door sizes and weights
- perfect door motion
- doesn't occupy additional space inside the cabinet

Stand-alone door soft closing solution

2.17

Glissando CR




- effortless silent and safe door closing
- easy retrofit installation
- adjustable to different door sizes and weights
- perfect door motion

Titusoft for Drawers

Stand-alone drawer
soft closing solution

2.19

Titusoft for wooden drawers
Titusoft for metal drawers




- self closing and soft closing in single mechanism
- safe drawer closing
- easy retrofit installation

Titusoft for Sliding Doors

Stand-alone sliding door soft closing solution

2.27

Titusoft SD100



- effortless silent and safe door closing
- intuitive mounting
- efficient damping
- smooth and controlled closing motion

Glissando

Soft Closing Range

How to Choose the Right Glissando?

Glissando TL
Glissando TL 170
Glissando CR

Titus Glissando soft closing system is available for the whole range of hinge applications. The user can choose between add-on hinge or stand-alone solutions.

Concealed hinges	Add-on hinge soft closing solutions		Stand-alone door soft closing solution
	Glissando TL	Glissando TL 170	Glissando CR
T-type 110	X		X
T-type 110/45°	X		
T-type 110/90°	X		
T-type 120			X
T-type 170		X	
S-type plus 110	X		X
S-type 110	X		X
S-type 110/15°	X		
S-type 110/24°	X		
S-type 110/30°	X		
S-type 110/45°	X		
S-type 110/90°	X		
S-type 170		X	X
B-type 110	X		X
B-type 110/30°	X		
B-type 110/45°	X		
B-type 110/90°	X		
B-type 170		X	X
Hinge Ø40			X

Glissando


Application

Glissando TL 'one for all'

T-type

- One item fits multiple applications
- Same item can be used on all crankings and angled hinges
- Adjustable damping enables perfect functioning on every door

- Designed to fit the concealed hinge cup
- Toolless mounting
- Suitable for different types of cabinets for kitchens, living rooms, bathrooms and other furniture



Glissando



Application

Glissando TL 'one for all'

S-type B-type

- One item fits multiple applications
- Same item can be used on all crankings and angled hinges
- Adjustable damping enables perfect functioning on every door

- Designed to fit the concealed hinge cup
- Toolless mounting
- Suitable for different types of cabinets for kitchens, living rooms, bathrooms and other furniture



Glissando

Number per Door and Positioning



Titus Glissando soft closing devices can not be used with free-swinging door hinges.
→ see page 3.24 for details


How Many Glissandos per Door?

Add-on hinge soft closing solution

Glissando TL
Glissando TL 170


Mount Glissando on the bottom hinge in case of 2 hinges on the door or on the middle hinge in case of 3 hinges on the door.

T-type



Recommended number per door and positioning

S-type, B-type




Recommended number per door and positioning

Stand-alone soft closing solution

Glissando CR

Mount Glissando CR on the hinged side of the cabinet on the top or bottom.



Recommended number per door and positioning


Glissando

Mounting

How to Mount Glissando?

Tool-less mounting

Glissando TL
Glissando TL 170



Simple toolless assembly: Insert Glissando into the holes on the hinge and press down with hand.


The tool-less ‘snap on’ version for reduced assembly time and flexibility of application. Glissando TL can be mounted at any time after furniture assembly so can be offered as a retro fit option by the installer.

Screw-on into the cabinet corner

Glissando CR

Glissando CR is mounted into the cabinet corner by using chipboard screws 20mm long.

Glissando dampers' discreet design enhances the look of the door and occupies minimal space in the cabinet interior.



Glissando

Damping Adjustment

How to Adjust Damping?


Add-on hinge soft closing solution

Glissando TL
Glissando TL 170

Glissando features quarter turn adjustment to provide optimal closing speed for any door dimensions and weight.


The damping function can be adjusted to fit different door weights which enables

- perfect door functioning
- use of the same type of Glissando for various doors



Adjustable damping zone

S-type, B-type




Turn towards '+' to increase and '-' to decrease the damping

Stand-alone soft closing solution

Glissando CR

Turn towards '+' to increase or towards '-' to decrease the damping.



Titus Hydraulic Damper

Efficient modular design

- Low number of assembly parts enables quick development of customised solutions
- Engineered for efficient and high precision manufacturing
- Wide range of applications




Wide operating scope

- High coefficient γ of Titus damper assures efficient damping at any closing speed
- Damping force can be easily adapted to customer needs

$$\gamma = \frac{F_H}{F_L}$$

F_H – damping force at slam speed (12mm/s)
F_L – damping force at slow speed (1mm/s)



Reliable damping and closing at any speed

Higher coefficient γ means reliable damping at high speed and ensures that the system will reach its final position even at very slow speed




Glissando

Soft Closing Systems for Hinges




'ConfidentClose'

- 1 Fast closing
- 2 Late start of deceleration action
- 3 Quiet landing with 'SoftTouch'



Tool-less mounting

- Reduced assembly time
- Flexible usage also as a retrofit option




Adjustable damping

- Consistent performance across a broad range of furniture doors of different dimensions and weights



Easy tool-less adjustment

- Intuitive adjustment procedure
- Controllable motion



'One for all'

- One item fits multiple applications
- Same item can be used on all crankings and angled hinges





'Titus Damper Inside'

- Titus proprietary multi-purpose damping technology
- Reliable and consistent damping

Glissando TL



Add-on Hinge Soft Closing Solution

For 110° hinges



Technical details

Glissando TL 'snap-on'
· T-type 110



200 Pcs



Made of steel and plastic

Glissando TL 'snap-on'
· S-type plus 110
· S-type 110
· B-type 110



200 Pcs


Made of steel and plastic




Hinge opening angle	Interaxis 45mm	Interaxis 48mm
Damping force	45mm	48mm
110°	Ø 35 9.5	Ø 35 6

110° ■ 45N	951-0X94-050
110° ■ 35N	951-0P59-050
110° ■ 60N	951-0P63-050

- Same item can be used on all crankings and angled hinges
- Designed to fit the concealed hinge cup and requires no extra space inside the cabinet
- Adjustable damping
- Toolless mounting




Adjustable damping zone




Turn towards '+' to increase and
'-' to decrease the damping

Mounting details


Toolless assembly




Insert Glissando TL into
the holes on the hinge



Press down



No additional drilling is required




Recommended number per
door and positioning

Glissando TL 170

Add-on Hinge Soft Closing Solution

For T-type 170, S-type 170 and B-type 170




Glissando TL 170
'snap-on'

Technical details

Hinge opening angle	Item number
170°	951-0F15-650




Soft closing mechanism



Box content
100 pcs soft closing mechanisms
100 pcs striking plates




Striking plate



Made of steel and plastic

- Gentle and reliable soft closing on doors with wider opening angle
- Fits perfectly 45/9.5mm, 48/6mm and 52/5.5mm hinge cups
- Furniture consumers' preferred 'ConfidentClose'
- Tool free mounting


Damping adjustment




Turn towards '+' to increase and '-' to decrease the damping

Mounting details


Toolless mounting




Insert Glissando TL 170 into the holes on the hinge cup




Press down



Place the striking plate into the hole on the hinge arm



Press down




Recommended number per door and positioning

Glissando CR

Stand-alone Door Soft Closing System

For full overlay and half overlay concealed hinges




Glissando CR
for full overlay
hinges



Technical details

Hinge opening angle	Cranking	Item number	White	Grey	Beige
110°	0mm	972-0X19 →	350	380	360


*Fixing screw included in a set



100 Pcs

Made of plastic


Glissando CR
for half overlay
hinges



110°	9mm	972-0X34 →		380	
------	-----	------------	--	-----	--


- Intuitive ‘place and fix’ installation in the corner of the cabinet
- Tool-less damping adjustment
- One item for a wide range of doors
- Reliable performance

Damping adjustment




Turn towards '+' to increase and towards '-' to decrease the damping

Mounting details




Further explanations → go to


http://www.youtube.com/watch?v=8-uWs_z2d0s



Mount Glissando CR on the hinged side of the cabinet




One screw fixing




Further explanations → go to

http://www.youtube.com/watch?v=8-uWs_z2d0s




Mount Glissando CR on the hinged side of the cabinet



One screw fixing



The functioning of Glissando CR depends on the hinge's closing force. A trial mounting is always recommended.





Recommended number per door and positioning

Titusoft WD

Soft Closing System for Wooden Drawer

For wooden drawer
with roller runners




Technical details

Titusoft WD


	Item number	Grey	White	Zinc plated blue
Titusoft mechanism	973-0X35 →	380		
Activator	973-4451 →	380	350	



Titusoft mechanism



Activator



Bag of 1
973-0X35-380-K2 120 Bags

- 1 Titusoft mechanism
- 1 activator
- 2 screws Ø3.5mm x 20mm
- 2 screws Ø3.5mm x 12mm
- 1 Mounting instruction sheet

Bag of 2
973-0X35-380-K1 80 Bags

- 2 Titusoft housings
- 2 activators
- 4 screws Ø3.5mm x 20mm
- 4 screws Ø3.5mm x 12mm
- 1 Mounting instruction sheet




250 Pcs

Made of plastic

- Works with most roller runner drawer slides
- Easy, intuitive mounting
- Smooth soft closing action independent of drawer hardware
- Optimal closing speed
- Non handed design


Capacity chart



Mount 1 or 2 Titusoft mechanisms depending on drawer weight and width


Mounting details

1.




Position the Titusoft mechanism on the top of the drawer slide

2.




Fix with 2 screws L=20mm

3.



4.



Fix with 2 screws L=12mm

1. Rest the activator against the drawer front
2. Align the vertical position of the activator with the top of the Titusoft mechanism and mark the screw locations



Further explanations → go to



<http://www.youtube.com/watch?v=U3aS2r6KC6k>

A trial mounting is always recommended. Please contact Titus Group or your local distributor for further technical assistance.

Titusoft FF

For wooden drawer
with roller runners

Soft Closing System
for Face Frame Cabinets
with Wooden Drawer



Technical details

Titusoft FF

Titusoft
mechanism

Activator

Item number


973-0M99 →

380

973-4451 →

380 350

Grey
White
Zinc plated
blue



Titusoft mechanism


Bag of 1

973-0M99-380-K1 300 Bags

- 1 Titusoft mechanisms
- 1 activators, grey
- 2 screws Ø3.5mm x 25mm
- 2 screws Ø3.5mm x 12mm
- 1 mounting instruction sheet



Activator




250 Pcs

Made of plastic

- Easy, intuitive mounting
- Universal application will fit most standard drawers
- Smooth soft closing action independent of drawer hardware
- Non handed design


Capacity chart



Mount 1 or 2 Titusoft mechanisms depending on drawer weight and width


Mounting details

1.




Position the Titusoft on the top of a drawer slide

2.




Screw the Titusoft mechanism to the face frame

3.



Align the activator with the top of the Titusoft mechanism and fix with two screws

4.



Fix with 2 (3) screws L=12mm



Further explanations → go to



<http://www.youtube.com/watch?v=jQ8DiMlkxbg>

A trial mounting is always recommended. Please contact Titus Group or your local distributor for further technical assistance.

Titusoft MD

Soft Closing System for Metal Box

For metal boxes



Titusoft MD



Titusoft mechanism



Activator




Mounting jig

250 Pcs


Made of plastic

Technical details

Retrofit mounting






Factory mounting (system holes)



- 'One-for-all' soft closing for single skin metal boxes
- Allows for easy factory mounting or retrofit application
- Intuitive positioning
- Preserve the life-time of the drawer

Capacity chart

**Mounting details****Retrofit mounting****Factory mounting**

Further explanations → go to


<http://www.youtube.com/watch?v=Qplq8uKGbng>

A trial mounting is always recommended. Please contact Titus Group or your local distributor for further technical assistance.

Titusoft SD100

Add-on Damper for Sliding Door

For top running sliding door systems



Titusoft SD100

Item number

Grey

[973-9018 →](#)

380



The system consists of
the following components

Quantity for
2 door cabinet


Standard component

Titusoft SD100 mechanism

2 pcs



Technical details



Customized components to suit
the customer's sliding door system

Base



4 pcs

Stopper



2 pcs

Activator for
internal door




1 pc

Activator for
external door



1 pc

Drilling details



Accessories

Screws

Countersunk screw D4x40mm
Countersunk screw D4x25mm
Chipboard screw Ø4x16mm
Euroscrew Ø6.3x15mm

4 pcs

4 pcs

3 pcs

2 pcs

1 pc

Mounting
instructions



32 Sets

- 'ConfidentClose'
- Intuitive mounting
- Non-handed design
- Efficient damping on different door sizes
- Smooth and controlled closing motion




Up to 50kg per door

Mounting details


Non-handed design




Mounting positions




Titusoft SD100 mechanism position



* Activator for internal door position



* Activator for external door position




Click to engage




* Activators are customized to suit specific sliding door system. Please contact your Titus Group representative for further information.

Concealed Hinges

Titus Hinges





'ConfidentClose'

The hinge is designed to provide consumer preferred way of soft closing action.

- Fast closing
- Late start of deceleration action
- Quiet landing with 'SoftTouch'

Based on independent consumer researches.

'One-for-All'

- Damping on the hinge cup
- Damper, positioned transversal to the hinge cup allows for easy introduction of various hinge versions
- Damped and non-damped version on one mounting plate platform

Adjustable Damping

Flexibility to tune performance to wide range of applications

- Consistent performance over a wide range of doors of different sizes and weights
- Easy accessible button for intuitive and quick adjustment

Titus Damper Inside

- Efficient damping at any closing speed
- Reliable closing
- Damping force consistency

A Comprehensive Range



T-type hinge



Titus New Generation hinge for quick furniture assembly and consistent performance on wide range of doors
'3Way' 'snap-on' mounting
Highly tolerant
Adjustable damping
'ConfidentClose'

Numerous application possibilities

- for simpler cabinet design
- for demanding high quality furniture of larger heights and weights

S-type hinge



Simple and quick 'snap-on' mounting system
Easy assembly and disassembly
Adjustable damping
'ConfidentClose'
Push to open for handleless furniture

B-type hinge



Reliable slide-on mounting system
Simplicity in use
Adjustable damping
'ConfidentClose'
Reliable door closing

Opening angle	Door thickness	Cranking	Door tab K	Mounting mode	Mounting plate type	Mounting plate height	Soft closing options	Durability (cycles)	Page
110° 120° 170°	15-26mm	0mm 5mm 9mm 17mm angled	3-6mm	'3Way' snap-on	cruciform linear for face frame	0mm 1mm 2mm 3mm 4mm	Damping integrated in the hinge cup	100.000	1.26
							Glissando add-on or stand-alone damping solutions		
110° 170°	16-24mm	0mm 9mm 15mm angled	3-5mm	snap-on	cruciform for face frame	0mm 1mm 2mm 3mm	Damping integrated in the hinge cup	80.000	1.53
							Glissando add-on or stand-alone damping solutions		
110° 170°	16-24mm	0mm 9mm 15mm angled	3-5mm	slide-on	cruciform	0mm 1mm 2mm 3mm	Damping integrated in the hinge cup	80.000	1.101
							Glissando add-on or stand-alone damping solutions		

Concealed Hinges

Product Guide

	Cranking	Opening angle	Cup type	Page
T-type				
T-type Glissando 110	0mm 5mm 9mm 17mm	110° 110° 110° 110°	for wood door for wood door for wood door for wood door	3.27 3.27 3.29 3.29
T-type Glissando 120	0mm 9mm	120° 120°	for wood door for wood door	3.31 3.31
T-type Glissando 110/45°	45°, 17mm	110°	for wood door	3.33
T-type Glissando 110/90°	90°, 17mm	110°	for wood door	3.35
T-type 110	0mm 5mm 9mm 17mm	110° 110° 110° 110°	for wood door for wood door for wood door for wood door	3.37 3.37 3.39 3.39
T-type 120	0mm 9mm	120° 120°	for wood door for wood door	3.41 3.41
T-type 110/45°	45°, 17mm	110°	for wood door	3.43
T-type 110/90°	90°, 17mm	110°	for wood door	3.45
T-type 170	0mm 5mm 9mm	170° 170° 170°	for wood door for wood door for wood door	3.47 3.47 3.49
T-type mounting plates				3.51
S-type				
S-type-i plus 110	0mm 9mm	110° 110°	for wood door for wood door	3.57 3.57
S-type-i 110	0mm 9mm 15mm	110° 110° 110°	for wood door for wood door for wood door	3.59 3.59 3.59
S-type-i 110/30°	30°, 9mm	110°	for wood door	3.61

	Cranking	Opening angle	Cup type	Page
S-type-i 110/45°	45°, 9mm	110°	for wood door	3.63
	45°, 18mm	110°	for wood door	3.65
S-type-i 110/90°	90°, 18mm	110°	for wood door	3.67
S-type plus 110	0mm	110°	for wood door	3.69
	9mm	110°	for wood door	3.69
S-type plus 110 Touch opening	0mm	110°	for wood door	3.71
	9mm	110°	for wood door	3.71
S-type 110	0mm	110°	for wood door	3.73
	9mm	110°	for wood door	3.73
	15mm	110°	for wood door	3.73
S-type 110/-15°	-15°, 0mm	110°	for wood door	3.75
S-type 110/15°	15°, 0mm	110°	for wood door	3.77
S-type 110/24°	24°, 9mm	110°	for wood door	3.79
S-type 110/30°	30°, 9mm	110°	for wood door	3.81
S-type 110/45°	45°, 9mm	110°	for wood door	3.83
	45°, 18mm	110°	for wood door	3.85
S-type 110/90°	90°, 18mm	110°	for wood door	3.87
S-type 110	0mm	110°	for aluminium frame door	3.89
S-type 170	0mm	165°	for wood door	3.91
	9mm	165°	for wood door	3.93
S-type for pie-cut corner cabinet			for wood door	3.95
S-type mounting plates				3.97

B-type

B-type-i 110	0mm	110°	for wood door	3.105
	9mm	110°	for wood door	3.105
	15mm	110°	for wood door	3.105
B-type-i 110/30°	30°, 9mm	110°	for wood door	3.107
B-type-i 110/45°	45°, 9mm	110°	for wood door	3.109

	Cranking	Opening angle	Cup type	Page
	45°, 18mm	110°	for wood door	3.111
B-type-i 110/90°	90°, 18mm	110°	for wood door	3.113
B-type 110	0mm	110°	for wood door	3.115
	9mm	110°	for wood door	3.115
	15mm	110°	for wood door	3.115
B-type 110/30°	30°, 9mm	110°	for wood door	3.117
B-type 110/45°	45°, 9mm	110°	for wood door	3.119
	45°, 18mm	110°	for wood door	3.121
B-type 110/90°	90°, 0mm	110°	for wood door	3.123
	90°, 18mm	110°	for wood door	3.123
B-type 110	0mm	165°	for aluminium frame door	3.125
B-type 170	0mm	165°	for wood door	3.127
	9mm	165°	for wood door	3.129
B-type for pie-cut corner cabinet			for wood door	3.131
B-type flap door hinge	0mm	90°	for wood door	3.133
B-type mounting plates				3.135
Hinge Ø40	0mm	93°	for wood door	3.139
	10mm	93°	for wood door	3.139
	18mm	93°	for wood door	3.141
	22mm	93°	for wood door	3.141
Hinge Ø40 mounting plates				3.143

Other Hinges

Wide angle hinge and mounting plate	270°	for wood door	3.145
Refrigerator cabinet door hinge	110°	for wood door	3.147

Accessories

Push latch			3.149
Cover caps			3.151

Concealed Hinges


Door Overlay

How to Achieve the Desired Door Overlay?


By choosing the hinge of appropriate cranking

Concealed hinges with specific hinge arms are available for different door overlays. The most common overlays are:

■ Cabinet side
■ Door



1. Full overlay
Use a hinge with 0mm cranking



2. Partial overlay for double doors
Use a hinge with 5mm or 9mm cranking




3. Inset door
Use a hinge with 15mm or 17mm cranking

By choosing the mounting plates of appropriate thickness

To achieve the desired overlay (x) while using a determined drilling distance (K), a mounting plate of appropriate

thickness (D) must be chosen from the enclosed table or calculated with given formula.




x	4	5	6	7	8	9
3	3	2	1	0		
4		3	2	1	0	
5			3	2	1	0

D=4+K-x

By choosing the appropriate drilling distance K



To achieve the desired door overlay (x) while using a determined mounting plate thickness (D), an appropriate drilling distance K must be chosen.



x	4	5	6	7	8	9
0			3	4	5	
1			3	4	5	
2			4	5		
3	3	4	5			K

Through side adjustment


The side adjustment is made by rotating the appropriate screw on the hinge arm.



Door clearance and gap

The door clearance ($F \geq F_{\min}$) and gap (Z) represent the minimal necessary space needed for the correct opening and closing of the door. The minimal required values depend on the cup drilling distance (K), door thickness (V)

and the type of hinge. The minimum clearance scale can be found on product pages → see Door clearance chart. When using hinges with partial overlay the door clearance must be twice as large ($F \geq 2F_{\min}$).



V	16	17	18	19	20	21	22
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5
4	0.3	0.5	0.7	0.9	1.2	1.6	2.1
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0

Gap $Z_{\min}=0$

Concealed Hinges


Hinge Cup Types

How to Mount the Hinge on the Door?

There are cup type symbols listed on product pages beside item numbers. Below you can find their explanation.


No pre-mounting

The hinge is fixed on the door with two screws.
3mm pilot holes recommended.




Easy-Fix time saving system

Quarter turn fixing for 8mm holes (interaxis 45/9.5) or 10mm holes (interaxis 48/6 and 52/5.5).



Machine insertion ready hinge cup

Premounted dowels suitable for machine insertion into 8mm holes (interaxis 45/9.5) or 10mm holes (interaxis 48/6 and 52/5.5)



Pre-mounted expando dowels


Pre-mounted expanding dowels with triple-start screw for fast fixing, suitable for 8mm holes.






Hinge cup with pre-mounted euro screws

Pre-mounted euro screws for 5mm holes.
Where not specified otherwise, euro screws are 13mm long.




Hinge cup with pre-mounted chipboard screws

Pre-mounted chipboard screws.
3mm pilot holes recommended.



Aluminium frame screw-on hinge cup

The hinge is fixed onto a specific drilling on the aluminium frame.



Concealed Hinges

Boring Details

Drilling Patterns for Hinge Cup

Interaxis 45mm, 48mm and 52mm*

- T-type
- S-type
- B-type

*Available on special request → see page 3.9

Hinge cup type	Interaxis 45mm	Interaxis 48mm	Interaxis 52mm
Screw-on ready			
Premounted chipboard screws			
Machine insertion ready			
Premounted expando dowels			
Easy-fix system			
Premounted euro screws			

Interaxis is the distance between two holes for fixing screws on the hinge cup.

Concealed Hinges

Mounting Plate Type

How to Fix the Mounting Plate on the Cabinet Side?

There are mounting plate type symbols listed on product pages beside item numbers. Below you can find their explanation.

No pre-mounting, chipboard screw ready

The mounting plate is fixed with two chipboard screws or equivalent.
3mm pilot holes recommended.




No pre-mounting, euro screw ready

Fixing with 6.3mm euro screws into pre-drilled 5mm holes. To choose appropriate head and length for use with this mounting plate is recommended.




Machine insertion ready

Pre-mounted dowels for machine insertion into 10mm holes.




Pre-mounted euro screws

Euro screws for 5mm holes are pre-mounted on the mounting plate. Available lengths: 11mm, 13mm and 15mm



Pre-mounted expanding dowels

Pre-mounted expanding dowels for 5mm holes. Available lengths: 7.5mm and 10.5mm



Pre-mounted chipboard screws

The mounting plate is fixed with two pre-mounted chipboard screws. 3mm pilot holes recommended.



Concealed Hinges

Hinge-to-plate Mounting




How to Assemble the Hinge and the Mounting Plate?

T-type '3Way' 'snap-on'




'3Way' 'snap-on' mounting for intuitive hinge-to-plate assembly in three directions:

- from the hinge arm front
- from the hinge arm rear
- from the top



front assembly






rear assembly



top assembly




disassembly:
for disassembly press rear button on the hinge arm.



S-type 'snap-on'

The door is assembled on the cabinet side simply by positioning the two hooks under the hinge arm on the outer part of the mounting plate and pressing gently on the rear part of the hinge arm.


For disassembly press the rear button on the hinge arm.



B-type slide-on

The hinge is assembled by sliding the hinge arm over the mounting plate. The hinge adjustment screw must fit into the groove on the mounting plate.

After adjusting the door depth, the mounting procedure is finished by tightening the fixing screw.




Key-hole

- Wide angle hinge
- Refrigerator cabinet door hinge

The hinge is assembled on the mounting plate by inserting the fixing screw on the appropriate hole on the hinge arm.

After adjusting the door depth, the mounting procedure is finished by tightening the fixing screw.



Concealed Hinges

Loadings




Use the appropriate number of hinges so that the door height or weight does not exceed that shown below.

How Many Hinges per Door?


Check the enclosed specifications for the number of required hinges per door by considering door height and weight.

Concealed hinges with Ø 35mm hinge cup diameter

- T-type
- S-type
- B-type
- Other hinges



- T-type Glissando
- S-type-i
- B-type-i



Hinges with integrated damping can be combined with non-damped hinges from standard hinge range. A trial mounting is always recommended.


Concealed Hinges

Adjustment



Adjustment range can be found
on the product pages.

Side Adjustment






The side adjustment aligns the door with the side of the cabinet.

By rotating the appropriate screw

T-type
S-type
B-type

The side adjustment is made by rotating the screw on the hinge arm.



Adjustment range



By temporarily loosening the fixing screw

- Wide angle hinge

For the side adjustment:

- Release the fixing screw
- Make the necessary adjustment by rotating the appropriate screw
- Tighten the fixing screw

Without releasing the fixing screw no side adjustment is possible.




Adjustment range

Concealed Hinges

Adjustment

Height Adjustment




Height adjustment is necessary to achieve optimal vertical door position.



By rotating the cam adjuster

The height adjustment is made by rotating the cam adjuster on the mounting plate.



T-type with cam adjustable cruciform mounting plate



T-type with cam adjustable horizontal mounting plate




S-type with cam adjustable cruciform mounting plate



By releasing the screw slot

- T-type and S-type with cruciform mounting plate
- B-type
- Wide angle hinge


For height adjustment the two mounting plate fixing screws have to be temporarily released while making the manual adjustment.



Concealed Hinges

Adjustment

Depth Adjustment





The system enables easy adjustment of the gap between door and cabinet.



By rotating the cam adjuster

Rotate the cam adjuster on the hinge arm.

- T-type




- S-type plus




By releasing the fixing or adjustment screw

- S-type
- B-type

The depth adjustment is made by temporarily releasing the adjustment screw (S-type) or fixing screw (B-type, Hinge Ø40). After the adjustment is made the screw has to be re-tightened.



Adjustment range




Door Closing Type

There are two door closing systems:

Concealed hinges with self-closing angle

- T-type
- S-type
- B-type


The self-closing angle is the point from which the door will close by itself, without user assistance. The mechanism starts closing the door from a 14° to 25° angle, depending on the concealed hinge type. From that point to the maximum opening angle the door remains in an open position.



Free-swinging door hinges*

- all series

Optionally most of Titus concealed hinges can be supplied without self-closing mechanism. These hinges may be ordered upon request. Soft closing devices can not be used with free-swinging door hinges.



* Available upon special request → see page 3.9


Concealed Hinges

Adjustment

Damping Adjustment


T-type Glissando

The damping action can be adjusted to fit different door weights and sizes which enables perfect door functioning.




Damping is factory pre-set to the medium damping value.
Turn towards '+' to increase and '-' to decrease the damping.


S-type-i plus series S-type-i series B-type-i series



The damping reduction switch in a pre-set position.




- To decrease the damping
1. Lift the damping activator.
2. Slide the damping reduction switch to opposite position.



To increase the damping, slide the damping reduction switch back to the factory pre-set position.

Damping force change

The damping reduction switch adjusts the damping. Example shows the damping change in case of two hinges on door.




Key Design Choices

'ConfidentClose'

The hinge is designed to provide consumer preferred way of soft closing action.

Based on results of Titus researches made in UK, Germany and Slovenia



'One-for-all' efficiency principle

Damping on the hinge cup
Damper, positioned transversal to the hinge cup allows for easy introduction of various hinge versions


Damped and non-damped version on one mounting plate platform



Adjustable damping

Flexibility to tune performance for all applications

- Consistent performance over a wide range of doors of different sizes and weights
- Easy accessible adjustment button for intuitive and quick adjustment







Adjustable damping zone and force

Titus Damper Inside

- Efficient damping at any closing speed
- Reliable closing
- Damping force consistency



T-type Hinges



Easy door installation even in cases of 4-5 hinges per door


- Easy and quick assembly and disassembly
- Flexibility for the furniture user
- Tight hinge-to-plate joint improves hinge stability and reduces door sag

Highly tolerant

- Efficient performance in marginal values of tolerances
- Reliable door closing in case of accidental misalignment
- 'ConfidentClose' assured

Rigidity

- Hinge-to-plate attachment assures stability and rigidity
- Smooth performance



Adjustable damping

- Consistent performance on doors of different dimensions and weights
- Intuitive adjustment procedure

'Titus Damper Inside'




- Titus proprietary multi-purpose damping technology
- Reliable and consistent life-long damping
- No rebounce

Proven Glissando concept

- Damper is positioned transversal on the hinge cup
- Reliable performance

T-type Glissando 110

For wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

110°
35mm
11.7mm
'3Way' snap-on





Technical details

Cup type	Interaxis 45mm	Interaxis 48mm
	Item number	Item number
	701-0AT0-054	701-0AS0-054

Cranking

0mm





150 Pcs

Made of steel

Drilling patterns for hinge cups → see page 3.15

Cranking

5mm



150 Pcs

Made of steel

Drilling patterns for hinge cups → see page 3.15

Mounting plates



Cam adjustable cruciform mounting plate
→ see page 3.51



Cruciform mounting plate
→ see page 3.53




Cam adjustable horizontal mounting plate
→ see page 3.51



Face frame adapter plate
→ see page 3.53

Hinge cup screws
If not pre-mounted



820-6328-050


10000 Pcs

Legend of hinge cup symbols

Screw-on ready screws

Machine insertion ready


Easy-fix system




Accessories
 Titus

Cover caps for hinge arm
→ see page 3.151

Damping adjustment





Door adjustment

Side
adjustment
+3/-1mmHeight
adjustment
+2/-2mmDepth
adjustment
+4/1mm

For further explanation → see page 3.25

For further explanation → see pages 3.20-3.23



Mounting
detailsMounting plate
drilling distance

Mounting plate thickness table

For further explanation → see page 3.11


x	13	14	15	16	17	18	19	
3	3	2	1	0				D
4	4	3	2	1	0			
5		4	3	2	1	0		
6			4	3	2	1	0	

$$D = 13 + K - x$$

Drawing show application on
D=0mm thick mounting plateDrawing show application on
D=0mm thick mounting plate

x	8	9	10	11	12	13	14	
3	3	2	1	0				D
4	4	3	2	1	0			
5		4	3	2	1	0		
6			4	3	2	1	0	

$$D = 8 + K - x$$




Door clearance at R=1mm
For further explanation → see page 3.12

V	16	17	18	19	20	21	22	23	24	25	26	F _{MIN}
3	0.5	0.7	0.8	1	1.2	1.5	1.7	2.1	2.8	4.1	5.5	
4	0.4	0.7	0.8	1	1.2	1.5	1.7	2.1	2.3	3.1	4.5	
5	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	3.5	
6	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	2.9	

Gap Z_{MIN}=0

T-type Glissando 110

For wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

110°
35mm
11.7mm
'3Way' snap-on






Technical details

Cup type	Interaxis 45mm	Interaxis 48mm
	Item number	Item number
	701-0CT0-054 701-0CT1-054 701-0CT4-054	701-0CS0-054 701-0CS1-054 701-0CS4-054

Cranking

9mm





150 Pcs

Made of steel

Drilling patterns for hinge cups → see page 3.15

Cranking

17mm



150 Pcs

Made of steel

Drilling patterns for hinge cups → see page 3.15

Mounting plates



Cam adjustable cruciform mounting plate
→ see page 3.51



Cruciform mounting plate
→ see page 3.53




Cam adjustable horizontal mounting plate
→ see page 3.51



Face frame adapter plate
→ see page 3.53

Hinge cup screws
If not pre-mounted



820-6328-050

10000 Pcs

Accessories



Cover caps for hinge arm
→ see page 3.151

Legend of hinge cup symbols



Screw-on
ready
screws




Machine
insertion
ready




Easy-fix
system



Damping adjustment





Door adjustment

Side
adjustment
+3/-1mmHeight
adjustment
+2/-2mmDepth
adjustment
+4/-1mm



For further explanation → see page 3.25

For further explanation → see pages 3.20-3.23

Mounting
detailsMounting plate
drilling distanceMounting plate thickness table
For further explanation → see page 3.11


	4	5	6	7	8	9	10	
x	3	2	1	0				
K	4	3	2	1	0			
5		4	3	2	1	0		
6			4	3	2	1	0	D

$D = 4 + K - x$

Drawing show application on
 $D=0\text{mm}$ thick mounting plateDrawing show application on
 $D=2\text{mm}$ thick mounting plate

	16	17	18	19	20	21	22	23	24	
V	3	0	0	0	1	1	1	1	2	
K	4	1	1	1	1	2	2	2	3	
5	2	2	2	2	3	3	3	3	4	
6	3	3	3	3	4	4	4	4	4	D

$D = -4 + K + F$




Door clearance at $R=1\text{mm}$
For further explanation → see page 3.12

V	16	17	18	19	20	21	22	23	24	25	26	
3	0.5	0.7	0.8	1	1.2	1.5	1.7	2.1	2.8	4.1	5.5	
4	0.4	0.7	0.8	1	1.2	1.5	1.7	2.1	2.3	3.1	4.5	
K	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	3.5	
5	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	3.5	
6	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	2.9	F_{MIN}

Gap $Z_{MIN}=0$

T-type Glissando 120

For wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

120°
35mm
11.9mm
'3Way' snap-on






Technical details

Cup type	Interaxis 45mm	Interaxis 48mm
	45 9.5 Ø 35	48 6 Ø 35
	Item number	Item number
	701-0UT0-054	701-0US0-054

Cranking

0mm






150 Pcs

Made of steel

Cranking

9mm



150 Pcs

Made of steel

Mounting plates



Cam adjustable cruciform mounting plate
→ see page 3.51



Cruciform mounting plate
→ see page 3.53




Cam adjustable horizontal mounting plate
→ see page 3.51



Face frame adapter plate
→ see page 3.53

Hinge cup screws
If not pre-mounted



820-6328-050

10000 Pcs

Accessories



Cover caps for hinge arm
→ see page 3.151

Legend of hinge cup symbols




Screw-on
ready
screws




Machine
insertion
ready




Easy-fix
system



Damping adjustment



Door adjustment



Side
adjustment
+3/-1mm


Height
adjustment
+2/-2mm

Depth
adjustment
+2.5/-2.5mm



For further explanation → see page 3.25

For further explanation → see pages 3.20-3.23

Mounting details



Mounting plate drilling distance






Mounting plate thickness table

For further explanation → see page 3.11

	x	13	14	15	16	17	18	19	D
K	3	3	2	1	0				
	4	4	3	2	1	0			
	5		4	3	2	1	0		
	6			4	3	2	1	0	

$$D = 13 + K - x$$

Drawing show application on
D=0mm thick mounting plate




	x	4	5	6	7	8	9	10	D
K	3	3	2	1	0				
	4	4	3	2	1	0			
	5		4	3	2	1	0		
	6			4	3	2	1	0	

$$D = 4 + K - x$$

Drawing show application on
D=0mm thick mounting plate

Door clearance at R=1mm
For further explanation → see page 3.12





V	16	17	18	19	
K	3	1.1	0.4	0	0
	4	2	1.4	0.7	0.1
	5	3	2.3	1.6	1

$$\text{Gap } Z_{\text{MIN}} = 2$$

T-type Glissando 110/45°

45° angled application for wood doors





- Opening angle 110°
- Drilling diameter for hinge cup 35mm
- Drilling depth 11.7mm
- Hinge on plate mounting system '3Way' snap-on



Technical details

Cranking

17mm



150 Pcs

Cup made of steel, arm made of zinc

	Interaxis 45mm	Interaxis 48mm
Cup type	Item number	Item number
	701-0B08-054	701-0B10-054
	701-0C78-054	701-0C80-054
	701-0C54-054	701-0C56-054

Drilling patterns for hinge cups → see page 3.15

Mounting plates



Cam adjustable cruciform mounting plate
→ see page 3.51



Cruciform mounting plate
→ see page 3.53




Cam adjustable horizontal mounting plate
→ see page 3.51



Face frame adapter plate
→ see page 3.53

Hinge cup screws *If not pre-mounted*



820-6328-050

10000 Pcs

Legend of hinge cup symbols

Screw-on ready
← screws

Machine insertion ready

Easy-fix system




Accessories




Cover caps for hinge arm
→ see page 3.151

Damping adjustment





Door adjustment




For further explanation → see page 3.25

For further explanation → see pages 3.20-3.23

Mounting details






Mounting plate drilling distance



Mounting plate thickness table


For further explanation → see page 3.11

P	0	0.5	1	1.5	2	2.5	3	3.5	4
K									
3	2		1		0				
4	3	2		1		0			
5		3	2		1		0		
6	4		3	2		1	0		D

Drawings show application on
D=0mm thick mounting plateDrawings show application on
D=0mm thick mounting plate

L=45 for thickness D=0
 L=44 for thickness D=1
 L=43 for thickness D=2
 L=42 for thickness D=3
 L=41 for thickness D=4

Door clearance at R=1mm
For further explanation → see page 3.12





V	16	17	18	19	20	21	22	23	24	25	26	F _{MIN}
K												
3	0.5	0.7	0.8	1	1.2	1.5	1.7	2.1	2.8	4.1	5.5	
4	0.4	0.7	0.8	1	1.2	1.5	1.7	2.1	2.3	3.1	4.5	
5	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	3.5	
6	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	2.9	

Gap Z_{MIN}=0

T-type Glissando 110/90°

For wood door cabinets with blind panels



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

110°
35mm
11.7mm
'3Way' snap-on





Technical details

	Interaxis 45mm	Interaxis 48mm
Cup type		
Item number	701-0A96-054	701-0A98-054
Item number	701-0D36-054	701-0D38-054
Item number	701-0D30-054	701-0D32-054

Cranking

17mm



150 Pcs

Cup made of steel, arm made of zinc

Mounting plates



Cam adjustable cruciform mounting plate
→ see page 3.51



Cruciform mounting plate
→ see page 3.53




Cam adjustable horizontal mounting plate
→ see page 3.51



Face frame adapter plate
→ see page 3.53

Hinge cup screws *If not pre-mounted*



820-6328-050

10000 Pcs

Accessories


Cover caps for hinge arm
→ see page 3.151

Legend of hinge cup symbols


Screw-on ready screws

Machine insertion ready


Easy-fix system



Damping adjustment







Door adjustment



For further explanation → see page 3.25

For further explanation → see pages 3.20-3.23

Mounting details




Drawings show application on
D=2mm thick mounting plateDrawings show application on
D=2mm thick mounting plateMounting plate
drilling distanceDoor clearance at R=1mm
For further explanation → see page 3.12

V	16	17	18	19	20	21	22	23	24	25	26	F _{MIN}
K	3	0.5	0.7	0.8	1	1.2	1.5	1.7	2.1	2.8	4.1	5.5
	4	0.4	0.7	0.8	1	1.2	1.5	1.7	2.1	2.3	3.1	4.5
	5	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	3.5
	6	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	2.9

Gap Z_{MIN}=0

T-type 110

For wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

110°
35mm
11.7mm
'3Way' snap-on






Technical details

	Interaxis 45mm	Interaxis 48mm
Cup type	45	48
Item number	702-0AK0-054	702-0AL0-054
	Ø 35	Ø 35

Cranking

0mm






150 Pcs

Made of steel

Cranking

5mm



150 Pcs

Made of steel

Mounting plates



Cam adjustable cruciform mounting plate
→ see page 3.51



Cruciform mounting plate
→ see page 3.53




Cam adjustable horizontal mounting plate
→ see page 3.51



Face frame adapter plate
→ see page 3.53

Hinge cup screws
If not pre-mounted



820-6328-050

10000 Pcs

Accessories



Cover caps for hinge arm
→ see page 3.151



Push latch
→ see page 3.149

Legend of hinge cup symbols




Screw-on
ready
screws




Machine
insertion
ready





Easy-fix
system



Door adjustment



Side
adjustment
+3/-1mmHeight
adjustment
+2/-2mmDepth
adjustment
+4/-1mm

For further explanation → see pages 3.20-3.23

Mounting
detailsMounting plate
drilling distanceMounting plate thickness table
For further explanation → see page 3.11

x	13	14	15	16	17	18	19	D
3	3	2	1	0				
4	4	3	2	1	0			
5		4	3	2	1	0		
6			4	3	2	1	0	D

$$D = 13 + K - x$$

Drawing show application on
D=0mm thick mounting plate

x	8	9	10	11	12	13	14	D
3	3	2	1	0				
4	4	3	2	1	0			
5		4	3	2	1	0		
6			4	3	2	1	0	D

$$D = 8 + K - x$$


Drawing show application on
D=0mm thick mounting plate

Soft closing systems

Glissando TL
→ see page 2.15Glissando CR
→ see page 2.19

Door clearance at R=1mm

For further explanation → see page 3.12






V	16	17	18	19	20	21	22	23	24	25	26	F _{MIN}
3	0.5	0.7	0.8	1	1.2	1.5	1.7	2.1	2.8	4.1	5.5	
4	0.4	0.7	0.8	1	1.2	1.5	1.7	2.1	2.3	3.1	4.5	
5	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	3.5	
6	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	2.9	F _{MIN}

$$\text{Gap } Z_{\text{MIN}} = 0$$

T-type 110

For wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

110°
35mm
11.7mm
'3Way' snap-on






Technical details

Cup type	Interaxis 45mm	Interaxis 48mm
	45 9.5 Ø 35	48 6 Ø 35
	Item number	Item number
	702-0CK0-054	702-0CL0-054

Cranking

9mm





Drilling patterns for hinge cups → see page 3.15

150 Pcs

Made of steel

Cranking

17mm



Drilling patterns for hinge cups → see page 3.15

150 Pcs

Made of steel

Mounting plates



Cam adjustable cruciform mounting plate
→ see page 3.51



Cruciform mounting plate
→ see page 3.53




Cam adjustable horizontal mounting plate
→ see page 3.51



Face frame adapter plate
→ see page 3.53

Hinge cup screws
If not pre-mounted



820-6328-050

10000 Pcs

Accessories

Cover caps for hinge arm
→ see page 3.151


Push latch
→ see page 3.149

Legend of hinge cup symbols


Screw-on ready
← screws

Machine insertion ready



Easy-fix system



Door adjustment



Side
adjustment
+3/-1mmHeight
adjustment
+2/-2mmDepth
adjustment
+4/-1mm

For further explanation → see pages 3.20-3.23

Mounting
detailsDrawing show application on
D=0mm thick mounting plateMounting plate
drilling distanceMounting plate thickness table
For further explanation → see page 3.11

	4	5	6	7	8	9	10
x	3	2	1	0			
K	4	3	2	1	0		
5		4	3	2	1	0	
6			4	3	2	1	0
D							

$$D=4+K-x$$

Drawing show application on
D=2mm thick mounting plate

	16	17	18	19	20	21	22	23	24
V	3	0	0	0	1	1	1	1	2
K	4	1	1	1	2	2	2	2	3
5		2	2	2	3	3	3	3	4
6		3	3	3	4	4	4	4	D
D									


$$D=-4+K+F$$

Soft closing systems

Glissando TL
→ see page 2.15Glissando CR
→ see page 2.19

Door clearance at R=1mm

For further explanation → see page 3.12






	16	17	18	19	20	21	22	23	24	25	26	
V	3	0.5	0.7	0.8	1	1.2	1.5	1.7	2.1	2.8	4.1	5.5
K	4	0.4	0.7	0.8	1	1.2	1.5	1.7	2.1	2.3	3.1	4.5
5		0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	3.5
6		0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	2.9
F _{MIN}												

$$\text{Gap } Z_{\text{MIN}}=0$$

T-type 120

For wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

120°
35mm
11.9mm
'3Way' snap-on






Technical details

Cup type	Interaxis 45mm	Interaxis 48mm
	702-0UK0-054	702-0UL0-054
	702-0UK1-054	702-0UL1-054
	702-0UK4-054	702-0UL4-054

Cranking

0mm






150 Pcs

Made of steel

Cranking

9mm



150 Pcs

Made of steel

Mounting plates



Cam adjustable cruciform mounting plate
→ see page 3.51



Cruciform mounting plate
→ see page 3.53




Cam adjustable horizontal mounting plate
→ see page 3.51



Face frame adapter plate
→ see page 3.53

Hinge cup screws
If not pre-mounted



820-6328-050

10000 Pcs

Accessories



Cover caps for hinge arm
→ see page 3.151




Push latch
→ see page 3.149

Legend of hinge cup symbols


Screw-on ready
← screws

Machine insertion ready



Easy-fix system



Door adjustment



Side
adjustment
+3/-1mmHeight
adjustment
+2/-2mmDepth
adjustment
+2.5/-2.5mm

For further explanation → see pages 3.20-3.23

Mounting
detailsDrawing show application on
D=0mm thick mounting plateMounting plate
drilling distanceMounting plate thickness table
For further explanation → see page 3.11

x	13	14	15	16	17	18	19	D
3	3	2	1	0				
4	4	3	2	1	0			
5		4	3	2	1	0		
6			4	3	2	1	0	

$$D=13+K-x$$

Drawing show application on
D=0mm thick mounting plate

x	4	5	6	7	8	9	10	D
3	3	2	1	0				
4	4	3	2	1	0			
5		4	3	2	1	0		
6			4	3	2	1	0	


$$D=4+K-x$$

Soft closing systems

Glissando CR
→ see page 2.19

Door clearance at R=1mm

For further explanation → see page 3.12





$$V \quad 16 \quad 17 \quad 18 \quad 19$$

3	1.1	0.4	0	0
K 4	2	1.4	0.7	0.1
5	3	2.3	1.6	1

$$\text{Gap } Z_{\text{MIN}} = 2$$

T-type 110/45°

45° angled application for wood doors



- Opening angle 110°
- Drilling diameter for hinge cup 35mm
- Drilling depth 11.7mm
- Hinge on plate mounting system '3Way' snap-on






Technical details

	Interaxis 45mm	Interaxis 48mm
Cup type		
Item number	702-0B07-054	702-0B09-054
Item number	702-0C53-054	702-0C55-054
Item number	702-0C77-054	702-0C79-054

Drilling patterns for hinge cups → see page 3.15

Cranking

17mm



150 Pcs

Cup made of steel, arm made of zinc

Mounting plates



Cam adjustable cruciform mounting plate
→ see page 3.51



Cruciform mounting plate
→ see page 3.53




Cam adjustable horizontal mounting plate
→ see page 3.51



Face frame adapter plate
→ see page 3.53

Hinge cup screws *If not pre-mounted*



820-6328-050

10000 Pcs

Accessories



Cover caps for hinge arm
→ see page 3.151

Legend of hinge cup symbols




Screw-on
ready
screws




Machine
insertion
ready



Easy-fix
system






Door adjustment



Side
adjustment
+3/-1mm Height
adjustment
+2/-2mm Depth
adjustment
+2.5/-2.5mm




For further explanation → see pages 3.20-3.23

Mounting details

Mounting plate
drilling distanceMounting plate thickness table
For further explanation → see page 3.11

P	0	0.5	1	1.5	2	2.5	3	3.5	4
K									
3	2		1		0				
4	3	2		1		0			
5		3	2		1		0		
6	4		3	2		1	0		D

Drawings show application on
D=0mm thick mounting plate



X	0	0.5	1	1.5	2	2.5	3	3.5	4	4.5	5	6
K												
3	2		1		0							
4		2		1		0						
5	3		2		1		0					
6	4		3	2		1	0					D

Drawings show application on
D=0mm thick mounting plate

L=45 for thickness D=0
L=44 for thickness D=1
L=43 for thickness D=2
L=42 for thickness D=3
L=41 for thickness D=4


Soft closing systems



Glissando TL
→ see page 2.15

Door clearance at R=1mm

For further explanation → see page 3.12





V	16	17	18	19	20	21	22	23	24	25	26	F _{MIN}
K												
3	0.5	0.7	0.8	1	1.2	1.5	1.7	2.1	2.8	4.1	5.5	
4	0.4	0.7	0.8	1	1.2	1.5	1.7	2.1	2.3	3.1	4.5	
5	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	3.5	
6	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	2.9	F _{MIN}

Gap Z_{MIN}=0

T-type 110/90°

For wood door cabinets with blind panels



- Opening angle 110°
- Drilling diameter for hinge cup 35mm
- Drilling depth 11.7mm
- Hinge on plate mounting system '3Way' snap-on





Technical details

	Interaxis 45mm	Interaxis 48mm
Cup type		
Item number	702-0A95-054	702-0A97-054
Item number	702-0D29-054	702-0D31-054
Item number	702-0D35-054	702-0D37-054

Drilling patterns for hinge cups → see page 3.15

Cranking

17mm



150 Pcs

Cup made of steel, arm made of zinc

Mounting plates



Cam adjustable cruciform mounting plate
→ see page 3.51



Cruciform mounting plate
→ see page 3.53




Cam adjustable horizontal mounting plate
→ see page 3.51



Face frame adapter plate
→ see page 3.53

Hinge cup screws *If not pre-mounted*



820-6328-050

10000 Pcs

Accessories



Cover caps for hinge arm
→ see page 3.151

Legend of hinge cup symbols




Screw-on
ready
screws




Machine
insertion
ready



Easy-fix
system





Door adjustment




For further explanation → see pages 3.20-3.23

Mounting details

Drawings show application on
D=2mm thick mounting plateDrawings show application on
D=2mm thick mounting plate

Mounting plate drilling distance




Soft closing systems

Glissando TL
→ see page 2.15

Door clearance at R=1mm

For further explanation → see page 3.12






V	16	17	18	19	20	21	22	23	24	25	26	F _{MIN}
K	3	0.5	0.7	0.8	1	1.2	1.5	1.7	2.1	2.8	4.1	5.5
K	4	0.4	0.7	0.8	1	1.2	1.5	1.7	2.1	2.3	3.1	4.5
K	5	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	3.5
K	6	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	2.9

Gap Z_{MIN}=0

T-type 170

For wood doors




- Opening angle 165°
- Drilling diameter for hinge cup 35mm
- Drilling depth 12mm
- Hinge on plate mounting system '3Way' snap-on



Cranking

0mm




50 Pcs

Made of steel and zinc

Cranking

5mm



50 Pcs

Made of steel and zinc

Mounting plates



Cam adjustable cruciform mounting plate
→ see page 3.51



Cruciform mounting plate
→ see page 3.53




Cam adjustable horizontal mounting plate
→ see page 3.51



Face frame adapter plate
→ see page 3.53

Hinge cup screws
If not pre-mounted



820-6328-050

10000 Pcs

Accessories



Push latch
→ see page 3.149

Legend of hinge cup symbols




Screw-on
ready
screws




Machine
insertion
ready




Easy-fix
system




Door adjustment

Side
adjustment
+3/-1mmHeight
adjustment
+2/-2mmDepth
adjustment
+4/-1mm

For further explanation → see pages 3.20-3.23


Mounting
details

Drawings show application on
D=0mm mounting plate
In 90° position the door is only
1.4mm distant from side panel


Mounting plate
drilling distanceMounting plate thickness table
For further explanation → see page 3.11

x	13	14	15	16	17	18	19
K	3	2	1	0			
4	4	3	2	1	0		
5		4	3	2	1	0	
6			4	3	2	1	0
					D		

$$D = 13 + K - x$$



Drawings show application on
D=0mm mounting plate



x	8	9	10	11	12	13	14
K	3	2	1	0			
4	4	3	2	1	0		
5		4	3	2	1	0	
6			4	3	2	1	0
					D		


$$D = 8 + K - x$$

Soft closing systems

Glissando TL 170
→ see page 2.17Glissando CR
→ see page 2.19

Door clearance at R=1mm

For further explanation → see page 3.12






V	16	17	18	19	20	21	22	23	24	F _{MIN}
K	3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.6	
7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.1	F _{MIN}

$$\text{Gap } Z_{\text{MIN}} = 0.5$$

T-type 170

For wood doors




- Opening angle 165°
- Drilling diameter for hinge cup 35mm
- Drilling depth 12mm
- Hinge on plate mounting system '3Way' snap-on



Cranking

9mm



	Interaxis 45mm	Interaxis 48mm
Cup type	Item number	Item number
	702-0GK0-054	702-0GL0-054
	702-0GK1-054	702-0GL1-054
	702-0GK4-054	702-0GL4-054

Drilling patterns for hinge cups → see page 3.15



Made of steel and zinc

Mounting plates



Cam adjustable cruciform mounting plate
→ see page 3.51



Cruciform mounting plate
→ see page 3.53




Cam adjustable horizontal mounting plate
→ see page 3.51



Face frame adapter plate
→ see page 3.53

Hinge cup screws *If not pre-mounted*



820-6328-050

10000 Pcs

Accessories



Push latch
→ see page 3.149

Legend of hinge cup symbols




Screw-on
ready
screws




Machine
insertion
ready






Easy-fix
system



Door adjustment

Side
adjustment
+3/-1mmHeight
adjustment
+2/-2mmDepth
adjustment
+4/-1mm

For further explanation → see pages 3.20-3.23

Mounting
detailsDrawings show application on
D=0mm thick mounting plateMounting plate
drilling distanceDrawings show application on
D=0mm thick mounting plateMounting plate thickness table
For further explanation → see page 3.11

	x	13	14	15	16	17	18	19
K	3	3	2	1	0			
	4	4	3	2	1	0		
	5		4	3	2	1	0	
	6			4	3	2	1	0
								D


$$D = 13 + K - x$$

Soft closing systems

Glissando TL 170
→ see page 2.17Glissando CR
→ see page 2.19

Door clearance at R=1mm

For further explanation → see page 3.12




V	16	17	18	19	20	21	22	23	24
K	3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
	4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
	5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
	6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.6
	7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.1
									F _{MIN}

Gap Z_{MIN}=0.5

T-type Mounting Plates

'3Way' snap-on mounting



Cam adjustable cruciform
mounting plate 37mm



Drilling pattern

Dimensions






150 Pcs Made of steel

Cam adjustable horizontal
mounting plate



150 Pcs Made of steel and zinc





Mounting plate thickness

Height adjustment +2/-2mm

Height adjustment +2/-2mm

Mounting plate type	15		10.5	15	14.5	
Mounting plate thickness (D)	min 11.5, Ø5 Item number	min 10.5, Ø10 Item number	min 10.5, Ø5 Item number	no pre-drilling required Item number	min 11.5, Ø3 Item number	
0mm	700-0KC0-054	700-0KB0-054	700-0KF0-054	700-0KA0-054	700-0KE0-054	
1mm	700-0KC1-054	700-0KB1-054	700-0KF1-054	700-0KA1-054	700-0KE1-054	
2mm	700-0KC2-054	700-0KB2-054	700-0KF2-054	700-0KA2-054	700-0KE2-054	
3mm	700-0KC3-054	700-0KB3-054	700-0KF3-054	700-0KA3-054	700-0KE3-054	
4mm	700-0KC4-054	700-0KB4-054	700-0KF4-054	700-0KA4-054	700-0KE4-054	
0mm	700-0LC0-650	700-0LB0-650	700-0LF0-650			
2mm	700-0LC2-650	700-0LB2-650	700-0LF2-650			
3mm	700-0LC3-650	700-0LB3-650	700-0LF3-650			

Legend of mounting plate type symbols



Pre-mounted 15mm euro screws



Machine insertion ready





Pre-mounted 10.5mm expanding dowels



Premounted chipboard screw




Premounted chipboard screw



T-type Mounting Plates



'3Way' snap-on mounting



Cruciform mounting plate 37mm

Drilling pattern



Dimensions



150 Pcs

Made of steel


Face frame mounting plate



150 Pcs


Made of steel and zinc

Fixing screw for cruciform mounting plate
If not pre-mounted



Chipboard screws
820-6328-050

10000 Pcs




Mounting plate thickness

Height adjustment +2/-2mm


Height adjustment +2/-2mm

Mounting plate type		15		10.5	15	14.5	
Mounting plate thickness (D)	3.9	min 11.5, Ø5, 15	min 10.5, Ø10	min 10.5, Ø5	no pre-drilling required	min 11.5, Ø3, 15	min 11.5, Ø3, 14.5
	Item number	Item number	Item number	Item number	Item number	Item number	Item number
0mm	700-0NA0-054	700-0NC0-054	700-0NB0-054	700-0NF0-054	700-0NR0-054	700-0NE0-054	
1mm	700-0NA1-054	700-0NC1-054	700-0NB1-054	700-0NF1-054	700-0NR1-054	700-0NE1-054	
2mm	700-0NA2-054	700-0NC2-054	700-0NB2-054	700-0NF2-054	700-0NR2-054	700-0NE2-054	
3mm	700-0NA3-054	700-0NC3-054	700-0NB3-054	700-0NF3-054	700-0NR3-054	700-0NE3-054	
4mm	700-0NA4-054	700-0NC4-054	700-0NB4-054	700-0NF4-054	700-0NR4-054	700-0NE4-054	
0mm							700-0NW0-054
3mm							700-0NW3-054

Legend of mounting plate type symbols

Screw-on ready for
chipboard screws
← screwsPre-mounted
15mm euro screwsMachine
insertion readyPre-mounted
10.5mm
expanding dowelsPremounted
chipboard screwPremounted
chipboard screw

S-type Hinges



'Snap-on' mounting system


- Easy and quick assembly and disassembly
- Flexibility for the furniture user
- Tight hinge-to-plate joint improves hinge stability and reduces door sag

Easily accessible height adjustment with cam

- Intuitive and quick height adjustment
- Consumer friendly

'ConfidentClose'

- 1 Fast closing
- 2 Late start of deceleration action
- 3 Quiet landing with 'SoftTouch'




Soft closing options

- Hinge integrated
- Add-on with Glissando ready hinge cup
- Stand-alone



Adjustable damping

- Adjustable damping assures perfect functioning on every door






Touch opening

- Guarantees effortless opening
- Elegant cabinet design
- Doors without handles

S-type-i Plus 110

For wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

110°
35mm
min. 11mm
'snap-on'





Technical details

	Interaxis 45mm	Interaxis 48mm
Cup type		
Item number	954-0228-050	954-0229-050

Cranking

0mm





200 Pcs

Made of steel and plastic

Drilling patterns for hinge cups → see page 3.15

Cranking

9mm



200 Pcs

Made of steel and plastic

Drilling patterns for hinge cups → see page 3.15

Mounting plates



Cam adjustable mounting plate
→ see page 3.97



Steel mounting plates
→ see page 3.99




Zinc diecast mounting plates
→ see page 3.99



Face frame adapters
→ see page 3.101

Hinge cup screws
If not pre-mounted



820-6308-050

10000 Pcs


Legend of hinge cup symbols

Screw-on ready ← screws




Cover caps for hinge arm
→ see page 3.151

Damping adjustment



Door adjustment




 Side
adjustment
+3/-1mm

 Height
adjustment
+2/-2mm

 Depth
adjustment
+1.5/-1.5mm

For further explanation → see page 3.25



For further explanation → see pages 3.20-3.23

 Mounting
details

 Mounting plate
drilling distance

 Mounting plate thickness table
For further explanation → see page 3.11

x	13	14	15	16	17	18	
3	3	2	1	0			D
4		3	2	1	0		
5			3	2	1	0	

$D = 13 + K \cdot x$


Drawings show application on D=0mm thick mounting plate



x	4	5	6	7	8	9	
3	3	2	1	0			D
4		3	2	1	0		
5			3	2	1	0	

$D = 4 + K \cdot x$

Drawings show application on D=0mm thick mounting plate




 Door clearance
For further explanation → see page 3.12


V	16	17	18	19	20	21	22	
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5	
4	0.3	0.5	0.7	0.9	1.2	1.6	2.1	
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0	F_{MIN}

Gap $Z_{MIN}=0$

S-type-i 110

For wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

110°
35mm
min. 11mm
'snap-on'





Technical details

	Interaxis 45mm	Interaxis 48mm
Cup type		
Item number	954-0226-050	954-0227-050

Cranking

0mm





200 Pcs

Made of steel and plastic

Drilling patterns for hinge cups → see page 3.15

Cranking

9mm






200 Pcs

Made of steel and plastic

Drilling patterns for hinge cups → see page 3.15

Cranking

15mm



200 Pcs

Made of steel and plastic

Drilling patterns for hinge cups → see page 3.15

Mounting plates



Cam adjustable mounting plate
→ see page 3.97



Steel mounting plates
→ see page 3.99




Zinc diecast mounting plates
→ see page 3.99



Face frame adapters
→ see page 3.101

Hinge cup screws
If not pre-mounted



820-6308-050

10000 Pcs

Accessories



Cover caps for hinge arm
→ see page 3.151


Legend of hinge cup symbols




Screw-on ready
← screws



Damping adjustment






Door adjustment

Side
adjustment
+3/-1mmHeight
adjustment
+2/-2mmDepth
adjustment
+5/-1.5mm

For further explanation → see page 3.25

For further explanation → see pages 3.20-3.23



Mounting
detailsDrawings show application on
D=0mm thick mounting plateMounting plate
drilling distance

Mounting plate thickness table

For further explanation → see page 3.11


x	13	14	15	16	17	18	D
3	3	2	1	0			
4		3	2	1	0		
5			3	2	1	0	

$$D = 13 + K - x$$

Drawings show application on
D=0mm thick mounting plate


x	4	5	6	7	8	9	D
3	3	2	1	0			
4		3	2	1	0		
5			3	2	1	0	

$$D = 4 + K - x$$

Drawings show application on
D=3mm thick mounting plate

V	16	17	18	19	20	21	D
3	2	2	2	3	3	3	
4	3	3	3				
5	3						

$$D = -2 + K + F$$



Door clearance
For further explanation → see page 3.12

V	16	17	18	19	20	21	22	F _{MIN}
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5	
4	0.3	0.5	0.7	0.9	1.2	1.6	2.1	
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0	

Gap Z_{MIN}=0

S-type-i 110/30°

30° angled application for wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

110°
35mm
min. 11mm
'snap-on'





Technical details

	Interaxis 45mm	Interaxis 48mm
Cup type		
Item number	954-0E09-650	954-0164-650

Cranking

9mm



Drilling patterns for hinge cups → see page 3.15

100 Pcs

Cup made of steel and plastic, arm made of zinc

Mounting plates



Cam adjustable
mounting plate
→ see page 3.97




Steel mounting plates
→ see page 3.99



Zinc diecast
mounting plates
→ see page 3.99

Hinge cup screws *If not pre-mounted*



820-6308-050

10000 Pcs

Legend of hinge cup symbols




Screw-on
ready
screws




Cover caps for hinge arm
→ see page 3.151

Damping adjustment





Door adjustment



Side
adjustment
+3/-1mmHeight
adjustment
+2/-2mmDepth
adjustment
+5/-1.5mm

For further explanation → see page 3.25


For further explanation → see pages 3.20-3.23

Mounting
detailsMounting plate
drilling distanceMounting plate thickness table
For further explanation → see page 3.11

P	2.5	3.5	4.5	8.5	9.5	10.5	11.5	12.5	13.5
3	9			3	2	1	0		
K	4			9		3	2	1	0
5				9		3	2	1	0
								D	

Drawings show application on
D=3mm thick mounting plateDrawings show application on
D=3mm thick mounting plateL=37 for thickness D=0
L=36 for thickness D=1
L=35 for thickness D=2
L=34 for thickness D=3
L=31 for thickness D=9

x	2	3	4	9	10	11	12	13	14	15
3	9			3	2			0		
K	4			9		3	2		0	
5				9		3	2		0	D



Door clearance
For further explanation → see page 3.12

V	16	17	18	19	20	21	22	F _{MIN}
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5	
K	4	0.3	0.5	0.7	0.9	1.2	1.6	2.1
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0	F _{MIN}

Gap Z_{MIN}=0

S-type-i 110/45°

45° angled application for wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

110°
35mm
min. 11mm
'snap-on'





Technical details

	Interaxis 45mm	Interaxis 48mm
Cup type		
Item number	954-0E10-650	954-0165-650

Cranking

9mm



Drilling patterns for hinge cups → see page 3.15

100 Pcs

Cup made of steel and plastic, arm made of zinc

Mounting plates



Cam adjustable mounting plate
→ see page 3.97




Steel mounting plates
→ see page 3.99



Zinc diecast mounting plates
→ see page 3.99

Hinge cup screws *If not pre-mounted*



820-6308-050

10000 Pcs

Legend of hinge cup symbols




Screw-on
ready
← screws




Cover caps for hinge arm
→ see page 3.151

Damping adjustment




Door adjustment



Side
adjustment
+3/-1mmHeight
adjustment
+2/-2mmDepth
adjustment
+5/-1.5mm

For further explanation → see page 3.25


For further explanation → see pages 3.20-3.23

Mounting
detailsMounting plate
drilling distanceMounting plate thickness table
For further explanation → see page 3.11

P	9	9.5	10	10.5	11	11.5	12	12.5	13.5
K	3		2		1		0		
									D

Drawings show application on
D=3mm thick mounting plate



x	11.5	12.5	13	13.5	14	14.5	15	15.5	16	16.5	17	18
3	3		2		1		0					
4				3		2		1		0		
5					3		2		1		0	D

L=36 for thickness D=0
L=35 for thickness D=1
L=34 for thickness D=2
L=33 for thickness D=3Drawings show application on
D=3mm thick mounting plateDoor clearance
For further explanation → see page 3.12

V	16	17	18	19	20	21	22
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5
4	0.3	0.5	0.7	0.9	1.2	1.6	2.1
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0
Gap Z _{MIN} =0							F _{MIN}

S-type-i 110/45°

45° angled application for wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

110°
35mm
min. 11mm
'snap-on'




Technical details

	Interaxis 45mm	Interaxis 48mm
Cup type		
Item number	954-0E11-650	954-0E14-650

Cranking

18mm



Drilling patterns for hinge cups → see page 3.15

100 Pcs

Cup made of steel and plastic, arm made of zinc

Mounting plates



Cam adjustable mounting plate
→ see page 3.97



Steel mounting plates
→ see page 3.99




Zinc diecast mounting plates
→ see page 3.99



Face frame adapters
→ see page 3.101

Hinge cup screws *If not pre-mounted*



820-6308-050

10000 Pcs


Legend of hinge cup symbols

Screw-on ready
← screws




Cover caps for hinge arm
→ see page 3.151

Damping adjustment








Door adjustment


Side
adjustment
+3/-1mmHeight
adjustment
+2/-2mmDepth
adjustment
+5/-1.5mm

For further explanation → see page 3.25

For further explanation → see pages 3.20-3.23

Mounting
detailsDrawings show application on
D=18mm thick mounting plateDrawings show application on
D=0mm thick mounting plateMounting plate
drilling distanceMounting plate thickness table
For further explanation → see page 3.11Drawings show application on
D=0mm thick mounting plate

K	3	4	5
D	0	1	2



Door clearance
For further explanation → see page 3.12

V	16	17	18	19	20	21	22	F _{MIN}
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5	
4	0.3	0.5	0.7	0.9	1.2	1.6	2.1	
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0	

Gap Z_{MIN}=0

S-type-i 110/90°

For wood door cabinets with blind panels



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

110°
35mm
min. 11mm
'snap-on'




Technical details

	Interaxis 45mm	Interaxis 48mm
Cup type		
Item number	954-0E12-650	954-0E15-650

Cranking

18mm



Drilling patterns for hinge cups → see page 3.15

100 Pcs

Cup made of steel and plastic, arm made of zinc

Mounting plates



Cam adjustable mounting plate
→ see page 3.97



Steel mounting plates
→ see page 3.99




Zinc diecast mounting plates
→ see page 3.99



Face frame adapters
→ see page 3.101

Hinge cup screws *If not pre-mounted*



820-6308-050

10000 Pcs

Legend of hinge cup symbols




Screw-on ready
← screws




Cover caps for hinge arm
→ see page 3.151

Damping adjustment






Door adjustment

Side
adjustment
+3/-1mmHeight
adjustment
+2/-2mmDepth
adjustment
+5/-1.5mm

For further explanation → see page 3.25

For further explanation → see pages 3.20-3.23




Mounting
detailsDrawings show application on
D=0mm thick mounting plateMounting plate
drilling distanceDrawings show application on
D=3mm thick mounting plateDoor clearance
For further explanation → see page 3.12

V	16	17	18	19	20	21	22	
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5	
4	0.3	0.5	0.7	0.9	1.2	1.6	2.1	
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0	F _{MIN}

Gap Z_{MIN}=0

S-type Plus 110

For wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system


110°
35mm
11.5mm
'snap-on'



	Interaxis 45mm	Interaxis 48mm	Interaxis 52mm
Cup type	Item number	Item number	Item number
	248-0T10-050	248-0T70-050	248-0T93-050
	248-0T13-050	248-0T71-050	248-0T94-050
	248-0T69-050	248-0T72-050	248-0T95-050

Cranking

0mm




200 Pcs

Made of steel

Cranking

9mm



Drilling patterns for hinge cups → see page 3.15

	248-0V69-050	248-0V71-050	
	248-0V70-050	248-0V72-050	248-0274-050
	248-0V56-050		248-0377-050

Drilling patterns for hinge cups → see page 3.15

200 Pcs

Made of steel

Mounting plates



Cam adjustable mounting plate
→ see page 3.97



Steel mounting plates
→ see page 3.99




Zinc diecast mounting plates
→ see page 3.99



Face frame adapters
→ see page 3.101

Hinge cup screws
If not pre-mounted



820-6308-050

10000 Pcs

Legend of hinge cup symbols



Screw-on
ready
← screws



Machine
insertion
ready



Easy-fix
system


Accessories




Cover caps for hinge arm
→ see page 3.151





Push latch
→ see page 3.149



Door adjustment



Side
adjustment
+3/-1mmHeight
adjustment
+2/-2mmDepth
adjustment
+1.5/-1.5mm

For further explanation → see pages 3.20-3.23

Mounting
detailsDrawings show application on
D=0mm thick mounting plateMounting plate
drilling distanceMounting plate thickness table
For further explanation → see page 3.11

x	13	14	15	16	17	18	
3	3	2	1	0			D
4		3	2	1	0		
5			3	2	1	0	

$$D = 13 + K \cdot x$$

Drawings show application on
D=0mm thick mounting plate

x	4	5	6	7	8	9	
3	3	2	1	0			D
4		3	2	1	0		
5			3	2	1	0	


$$D = 4 + K \cdot x$$

Soft closing systems

Glissando TL
→ see page 2.15Glissando CR
→ see page 2.19

Door clearance

For further explanation → see page 3.12






V	16	17	18	19	20	21	22	
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5	F _{MIN}
4	0.3	0.5	0.7	0.9	1.2	1.6	2.1	
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0	

Gap $Z_{MIN}=0$

S-type Plus 110

Touch opening



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system


110°
35mm
11.5mm
'snap-on'



Cup type	Interaxis 45mm	Interaxis 48mm	Interaxis 52mm
	Item number	Item number	Item number
	915-0Z85-050	915-0Z96-050	
	Drilling patterns for hinge cups → see page 3.15		

Cranking

0mm




200 Pcs

Made of steel

Cranking

9mm



200 Pcs

Made of steel

Catches



Catch



Catch with base plate



Knock-in pad



Self adhesive pad

100 Pcs

Made of plastic

915-0007-050 915-0032-050 915-0012-050

Drilling patterns for hinge cups → see page 3.15

Catch

915-7016-380

Catch with base plate

915-7022-380

Knock-in pad

915-7109-050

Self adhesive pad

915-7105-050

Mounting plates



Cam adjustable mounting plate
→ see page 3.97




Steel mounting plates
→ see page 3.99



Zinc diecast mounting plates
→ see page 3.99

Hinge cup screws
If not pre-mounted



820-6308-050

10000 Pcs

Legend of hinge cup symbols




Screw-on ready
← screws





- Hinge integrated self-opening mechanism
- Effortless opening with just a light touch

Door adjustment

Side
adjustment
+3/-1mmHeight
adjustment
+2/-2mmDepth
adjustment
+1.5/-1.5mm

For further explanation → see pages 3.20-3.23

Mounting details



Drawings show application on
D=0mm thick mounting plateMounting plate
drilling distance

Mounting plate thickness table

For further explanation → see page 3.11



x	13	14	15	16	17	18	D
3	3	2	1	0			
4		3	2	1	0		
5			3	2	1	0	

$$D = 13 + K \cdot x$$





Drawings show application on
D=0mm thick mounting plate

x	4	5	6	7	8	9	D
3	3	2	1	0			
4		3	2	1	0		
5			3	2	1	0	

$$D = 4 + K \cdot x$$



Catch


Fixing of pad depends
on the catch positionpre-drilled hole
Ø2 / 10mm

Accessories

Cover caps for hinge arm
→ see page 3.151

Door clearance

For further explanation → see page 3.12






V	16	17	18	19	20	21	22	F _{MIN}
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5	
4	0.3	0.5	0.7	0.9	1.2	1.6	2.1	
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0	

Gap Z_{MIN}=0

S-type 110




For wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system


110°
35mm
11.5mm
'snap-on'



Cup type	Interaxis 45mm	Interaxis 48mm	Interaxis 52mm
			
Item number	248-0535-050	248-0532-050	248-0538-050
			
	248-0171-050	248-0172-050	248-0400-050
			
	248-0186-050	248-0188-050	248-0366-050
			
	248-0197-050		

Cranking

0mm




200 Pcs

Made of steel

Drilling patterns for hinge cups → see page 3.15

Cranking

9mm




200 Pcs

Made of steel

Drilling patterns for hinge cups → see page 3.15

Cranking

15mm



200 Pcs

Made of steel

Drilling patterns for hinge cups → see page 3.15

Mounting plates



Cam adjustable mounting plate
→ see page 3.97



Steel mounting plates
→ see page 3.99




Zinc diecast mounting plates
→ see page 3.99



Face frame adapters
→ see page 3.101

Hinge cup screws
If not pre-mounted



820-6308-050

10000 Pcs

Legend of hinge cup symbols



Screw-on
ready
← screws




Machine
insertion
ready




Easy-fix
system



Preinserted
expando
dowels





Door adjustment




Side
adjustment
+3/-1mm Height
adjustment
+2/-2mm Depth
adjustment
+5/-1.5mm

For further explanation → see pages 3.20-3.23

Mounting details



Drawings show application on
D=0mm thick mounting plate



Mounting plate
drilling distance

Mounting plate thickness table

For further explanation → see page 3.11

x	13	14	15	16	17	18	D
3	3	2	1	0			
4		3	2	1	0		
5			3	2	1	0	

$$D = 13 + K - x$$




Drawings show application on
D=0mm thick mounting plate



x	4	5	6	7	8	9	D
3	3	2	1	0			
4		3	2	1	0		
5			3	2	1	0	

$$D = 4 + K - x$$



Drawings show application on
D=3mm thick mounting plate



V	16	17	18	19	20	21	D
3	2	2	2	3	3	3	
4	3	3	3				
5	3						

$$D = -2 + K - F$$

Soft closing systems



Glissando TL
→ see page 2.15



Glissando CR
→ see page 2.19

Accessories




Cover caps for hinge arm
→ see page 3.151



Push latch
→ see page 3.149

Door clearance

For further explanation → see page 3.12






V	16	17	18	19	20	21	22	F _{MIN}
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5	
4	0.3	0.5	0.7	0.9	1.2	1.6	2.1	
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0	

Gap Z_{MIN}=0

S-type 110/-15°

-15° angled application for wood doors




- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

110°
35mm
11.5mm
'snap-on'



Cranking

0mm



	Interaxis 45mm	Interaxis 48mm	Interaxis 52mm
Cup type	Item number	Item number	Item number
	248-0V14-050	248-0V39-050	248-0V40-050
	248-0V41-050	248-0V42-050	248-0V43-050

Drilling patterns for hinge cups → see page 3.15

100 Pcs

Cup made of steel, arm made of zinc

Mounting plates



Cam adjustable
mounting plate
→ see page 3.97




Steel mounting
plates
→ see page 3.99



Zinc diecast
mounting plates
→ see page 3.99

Hinge cup screws *If not pre-mounted*



820-6308-050

10000 Pcs


Legend of hinge cup symbols




Screw-on
ready
↓ screws





Machine
insertion
ready



Door adjustment

Side
adjustment
+3/-1mmHeight
adjustment
+2/-2mmDepth
adjustment
+5/-1.5mm

For further explanation → see pages 3.20-3.23

Mounting
detailsMounting plate
drilling distance

Mounting plate thickness table

For further explanation → see page 3.11

x	4	5	6	10	11	12	13	14	15
3	9			3	2	1	0		
4		9			3	2	1	0	
5			9			3	2	1	0
D									


Drawings show application on
D=0mm thick mounting plate

Accessories

Cover caps for hinge arm
→ see page 3.151

Door clearance

For further explanation → see page 3.12





V	16	17	18	19	20	21	22	F _{MIN}
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5	
4	0.3	0.5	0.7	0.9	1.2	1.6	2.1	
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0	F _{MIN}

Gap Z_{MIN}=0

S-type 110/15°

15° angled application for wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system


110°
35mm
11.5mm
'snap-on'



	Interaxis 45mm	Interaxis 48mm	Interaxis 52mm
Cup type	Item number	Item number	Item number
	248-0080-050	248-0V62-050	248-0C66-050

Cranking

9mm



Drilling patterns for hinge cups → see page 3.15

100 Pcs

Cup made of steel, arm made of zinc

Mounting plates



Cam adjustable
mounting plate
→ see page 3.97




Steel mounting
plates
→ see page 3.99



Zinc diecast
mounting plates
→ see page 3.99

Hinge cup screws
If not pre-mounted




820-6308-050

10000 Pcs

Legend of hinge cup symbols





Door adjustment





Side
adjustment
+3/-1mm Height
adjustment
+2/-2mm Depth
adjustment
+5/-1.5mm

For further explanation → see pages 3.20-3.23

Mounting details

Mounting plate
drilling distanceMounting plate thickness table
For further explanation → see page 3.11

Drawings show application on
D=0 and K=4mm thick mounting plate



Drawings show application on
D=0 and K=4mm thick mounting plate

x,P	1	2	3	7	8	9	10	11	12
3	9			3	2	1	0		
4		9			3	2	1	0	
5			9			3	2	1	0

L=37 for thickness D=0
L=36 for thickness D=1
L=36 for thickness D=2
L=35 for thickness D=3
L=33 for thickness D=9

Soft closing systems



Glissando TL
→ see page 2.15


Accessories



Cover caps for hinge arm
→ see page 3.151

Door clearance

For further explanation → see page 3.12





V	16	17	18	19	20	21	22	F _{MIN}
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5	
4	0.3	0.5	0.7	0.9	1.2	1.6	2.1	
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0	F _{MIN}

Gap Z_{MIN}=0

S-type 110/24°

24° angled application for wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

110°
35mm
11.5mm
'snap-on'



	Interaxis 45mm	Interaxis 48mm	Interaxis 52mm
Cup type	Item number	Item number	Item number
	248-0V18-050	248-0V45-050	248-0Z29-050
	248-0V47-050	248-0V48-050	248-0V49-050

Drilling patterns for hinge cups → see page 3.15

Cranking

9mm



100 Pcs

Cup made of steel, arm made of zinc

Mounting plates



Cam adjustable mounting plate
→ see page 3.97




Steel mounting plates
→ see page 3.99



Zinc diecast mounting plates
→ see page 3.99

Hinge cup screws
If not pre-mounted



820-6308-050

10000 Pcs


Legend of hinge cup symbols




Screw-on
ready
↓
screws





Machine
insertion
ready



Door adjustment

Side
adjustment
+3/-1mmHeight
adjustment
+2/-2mmDepth
adjustment
+5/-1.5mm

For further explanation → see pages 3.20-3.23

Mounting
detailsMounting plate
drilling distance

Mounting plate thickness table

For further explanation → see page 3.11

x	3	4	5	9	10	11	12	13	14
3	9			3	2	1	0		
4		9			3	2	1	0	
5			9			3	2	1	0
D									

Drawings show application on
D=0mm thick mounting plate

Soft closing systems

Glissando TL
→ see page 2.15

Accessories

Cover caps for hinge arm
→ see page 3.151

Door clearance

For further explanation → see page 3.12





V	16	17	18	19	20	21	22	F _{MIN}
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5	
4	0.3	0.5	0.7	0.9	1.2	1.6	2.1	
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0	F _{MIN}

Gap Z_{MIN}=0

S-type 110/30°

30° angled application for wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

110°
35mm
11.5mm
'snap-on'




	Interaxis 45mm	Interaxis 48mm	Interaxis 52mm
Cup type	Item number	Item number	Item number
	248-0675-050	248-0665-050	248-0677-050
	248-0N12-050	248-0N13-050	248-0N14-050

Drilling patterns for hinge cups → see page 3.15

Cranking

9mm



200 Pcs

Cup made of steel, arm made of zinc

Mounting plates



Cam adjustable mounting plate
→ see page 3.97




Steel mounting plates
→ see page 3.99



Zinc diecast mounting plates
→ see page 3.99

Hinge cup screws
If not pre-mounted



820-6308-050

10000 Pcs


Legend of hinge cup symbols




Screw-on
ready
screws





Machine
insertion
ready



Door adjustment

Side
adjustment
+3/-1mmHeight
adjustment
+2/-2mmDepth
adjustment
+5/-1.5mm



For further explanation → see pages 3.20-3.23

Mounting
detailsDrawings show application on
D=3mm thick mounting plateMounting plate
drilling distance

Mounting plate thickness table

For further explanation → see page 3.11

P	2.5	3.5	4.5	8.5	9.5	10.5	11.5	12.5	13.5
3	9			3	2	1	0		
K	4				3	2	1	0	
5				9		3	2	1	0
						D			

Drawings show application on
D=3mm thick mounting plate

L=37 for thickness D=0
 L=36 for thickness D=1
 L=35 for thickness D=2
 L=34 for thickness D=3
 L=31 for thickness D=9

x	2	3	4	9	10	11	12	13	14	15
3	9			3	2			0		
K	4				3	2			0	
5				9		3	2		0	D

Soft closing systems


Glissando TL
→ see page 2.15

Accessories

Cover caps for hinge arm
→ see page 3.151

Door clearance

For further explanation → see page 3.12





V	16	17	18	19	20	21	22	
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5	
K	4	0.3	0.5	0.7	0.9	1.2	1.6	2.1
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0	F _{MIN}

Gap Z_{MIN}=0

S-type 110/45°

45° angled application for wood doors



- Opening angle 110°
- Drilling diameter for hinge cup 35mm
- Drilling depth 11.5mm
- Hinge on plate mounting system 'snap-on'




	Interaxis 45mm	Interaxis 48mm	Interaxis 52mm
Cup type	Item number	Item number	Item number
	248-0433-050	248-0431-050	248-0518-050
	248-0N16-050	248-0N17-050	248-0N18-050

Drilling patterns for hinge cups → see page 3.15

Cranking

9mm



200 Pcs

Cup made of steel, arm made of zinc

Mounting plates



Cam adjustable mounting plate
→ see page 3.97




Steel mounting plates
→ see page 3.99



Zinc diecast mounting plates
→ see page 3.99

Hinge cup screws
If not pre-mounted



820-6308-050

10000 Pcs


Legend of hinge cup symbols




Screw-on
ready
screws



Machine
insertion
ready




Door adjustment



Side
adjustment
+3/-1mm Height
adjustment
+2/-2mm Depth
adjustment
+5/-1.5mm



For further explanation → see pages 3.20-3.23

Mounting details

Mounting plate
drilling distanceMounting plate thickness table
For further explanation → see page 3.11

P	9	9.5	10	10.5	11	11.5	12	12.5	13.5
K	3		2		1		0		
									D

Drawings show application on
D=3mm thick mounting plate



x	11.5	12.5	13	13.5	14	14.5	15	15.5	16	16.5	17	18
3	3		2		1		0					
K	4		3		2		1		0			
												D

Drawings show application on
D=3mm thick mounting plate

L=36 for thickness D=0
L=35 for thickness D=1
L=34 for thickness D=2
L=33 for thickness D=3

Soft closing systems



Glissando TL
→ see page 2.15


Accessories



Cover caps for hinge arm
→ see page 3.151

Door clearance

For further explanation → see page 3.12





V	16	17	18	19	20	21	22	
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5	
K	4	0.3	0.5	0.7	0.9	1.2	1.6	2.1
								F _{MIN}

Gap Z_{MIN}=0

S-type 110/45°

45° angled application for wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

110°
35mm
11.5mm
'snap-on'




Cup type	Interaxis 45mm	Interaxis 48mm	Interaxis 52mm
	Item number	Item number	Item number
	248-0285-050	248-0283-050	248-0291-050
	248-0N20-050	248-0N21-050	248-0N22-050

Drilling patterns for hinge cups → see page 3.15

Cranking

18mm



100 Pcs

Cup made of steel, arm made of zinc

Mounting plates



Cam adjustable mounting plate
→ see page 3.97



Steel mounting plates
→ see page 3.99




Zinc diecast mounting plates
→ see page 3.99



Face frame adapters
→ see page 3.101

Hinge cup screws
If not pre-mounted



820-6308-050

10000 Pcs


Legend of hinge cup symbols




Screw-on
ready
↓ screws







Machine
insertion
ready



Door adjustment

Side
adjustment
+3/-1mmHeight
adjustment
+2/-2mmDepth
adjustment
+5/-1.5mm

For further explanation → see pages 3.20-3.23

Mounting
detailsDrawings show application on
D=18mm thick mounting plateMounting plate
drilling distanceMounting plate thickness table
For further explanation → see page 3.11Drawings show application on
D=0mm thick mounting plateDrawings show application on
D=0mm thick mounting plate

K	3	4	5
D	0	1	2

Soft closing systems


Glissando TL
→ see page 2.15

Accessories

Cover caps for hinge arm
→ see page 3.151

Door clearance

For further explanation → see page 3.12





V	16	17	18	19	20	21	22
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5
4	0.3	0.5	0.7	0.9	1.2	1.6	2.1
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0

Gap $Z_{MIN}=0$

S-type 110/90°

For wood door cabinets with blind panels



- Opening angle 110°
- Drilling diameter for hinge cup 35mm
- Drilling depth 11.5mm
- Hinge on plate mounting system 'snap-on'



Cranking

18mm



Cup type	Interaxis 45mm	Interaxis 48mm	Interaxis 52mm
	Item number 248-0745-050	Item number 248-0742-050	Item number 248-0748-050
	Item number 248-0N24-050	Item number 248-0N25-050	Item number 248-0N26-050
	Item number 248-0L61-050	Item number 248-0N62-050	Item number 248-0Z81-050

Drilling patterns for hinge cups → see page 3.15

100 Pcs

Cup made of steel, arm made of zinc

Mounting plates



Cam adjustable mounting plate
→ see page 3.97



Steel mounting plates
→ see page 3.99




Zinc diecast mounting plates
→ see page 3.99



Face frame adapters
→ see page 3.101

Hinge cup screws *If not pre-mounted*



820-6308-050

10000 Pcs

Legend of hinge cup symbols




Screw-on
ready
← screws




Machine
insertion
ready



Easy-fix
system



Door adjustment



Side
adjustment
+3/-1mm


Height
adjustment
+2/-2mm

Depth
adjustment
+5/-1.5mm

For further explanation → see pages 3.20-3.23


Mounting details

Mounting plate drilling distance



Drawings show application on
 $D=0\text{mm}$ thick mounting plate

Drawings show application on
 $D=3\text{mm}$ thick mounting plate



Soft closing systems



Glissando TL
→ see page 2.15


Accessories



Cover caps for hinge arm
→ see page 3.151

Door clearance

For further explanation → see page 3.12




V	16	17	18	19	20	21	22	
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5	
4	0.3	0.5	0.7	0.9	1.2	1.6	2.1	
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0	F_{MIN}



Gap $Z_{MIN}=0$

S-type 110

For aluminium frame doors



110°




- Opening angle
- Hinge on plate mounting system

110°
'snap-on'




Cranking

0mm



Interaxis
28mm



Cup type



Item number

950-0T27-050



200 Pcs

Cup made of zinc, arm made of steel

Mounting plates



Cam adjustable
mounting plate
→ see page 3.97



Steel mounting
plates
→ see page 3.99




Zinc diecast
mounting plates
→ see page 3.99




Face frame adapters
→ see page 3.101

Door adjustment




For further explanation → see pages 3.20-3.23

Mounting details





Mounting plate drilling distance



Mounting plate thickness table

For further explanation → see page 3.11

x	12	13	14	15	16	17	18	D
17	3	2	1	0				
18		3	2	1	0			
19			3	2	1	0		
20				3	2	1	0	

Drawings show application on
D=0mm thick mounting plate

Drilling pattern for aluminium frame hinges


Screws included

Accessories

Cover caps for hinge arm
→ see page 3.151

Door clearance

For further explanation → see page 3.12




H	17	18	19	20	21	22	F _{MIN}
17	0.5	0.7	1.1	1.4	1.8	2.9	
18	0.5	0.7	1.0	1.3	1.7	2.5	
19	0.5	0.7	0.9	1.2	1.6	2.1	
20	0.5	0.7	0.9	1.2	1.5	2.0	



Gap Z_{MIN}=0.5

S-type 170

For wood doors



135°-165°




- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

135°-165°
35mm
12mm
'snap-on'



Cranking

0mm




50 Pcs

Made of steel and zinc

Cranking

0mm

With adjustable opening angle



Cup type	Interaxis 45mm	Interaxis 48mm	Interaxis 52mm
	248-0R14-050	248-0R17-050	248-0R15-050
	248-0M73-050	248-0R13-050	248-0M74-050
	248-0198-050		

Drilling patterns for hinge cups → see page 3.15

	248-0R18-050	*248-0V65-050	
		*248-0S69-050	
Drilling patterns for hinge cups → see page 3.15			
* Available upon special request → see page 0.3			
<i>Adjustable opening angle 135°</i>			



Adjustable opening angle 135°

50 Pcs

Made of steel and zinc

Mounting plates



Cam adjustable mounting plate
→ see page 3.97



Steel mounting plates
→ see page 3.99




Zinc diecast mounting plates
→ see page 3.99



Face frame adapters
→ see page 3.101

Hinge cup screws
If not pre-mounted



820-6308-050

10000 Pcs

Legend of hinge cup symbols




Screw-on ready
← screws




Machine insertion ready



Preinserted expando dowels




Door adjustment




Side
adjustment
+3/-1mm Height
adjustment
+2/-2mm Depth
adjustment
+5/-1.5mm

For further explanation → see pages 3.20-3.23

Mounting details



Mounting plate drilling distance

Mounting plate thickness table
For further explanation → see page 3.11

x	10	11	12	13	14	15	16	17	18	19	20
3	6	5	4	3	2	1	0				
4		6	5	4	3	2	1	0			
K	5		6	5	4	3	2	1	0		
6			6	5	4	3	2	1	0		
7				6	5	4	3	2	1	0	D

$$D = 13 + K \cdot x$$

Drawings show application on
D=0mm mounting plate

In 90° position the door is only
1.4mm distant from side panel

C value with D=0 mounting plates

K	3	4	5	6	7	D
C	-9.0	-8.1	-7.1	-6.1	-5.2	

Soft closing systems



Glissando TL 170
→ see page 2.17



Glissando CR
→ see page 2.19

Accessories



Push latch
→ see page 3.149

Door clearance

For further explanation → see page 3.12




V	16	17	18	19	20	21	22	23	24
3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
K	5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.6
7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.1 F_{MIN}


$$\text{Gap } Z_{MIN} = 0.5$$

S-type 170

For wood doors



135°-165°



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system


135°-165°
35mm
12mm
'snap-on'



Cup type	Interaxis 45mm	Interaxis 48mm	Interaxis 52mm
	Item number 248-0162-050	Item number 248-0163-050	Item number

Cranking

9mm



Drilling patterns for hinge cups → see page 3.15

50 Pcs

Made of steel and zinc

Mounting plates



Cam adjustable
mounting plate
→ see page 3.97



Steel mounting
plates
→ see page 3.99




Zinc diecast
mounting plates
→ see page 3.99



Face frame adapters
→ see page 3.101

Hinge cup screws *If not pre-mounted*



820-6308-050


10000 Pcs

Legend of hinge cup symbols

Screw-on
ready
← screws





Door adjustment




Side
adjustment
+3/-1mm Height
adjustment
+2/-2mm Depth
adjustment
+5/-1.5mm

For further explanation → see pages 3.20-3.23

Mounting details



Mounting plate drilling distance



Mounting plate thickness table

For further explanation → see page 3.11


x	1	2	3	4	5	6	7	8	9	10	11
K	6		3	2	1	0					
6		6		3	2	1	0				
7			6		3	2	1	0			
D											

$D=4+K \cdot x$


Drawings show application on
D=0mm thick mounting plate

C value with D=0 mounting plates


K	3	4	5	6	7
C	0	0.9	1.9	2.9	3.8
D					



Drawings show application on
D=0mm thick mounting plate



Drawings show application on
D=9mm thick mounting plate



Drawings show application on
D=18mm thick mounting plate

Soft closing systems



Glissando TL 170
→ see page 2.17



Glissando CR
→ see page 2.19


Accessories



Push latch
→ see page 3.149

Door clearance

For further explanation → see page 3.12




V	16	17	18	19	20	21	22	23	24
K	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.6
7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.1 F_{MIN}

Gap $Z_{MIN}=0.5$

S-type for Pie-cut Corner Cabinet

For wood doors




- Opening angle 110°
- Drilling diameter for hinge cup 35mm
- Drilling depth 11.5mm
- Hinge on plate mounting system 'snap-on'

	Interaxis 45mm	Interaxis 48mm	Interaxis 52mm
Cup type	Item number	Item number	Item number
	248-0U21-050	248-0U16-050	248-0308-050
	248-0U22-050	248-0V15-050	248-0Z20-050

Drilling patterns for hinge cups → see page 3.15



Corner cabinet



100 Pcs

Cup made of steel, arm made of zinc

Mounting plates



Cam adjustable mounting plate
→ see page 3.97




Steel mounting plates
→ see page 3.99



Zinc diecast mounting plates
→ see page 3.99

Hinge cup screws *If not pre-mounted*



820-6308-050

10000 Pcs


Legend of hinge cup symbols




Screw-on
ready
← screws



Machine
insertion
ready



Door adjustment





For further explanation → see pages 3.20-3.23


Mounting details

Mounting plate drilling distance


Adjustments



Any S-type-i mounting plate of thickness D=0 can be used



The diagonal adjustment is made by rotating the appropriate screw as shown on the drawing




Accessories

Cover caps for hinge arm
→ see page 3.151

S-type Mounting Plates



For all S-type concealed hinges



Cam adjustable
mounting plate


Drilling pattern

Dimensions



200 Pcs

Made of steel



Mounting plate thickness

Height adjustment +/- 2mm

Mounting plate type	13	15	T	M	10.5	
Mounting plate thickness (D)						
	Item number	Item number	Item number	Item number	Item number	
0mm	244-0258-050	244-0261-050	*244-0264-050	*244-0342-050	244-0270-050	
2mm	244-0259-050	244-0262-050	*244-0265-050	*244-0343-050	244-0271-050	
3mm	244-0260-050	244-0263-050	*244-0266-050	*244-0344-050	244-0272-050	


* Available upon special request ----> see page 0.3

Legend of mounting plate type symbols

Pre-mounted
13mm euro screwsPre-mounted
15mm euro screwsPre-mounted
chipboard screwsMachine
insertion readyPre-mounted
10.5mm
expanding dowels

S-type Mounting Plates



For all S-type concealed hinges



Steel mounting plates



Drilling pattern

Dimensions



200 Pcs


Made of steel



200 Pcs


Made of zinc

Fixing screws for mounting plates
If not pre-mounted




Euro screws
821-6304-050 L=11
821-6323-050 L=13
821-6332-050 L=15

5000 Pcs



Chipboard screws
820-6328-050

10000 Pcs



Mounting plate thickness

Height adjustment +/- 2mm

Mounting plate type			11	13	15			10.5
Mounting plate thickness (D)								
Item number	244-1136-050	244-1233-050	244-0Z26-050	244-0134-050	244-0118-050	244-0136-050	244-0166-050	244-0P26-050
0mm	244-1136-050	*244-1233-050	244-0Z26-050	244-0134-050	244-0118-050	*244-0136-050	*244-0166-050	244-0P26-050
1mm	244-1137-050	*244-1228-050		244-0561-050		*244-0565-050	*244-0567-050	
2mm	244-1138-050	*244-1229-050	244-0Z63-050	244-0562-050	244-0120-050	*244-0566-050	*244-0568-050	244-0V19-050
3mm	244-1139-050	*244-1234-050		244-0135-050	244-0119-050	*244-0137-050	*244-0167-050	244-0P27-050
6mm	244-1645-050				244-0Z51-050			

* Available upon special request → see page 0.3

* Mounting plates with premounted 7.5mm expanding dowels available upon special request → see page 0.3

9mm	244-3651-650			244-0M33-650	244-0P29-650			
18mm	244-3016-650			244-0085-650	244-0095-650			

* Available upon special request → see page 0.3

Legend of mounting plate type symbols

		11	13	15			10.5
Screw on ready for euro screws ← s crews	Screw-on ready for chipboard screws	Pre-mounted 11mm euro screws	Pre-mounted 13mm euro screws	Pre-mounted 15mm euro screws	Pre-mounted chipboard screws	Machine insertion ready	Pre-mounted 10.5mm expanding dowels

S-type


Face Frame Mounting Plates

For all S-type concealed hinges


Face frame adapter for
S-type hinges



Drilling pattern





Dimensions




 200 Pcs Made of zinc alloy

Face frame adapter for
S-type hinges
cam adjustable




 200 Pcs Made of zinc alloy

Fixing screw for mounting plates
If not pre-mounted




Chipboard screws
820-6328-050

 10000 Pcs



Mounting plate thickness



Height adjustment +/- 2mm


Mounting plate type		
Mounting plate thickness (D)		
Item number		
0mm	244-3653-650	
3mm	244-3654-650	
6mm	244-3655-650	

0mm	248-3600-650	
3mm	248-3603-650	


Legend of mounting plate type symbols



Screw-on ready for
chipboard screws
← screws



B-type Hinges




'Slide-on' mounting system

- Proven and reliable hinge-to-plate mounting solution
- Cost effectiveness



Designed for a wide use

- Solution for different applications and materials
- Proven solution for RTA furniture, household application and tall cabinets



'ConfidentClose'

- 1 Fast closing
- 2 Late start of deceleration action
- 3 Quiet landing with 'SoftTouch'



Soft closing options

- Hinge integrated
- Add-on with Glissando ready hinge cup
- Stand-alone
- Rigid slide-on hinge design enables optimal performance when used with soft closer






Adjustable damping

- Adjustable damping assures perfect functioning on every door

B-type-i 110

For wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

110°
35mm
min. 11mm
slide-on





Technical details

	Interaxis 45mm	Interaxis 48mm
Cup type		
Item number	954-0B97-050	954-0C01-050

Cranking

0mm



200 Pcs



Made of steel and plastic

954-0B97-050 954-0C01-050

Drilling patterns for hinge cups → see page 3.15

Cranking

9mm



200 Pcs



Made of steel and plastic

954-0B98-050 954-0C02-050

Drilling patterns for hinge cups → see page 3.15

Cranking

15mm



200 Pcs

Made of steel and plastic

954-0B99-050 954-0C03-050

Drilling patterns for hinge cups → see page 3.15

Mounting plates




Steel mounting plates
→ see page 3.135



Zinc diecast mounting plates
→ see page 3.135

Hinge cup screws
If not pre-mounted



820-6308-050

10000 Pcs

Accessories



Cover caps for hinge arm
→ see page 3.151


Legend of hinge cup symbols




Screw-on
ready
← screws



Damping adjustment



Door adjustment



Side
adjustment
 $+3/-0.5\text{mm}$


Height
adjustment
 $+2/-2\text{mm}$

Depth
adjustment
 $+4/-0\text{mm}$

For further explanation → see page 3.25


For further explanation → see pages 3.20-3.23

Mounting details



Drawings show application on
 $D=0\text{mm}$ thick mounting plate

Mounting plate drilling distance




Mounting plate thickness table

For further explanation → see page 3.11

x	10	11	12	13	14	15	16	17	18
3	6	5	4	3	2	1	0	0	
K	4		6	5	4	3	2	1	0
5			6	5	4	3	2	1	0

$$D=13+K-x$$




Drawings show application on
 $D=0\text{mm}$ thick mounting plate




x	0	1	2	3	4	5	6	7	8	9
3		6	5	4	3	2	1	0		
K	4		6	5	4	3	2	1	0	
5	9		6	5	4	3	2	1	0	D

$$D=4+K-x$$



Drawings show application on
 $D=3\text{mm}$ thick mounting plate




V	16	17	18	19	20	21	22
3	2	2	2	3	3	3	4
K	4	3	3	4	4	4	5
5	4	4	4	5	5	5	6

$$D=-2+K+F$$

Door clearance

For further explanation → see page 3.12



V 16 17 18 19 20 21 22



3	0.3	0.5	0.7	1.0	1.3	1.7	2.5	
K	4	0.3	0.5	0.7	0.9	1.2	1.6	2.1

5	0.3	0.5	0.7	0.9	1.2	1.5	2.0	F_{MIN}
---	-----	-----	-----	-----	-----	-----	-----	-----------

Gap $Z_{MIN}=0$

B-type-i 110/30°

30° angled application for wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

110°
35mm
min. 11mm
slide-on





Technical details

	Interaxis 45mm	Interaxis 48mm
Cup type		
Item number	954-0153-650	954-0147-650

Cranking

9mm



Drilling patterns for hinge cups → see page 3.15

100 Pcs

Cup made of steel and plastic, arm made of zinc

Mounting plates




Steel mounting plates
→ see page 3.135



Zinc diecast mounting plates
→ see page 3.135

Hinge cup screws
If not pre-mounted



820-6308-050

10000 Pcs

Legend of hinge cup symbols



Screw-on
ready
screws


Accessories




Cover caps for hinge arm
→ see page 3.151



Damping adjustment





Door adjustment



Side
adjustment
+3/-0.5mmHeight
adjustment
+2/-2mmDepth
adjustment
+4/-0mm

For further explanation → see page 3.25

For further explanation → see pages 3.20-3.23


Mounting
detailsMounting plate
drilling distanceMounting plate thickness table
For further explanation → see page 3.11

P	2.5	3.5	4.5	8.5	9.5	10.5	11.5	12.5	13.5
3	9			3	2	1	0		
K	4			3	2	1	0		
5				9		3	2	1	0
								D	

Drawings show application on
D=3mm thick mounting plateDrawings show application on
D=3mm thick mounting plate

L=37 for thickness D=0
L=36 for thickness D=1
L=35 for thickness D=2
L=34 for thickness D=3
L=31 for thickness D=9

x	2	3	4	9	10	11	12	13	14	15
3	9			3	2			0		
K	4			3	2			0		
5				9		3	2	0		D



Door clearance
For further explanation → see page 3.12

V	16	17	18	19	20	21	22	
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5	
K	4	0.3	0.5	0.7	0.9	1.2	1.6	2.1
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0	F _{MIN}

Gap Z_{MIN}=0

B-type-i 110/45°

45° angled application for wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

110°
35mm
min. 11mm
slide-on





Technical details

	Interaxis 45mm	Interaxis 48mm
Cup type		
Item number	954-0154-650	954-0148-650

Cranking

9mm



Drilling patterns for hinge cups → see page 3.15



Cup made of steel and plastic, arm made of zinc

Mounting plates




Steel mounting plates
→ see page 3.135



Zinc diecast mounting plates
→ see page 3.135

Hinge cup screws
If not pre-mounted



820-6308-050

10000 Pcs

Legend of hinge cup symbols



Screw-on
ready
screws


Accessories




Cover caps for hinge arm
→ see page 3.151



Damping adjustment




Door adjustment



Side
adjustment
+3/-0.5mmHeight
adjustment
+2/-2mmDepth
adjustment
+4/-0mm

For further explanation → see page 3.25


For further explanation → see pages 3.20-3.23

Mounting
detailsMounting plate
drilling distanceMounting plate thickness table
For further explanation → see page 3.11

	P	9	9.5	10	10.5	11	11.5	12	12.5	13.5
K	3	3	2	1	0					
	4		3	2	1	0				
	5			3	2	1	0			D

Drawings show application on
D=3mm thick mounting plate

x	11.5	12.5	13	13.5	14	14.5	15	15.5	16	16.5	17	18
K	3	3	2		1		0					
	4		3	2	1	0						
	5			3	2	1	0					D



Drawings show application on
D=3mm thick mounting plateL=36 for thickness D=0
L=35 for thickness D=1
L=34 for thickness D=2
L=33 for thickness D=3Door clearance
For further explanation → see page 3.12

V	16	17	18	19	20	21	22
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5
4	0.3	0.5	0.7	0.9	1.2	1.6	2.1
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0

Gap Z_{MIN}=0 F_{MIN}

B-type-i 110/45°

45° angled application for wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

110°
35mm
min. 11mm
slide-on





Technical details

	Interaxis 45mm	Interaxis 48mm
Cup type		
Item number	954-0158-650	954-0168-650

Cranking

18mm



Drilling patterns for hinge cups → see page 3.15



200 Pcs Cup made of steel and plastic, arm made of zinc

Mounting plates




Steel mounting plates
→ see page 3.135



Zinc diecast mounting plates
→ see page 3.135

Hinge cup screws
If not pre-mounted



820-6308-050

10000 Pcs

Accessories



Cover caps for hinge arm
→ see page 3.151


Legend of hinge cup symbols




Screw-on
ready
screws



Damping adjustment








Door adjustment

Side
adjustment
+3/-0.5mmHeight
adjustment
+2/-2mmDepth
adjustment
+4/-0mm


For further explanation → see page 3.25

For further explanation → see pages 3.20-3.23

Mounting
detailsDrawings show application on
D=18mm thick mounting plateMounting plate
drilling distanceDrawings show application on
D=0mm thick mounting plateMounting plate thickness table
For further explanation → see page 3.11Drawings show application on
D=0mm thick mounting plate

3	0
K	4
5	2

D



L=36 for thickness D=0
L=35 for thickness D=1
L=34 for thickness D=2
L=33 for thickness D=3Door clearance
For further explanation → see page 3.12

V	16	17	18	19	20	21	22	
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5	
K	4	0.3	0.5	0.7	0.9	1.2	1.6	2.1
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0	F _{MIN}

Gap Z_{MIN}=0

B-type-i 110/90°

For wood door cabinets with blind panels



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

110°
35mm
min. 11mm
slide-on




Technical details

	Interaxis 45mm	Interaxis 48mm
Cup type		
Item number	954-0159-650	954-0149-650

Cranking

18mm



Drilling patterns for hinge cups → see page 3.15

200 Pcs

Cup made of steel and plastic, arm made of zinc

Blind panel
mounting
plate



244-0810-650

15 244-0810-650

This mounting plate can be used only
with B-type-i 110/90° hinges.
Information about mounting plate symbols
→ see page 3.135

200 Pcs


Cup made of steel and plastic, arm made of zinc

Mounting plates



These hinges can only
be used with blind panel
mounting plates

Hinge cup screws
If not pre-mounted



820-6308-050

10000 Pcs

Legend of hinge cup symbols

Screw-on
ready
 screws


Accessories




Cover caps for hinge arm
→ see page 3.151



Damping adjustment






Door adjustment

Side
adjustment
+3/-0.5mmHeight
adjustment
+2/-2mmDepth
adjustment
+4/-0mm

For further explanation → see page 3.25

For further explanation → see pages 3.20-3.23

Mounting
detailsMounting plate
drilling distanceDoor clearance
For further explanation → see page 3.12




V	16	17	18	19	20	21	22
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5
4	0.3	0.5	0.7	0.9	1.2	1.6	2.1
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0

F_{MIN}

Gap Z_{MIN}=0

B-type 110

For wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

110°
35mm
min. 11.5mm
slide-on




Technical details

	Interaxis 45mm	Interaxis 48mm	Interaxis 52mm
Cup type	Item number	Item number	Item number
	248-0G54-050	248-0G49-050	248-0G59-050
	248-0G79-050	248-0K40-050	248-0L63-050

Drilling patterns for hinge cups → see page 3.15

Cranking

0mm




200 Pcs

Made of steel

Cranking

9mm




200 Pcs

Made of steel

Cranking

15mm



200 Pcs

Made of steel

Mounting plates




Steel mounting plates
→ see page 3.135



Zinc diecast mounting plates
→ see page 3.135

Hinge cup screws
If not pre-mounted



820-6308-050

10000 Pcs


Legend of hinge cup symbols




Screw-on ready
← screws



Machine insertion ready





Door adjustment





Side
adjustment
+3/-0.5mm Height
adjustment
+2/-2mm Depth
adjustment
+4/-0mm

For further explanation → see pages 3.20-3.23

Mounting details



Drawings show application on
D=0mm thick mounting plate

Mounting plate
drilling distance



Drawings show application on
D=0mm thick mounting plate

Mounting plate thickness table


For further explanation → see page 3.11

x	10	11	12	13	14	15	16	17	18
3	6	5	4	3	2	1	0	0	
K	4		6	5	4	3	2	1	0
5			6	5	4	3	2	1	0

$$D = 13 + K - x$$





Drawings show application on
D=0mm thick mounting plate




37

x	0	1	2	3	4	5	6	7	8	9
3		6	5	4	3	2	1	0		
K	4		6	5	4	3	2	1	0	
5	9		6	5	4	3	2	1	0	D

$$D = 4 + K - x$$



Drawings show application on
D=3mm thick mounting plate



37+V

V	16	17	18	19	20	21	22
3	2	2	2	3	3	3	4
K	4	3	3	4	4	4	5
5	4	4	4	5	5	5	6

$$D = -2 + K + F$$

Soft closing systems



Glissando TL
→ see page 2.15



Glissando CR
→ see page 2.19

Accessories




Cover caps for hinge arm
→ see page 3.151



Push latch
→ see page 3.149

Door clearance

For further explanation → see page 3.12



V	16	17	18	19	20	21	22	
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5	
K	4	0.3	0.5	0.7	0.9	1.2	1.6	2.1

V	16	17	18	19	20	21	22	
3	0.3	0.5	0.7	0.9	1.2	1.5	2.0	
K	4	0.3	0.5	0.7	0.9	1.2	1.6	2.1

V	16	17	18	19	20	21	22	
3	0.3	0.5	0.7	0.9	1.2	1.5	2.0	
K	4	0.3	0.5	0.7	0.9	1.2	1.6	2.1

V	16	17	18	19	20	21	22	
3	0.3	0.5	0.7	0.9	1.2	1.5	2.0	
K	4	0.3	0.5	0.7	0.9	1.2	1.6	2.1

V	16	17	18	19	20	21	22	
3	0.3	0.5	0.7	0.9	1.2	1.5	2.0	
K	4	0.3	0.5	0.7	0.9	1.2	1.6	2.1

V	16	17	18	19	20	21	22	
3	0.3	0.5	0.7	0.9	1.2	1.5	2.0	
K	4	0.3	0.5	0.7	0.9	1.2	1.6	2.1

V	16	17	18	19	20	21	22	
3	0.3	0.5	0.7	0.9	1.2	1.5	2.0	
K	4	0.3	0.5	0.7	0.9	1.2	1.6	2.1

V	16	17	18	19	20	21	22	
3	0.3	0.5	0.7	0.9	1.2	1.5	2.0	
K	4	0.3	0.5	0.7	0.9	1.2	1.6	2.1

V	16	17	18	19	20	21	22	
3	0.3	0.5	0.7	0.9	1.2	1.5	2.0	
K	4	0.3	0.5	0.7	0.9	1.2	1.6	2.1

V	16	17	18	19	20	21	22	
3	0.3	0.5	0.7	0.9	1.2	1.5	2.0	
K	4	0.3	0.5	0.7	0.9	1.2	1.6	2.1



V	16	17	18	19	20	21	22	
3	0.3	0.5	0.7	0.9	1.2	1.5	2.0	
K	4	0.3	0.5	0.7	0.9	1.2	1.6	2.1

V	16	17	18	19	20	21	22	
3	0.3	0.5	0.7	0.9	1.2	1.5	2.0	
K	4	0.3	0.5	0.7	0.9	1.2	1.6	2.1

<tbl_struct

B-type 110/30°

30° angled application for wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system


110°
35mm
11.5mm
slide-on




Technical details

Cup type


Interaxis
45mm



Interaxis
48mm



Interaxis
52mm




Item number

Item number

Item number

Cranking

9mm



248-0G57-050 248-0G52-050 248-0G62-050

248-0G82-050 248-0L72-050

Drilling patterns for hinge cups → see page 3.15

200 Pcs

Cup made of steel, arm made of zinc

Mounting plates




Steel mounting plates
→ see page 3.135



Zinc diecast mounting plates
→ see page 3.135

Hinge cup screws
If not pre-mounted



820-6308-050

10000 Pcs

Legend of hinge cup symbols




Screw-on
ready
← screws





Machine
insertion
ready





Door adjustment

Side
adjustment
+3/-0.5mmHeight
adjustment
+2/-2mmDepth
adjustment
+4/-0mm

For further explanation → see pages 3.20-3.23

Mounting
detailsMounting plate
drilling distanceMounting plate thickness table
For further explanation → see page 3.11

P	2.5	3.5	4.5	8.5	9.5	10.5	11.5	12.5	13.5
3	9			3	2	1	0		
K 4		9			3	2	1	0	
5			9			3	2	1	0
								D	

Drawings show application on
D=3mm thick mounting plate

x	2	3	4	9	10	11	12	13	14	15
3	9			3	2			0		
K 4		9			3	2		0		
5			9			3	2		0	
								D		

Drawings show application on
D=3mm thick mounting plateL=37 for thickness D=0
L=36 for thickness D=1
L=35 for thickness D=2
L=34 for thickness D=3
L=31 for thickness D=9


Soft closing systems

Glissando TL
→ see page 2.15

Accessories

Cover caps for hinge arm
→ see page 3.151

Door clearance



For further explanation → see page 3.12

V	16	17	18	19	20	21	22	F _{MIN}
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5	
K 4	0.3	0.5	0.7	0.9	1.2	1.6	2.1	
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0	F _{MIN}

Gap Z_{MIN}=0

B-type 110/45°

45° angled application for wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system


110°
35mm
11.5mm
slide-on




Technical details

Cup type


Interaxis
45mm



Interaxis
48mm



Interaxis
52mm



Item number

248-0L32-650

248-0L27-650

248-0M83-050

Item number


248-0N38-050

248-0L71-050

Item number

Cranking

9mm



200 Pcs

Cup made of steel, arm made of zinc

Mounting plates




Steel mounting plates
→ see page 3.135



Zinc diecast mounting plates
→ see page 3.135

Hinge cup screws
If not pre-mounted



820-6308-050

10000 Pcs


Legend of hinge cup symbols




Screw-on
ready
← screws




Machine
insertion
ready





Door adjustment

Side
adjustment
+3/-0.5mmHeight
adjustment
+2/-2mmDepth
adjustment
+4/-0mm

For further explanation → see pages 3.20-3.23

Mounting
detailsMounting plate
drilling distanceMounting plate thickness table
For further explanation → see page 3.11

P	9	9.5	10	10.5	11	11.5	12	12.5	13.5
K	3		2		1		0		
D									

Drawings show application on
D=3mm thick mounting plate

x	11.5	12.5	13	13.5	14	14.5	15	15.5	16	16.5	17	18
3	3		2		1		0					
K	4		3		2		1		0			
D												

Drawings show application on
D=3mm thick mounting plateL=36 for thickness D=0
L=35 for thickness D=1
L=34 for thickness D=2
L=33 for thickness D=3

Soft closing systems


Glissando TL
→ see page 2.15

Accessories

Cover caps for hinge arm
→ see page 3.151

Door clearance

For further explanation → see page 3.12





V	16	17	18	19	20	21	22	
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5	
K	4	0.3	0.5	0.7	0.9	1.2	1.6	2.1
F _{MIN}								

Gap Z_{MIN}=0

B-type 110/45°

45° angled application for wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system


110°
35mm
11.5mm
slide-on

Technical details	Cup type	Interaxis 45mm	Interaxis 48mm	Interaxis 52mm
		Item number	Item number	Item number
Cranking 18mm		248-0L33-050	248-0L28-050	248-0M84-050
		248-0L46-050	248-0L70-050	

Drilling patterns for hinge cups → see page 3.15

Cranking

18mm



200 Pcs

Cup made of steel, arm made of zinc

Mounting plates




Steel mounting plates
→ see page 3.135



Zinc diecast mounting plates
→ see page 3.135

Hinge cup screws
If not pre-mounted



820-6308-050

10000 Pcs

Legend of hinge cup symbols




Screw-on
ready
← screws








Machine
insertion
ready



Door adjustment

Side
adjustment
+3/-0.5mmHeight
adjustment
+2/-2mmDepth
adjustment
+4/-0mm

For further explanation → see pages 3.20-3.23

Mounting
detailsDrawings show application on
D=18mm thick mounting plateDrawings show application on
D=0mm thick mounting plateMounting plate
drilling distanceMounting plate thickness table
For further explanation → see page 3.11Drawings show application on
D=3mm thick mounting plate

3	0
K	4
5	2

D

Soft closing systems


Glissando TL
→ see page 2.15

Accessories

Cover caps for hinge arm
→ see page 3.151

Door clearance

For further explanation → see page 3.12





V	16	17	18	19	20	21	22
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5
K	0.3	0.5	0.7	0.9	1.2	1.6	2.1
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0

Gap Z_{MIN}=0

B-type 110/90°

For wood door cabinets with blind panels



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

110°
35mm
11.5mm
slide-on




Technical details

	Interaxis 45mm	Interaxis 48mm	Interaxis 52mm
Cup type	Item number	Item number	Item number
	248-0G58-050	248-0G53-050	248-0G63-050
	248-0G83-050	248-0L73-050	

Drilling patterns for hinge cups → see page 3.15

Cranking

18mm




200 Pcs

Cup made of steel, arm made of zinc

Cranking

0mm



200 Pcs

Cup made of steel, arm made of zinc

Cranking



244-0810-650

244-0813-650

244-0C32-650

244-0P28-650

200 Pcs

Made of zinc


This mounting plate can be used only with B-type 110/90° hinges.
Information about mounting plate symbols → see page 3.135

Mounting plates



These hinges can only be used with blind panel mounting plates

Hinge cup screws
If not pre-mounted



820-6308-050

10000 Pcs

Legend of hinge cup symbols




Screw-on
ready
← screws




Machine
insertion
ready








Pre-
mounted
euro screws



Door adjustment

Side
adjustment
+3/-0.5mmHeight
adjustment
+2/-2mmDepth
adjustment
+4/-0mm

For further explanation → see pages 3.20-3.23

Mounting
detailsMounting plate
drilling distance

Soft closing systems


Glissando TL
→ see page 2.15

Accessories

Cover caps for hinge arm
→ see page 3.151

Door clearance

For further explanation → see page 3.12






V	16	17	18	19	20	21	22
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5
4	0.3	0.5	0.7	0.9	1.2	1.6	2.1
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0

Gap $Z_{\text{MIN}}=0$

B-type 110

For aluminium frame doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

110°
35mm
11.5mm
slide-on



Technical details	Cup type	Item number
		Interaxis 28mm
Cranking 0mm	●	950-0T26-050

Cranking

0mm



200 Pcs

Cup made of zinc, arm made of steel

Mounting plates




Steel mounting plates
→ see page 3.135





Zinc diecast mounting plates
→ see page 3.135



Door adjustment

Side
adjustment
+3/-0.5mmHeight
adjustment
+2/-2mmDepth
adjustment
+4/-0mm

For further explanation → see pages 3.20-3.23

Mounting
detailsMounting plate
drilling distanceMounting plate thickness table
For further explanation → see page 3.11

x	12	13	14	15	16	17	18	D
G	17	3	2	1	0			
	18	4	3	2	1	0		
	19	5	4	3	2	1	0	
	20	6	5	4	3	2	1	0

Drawings show application on
D=0mm thick mounting plate

Drilling pattern for aluminium frame hinges


Screws included

Accessories

Cover caps for hinge arm
→ see page 3.151

Door clearance

For further explanation → see page 3.12




H	17	18	19	20	21	22	F _{MIN}
G	17	0.5	0.7	1.1	1.4	1.8	2.9
	18	0.5	0.7	1.0	1.3	1.7	2.5
	19	0.5	0.7	0.9	1.2	1.6	2.1
	20	0.5	0.7	0.9	1.2	1.5	2.0



Gap Z_{MIN}=0.5

B-type 170

For wood doors



135°-165°



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

135°-165°
35mm
112mm
slide-on




Technical details

Cup type	Interaxis 45mm	Interaxis 48mm	Interaxis 52mm
	 45 mm	 48 mm	 52 mm
	Item number 248-0R10-050	Item number 248-0P43-050	Item number 248-0R11-050

Cranking

0mm



50 Pcs

Made of steel and zinc

Cranking

0mm


With adjustable opening angle



Drilling patterns for hinge cups → see page 3.15

Drilling patterns for hinge cups → see page 3.15

* Available upon special request → see page 0.3



Adjustable opening angle

50 Pcs

Made of steel and zinc

Mounting plates




Steel mounting plates
→ see page 3.135



Zinc diecast mounting plates
→ see page 3.135

Hinge cup screws
If not pre-mounted



820-6308-050

10000 Pcs


Legend of hinge cup symbols




Screw-on ready
← screws



Machine insertion ready




- Enable better accessibility into cabinet interior due to the wider opening angle
- Opening angle can be easily adjusted by rotating the appropriate screw on hinge arm




For further explanation → see pages 3.20-3.23

Mounting details



Drawings show application on
D=0mm mounting plate

Mounting plate drilling distance



Mounting plate thickness table

For further explanation → see page 3.11

x	10	11	12	13	14	15	16	17	18	19	20
3	6	5	4	3	2	1	0				
4		6	5	4	3	2	1	0			
K			6	5	4	3	2	1	0		
5				6	5	4	3	2	1	0	
6					6	5	4	3	2	1	0
7						6	5	4	3	2	1
											D

$$D = 13 + K \cdot x$$

C value with D=0 mounting plates

K	3	4	5	6	7	D
C	-9.0	-8.1	-7.1	-6.1	-5.2	

Soft closing systems




Accessories



Door clearance

For further explanation → see page 3.12




V	16	17	18	19	20	21	22	23	24
3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
K									
5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.6
7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.1 F _{MIN}


Gap Z_{MIN}=0

B-type 170

For wood doors



135°-165°




- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

135°-165°
35mm
112mm
slide-on



Cranking

9mm



	Interaxis 45mm	Interaxis 48mm	Interaxis 52mm
Cup type	Item number	Item number	Item number
	248-0160-050	248-0161-050	

Drilling patterns for hinge cups → see page 3.15



50 Pcs

Made of steel and zinc

Mounting plates




Steel mounting plates
→ see page 3.135



Zinc diecast mounting plates
→ see page 3.135

Hinge cup screws
If not pre-mounted



820-6308-050




Legend of hinge cup symbols



Screw-on
ready
screws





- Enable better accessibility into cabinet interior due to the wider opening angle
- Opening angle can be easily adjusted by rotating the appropriate screw on hinge arm




For further explanation → see pages 3.20-3.23

Mounting details



Mounting plate drilling distance



Mounting plate thickness table

For further explanation → see page 3.11


x	1	2	3	4	5	6	7	8	9	10	11
3	6	5	4	3	2	1	0				
4		6	5	4	3	2	1	0			
K	5		6	5	4	3	2	1	0		
6			6	5	4	3	2	1	0		
7				6	5	4	3	2	1	0	D

$$D=4+K-x$$


Drawings show application on D=0mm thick mounting plate

C value with D=0 mounting plates


K	3	4	5	6	7
C	0	0.9	1.9	2.9	3.8



Drawings show application on D=0mm thick mounting plate



Drawings show application on D=9mm thick mounting plate



Drawings show application on D=18mm thick mounting plate

Soft closing systems



Glissando TL 170
→ see page 2.17



Glissando CR
→ see page 2.19


Accessories



Push latch
→ see page 3.149

Door clearance

For further explanation → see page 3.12




V	16	17	18	19	20	21	22	23	24
3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
K	5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.6
7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.1 F _{MIN}

Gap Z_{MIN}=0

B-type

for Pie-cut Corner Cabinet

For wood doors




- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

35mm
11.5mm
slide-on




Corner cabinet



100 Pcs


Cup made of steel, arm made of zinc

Interaxis
45mm



Cup type

Interaxis
48mm



Item number

Item number

248-0T81-050 248-0T80-050

248-0U13-050 248-0U14-050

Drilling patterns for hinge cups → see page 3.15

Mounting plates




Steel mounting plates
→ see page 3.135



Zinc diecast mounting plates
→ see page 3.135

Hinge cup screws
If not pre-mounted




820-6308-050

10000 Pcs


Legend of hinge cup symbols

Screw-on ready
← screws

Machine insertion ready



Door adjustment





For further explanation → see pages 3.20-3.23


Mounting details

Mounting plate drilling distance


Adjustments



Any B-type mounting plate of thickness D=0 can be used.



The diagonal adjustment is made by rotating the appropriate screw as shown on the drawing.




Accessories

Cover caps for hinge arm
→ see page 3.151

B-type

Flap door hinge

For wood doors



- Opening angle
 - Drilling diameter for hinge cup
 - Drilling depth
 - Hinge on plate mounting system

90°
35mm
11.5mm
slide-on



200 Pcs

Cup made of steel

Mounting plates




**Steel mounting
plates**
→ see page 3.135



Zinc diecast
mounting plates
→ see page 3.135

Hinge cup screws
If not pre-mounted



820-6308-050



 10000 Pcs

Legend of hinge cup symbols




Screw-on
ready
← screws



- To be used with flap stay mechanisms
- Mounted on the cabinet side
- Standard drillings

Door adjustment




Side
adjustment
+0.5/-0.5mm

Height
adjustment
+2/-2mm

Depth
adjustment
+4/-0mm

For further explanation → see pages 3.20-3.23

Mounting details




Mounting plate thickness table

For further explanation → see page 3.11

D	0	1	2	3
B (mm)	20	21	22	23

D=mounting plate height
X=22.5 + K - A +/-2mm height adjustment



Accessories



Cover caps for hinge arm
→ see page 3.151

Door clearance

For further explanation → see page 3.12




V	16	17	18	19	20	21	22	F _{MIN}
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5	
4	0.3	0.5	0.7	0.9	1.2	1.6	2.1	
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0	

Gap Z_{MIN}=0

B-type Mounting Plates

For B-type concealed hinges



Steel mounting plates

Drilling pattern





Dimensions



200 Pcs

Made of steel


Zinc diecast mounting plates



200 Pcs


Made of zinc

Fixing screws for mounting plates
If not pre-mounted




Euro screws
821-6304-050 L=11
821-6323-050 L=13
821-6332-050 L=15

10000 Pcs



Chipboard screws
820-6328-050

10000 Pcs




Mounting plate thickness

Height adjustment +/- 2mm


Mounting plate type			13	15			7.5	10.5
Mounting plate thickness (D)								
0mm	244-0866-050	*244-0L29-050	244-0965-050	244-0929-050	*244-0L26-050	*244-0L50-050	244-0H64-050	244-0P24-050
1mm	244-0T40-050		244-0K95-050		*244-0S65-050		244-0S67-050	
2mm	244-0T28-050		244-0K96-050		*244-0S66-050	*244-0V64-050	244-0S68-050	
3mm	244-0867-050	*244-0L39-050	244-0G19-050	244-0930-050	*244-0L98-050	*244-0L40-050	244-0H65-050	244-0P25-050
	* Available upon special request → see page 0.3							
4mm	244-0L37-650		244-0K97-650				244-0M28-650	
5mm	244-0L38-650		244-0K98-650	244-0T14-650			244-0M29-650	
6mm	244-0232-650		244-0914-650			*244-0B12-650		
9mm	244-0062-650		244-0067-650	244-0P41-650				
18mm	244-0063-650		244-0068-650	244-0175-650				
	* Available upon special request → see page 0.3							

Legend of mounting plate type symbols



B-type Mounting Plates

For B-type concealed hinges






Drilling pattern

Dimensions

Steel mounting plates



- Back-to back application



200 Pcs Made of steel


Zinc diecast mounting plates

- For 18mm inset doors




200 Pcs Made of zinc

Fixing screws for mounting plates
If not pre-mounted





Euro screws
821-6304-050 L=11
821-6323-050 L=13
821-6332-050 L=15

10000 Pcs



Chipboard screws
820-6328-050

10000 Pcs



Mounting plate type			
Mounting plate thickness (D)			
Item number			
3mm		244-0V50-050	
2mm	244-0036-650		
Fits standard 37mm drilling			

Legend of mounting plate type symbols



Screw on ready
for euro screws
← screws






Pre-mounted
10.5mm
expanding dowels



B-type Hinge Ø40

For wood doors

For Door Thickness up to 40mm



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system


93°
40mm
14.5mm
slide-on



	Interaxis 52mm
Cup type	Item number

Cranking

0mm



249-7301-050


Drilling patterns for hinge cups →
see page 3.15

200 Pcs

Made of steel

Cranking

10mm



249-7302-050

Drilling patterns for hinge cups →
see page 3.15

200 Pcs


Made of steel

Mounting plates



Steel
mounting plate
→ see page 3.143

Hinge cup screws
If not pre-mounted



820-6308-050

10000 Pcs

Legend of hinge cup symbols

Screw-on
ready
← screws



Soft closing systems




Glissando CR
→ see page 2.19

Accessories




Push latch
→ see page 3.149

Door adjustment

Side
adjustment
+2/-1mmHeight
adjustment
+2/-2mmDepth
adjustment
+4/-0mm


For further explanation → see pages 3.20-3.23

Mounting
details

Mounting plate thickness table

For further explanation → see page 3.11

x	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32
K	3	8	7	6	5	4	3	2	1	0					
4		8	7	6	5	4	3	2	1	0					
5			8	7	6	5	4	3	2	1	0				
6				8	7	6	5	4	3	2	1	0			
7					8	7	6	5	4	3	2	1	0		
8						8	7	6	5	4	3	2	1	0	
9							8	7	6	5	4	3	2	1	0
10								8	7	6	5	4	3	2	1
11									8	7	6	5	4	3	2
12										8	7	6	5	4	3
D															






x	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22
K	3	8	7	6	5	4	3	2	1	0					
4		8	7	6	5	4	3	2	1	0					
5			8	7	6	5	4	3	2	1	0				
6				8	7	6	5	4	3	2	1	0			
7					8	7	6	5	4	3	2	1	0		
8						8	7	6	5	4	3	2	1	0	
9							8	7	6	5	4	3	2	1	0
10								8	7	6	5	4	3	2	1
11									8	7	6	5	4	3	2
12										8	7	6	5	4	3
D															

Door clearance (Fmin)	x	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	38	40	Z
K	3	0.4	0.6	0.7	0.8	1.0	1.2	1.4	1.6	1.6	2.0	2.3	2.3	2.6	2.8	3.2	6.1	9.0	10.9	0.4
4		0.4	0.6	0.7	0.8	1.0	1.2	1.4	1.6	1.6	2.0	2.3	2.3	2.6	2.8	3.1	5.3	8.2	10.2	0.4
5		0.4	0.5	0.7	0.8	1.0	1.2	1.3	1.5	1.5	2.0	2.2	2.2	2.5	2.8	3.1	4.7	7.5	9.4	0.4
6		0.4	0.5	0.7	0.8	1.0	1.1	1.3	1.5	1.5	2.0	2.2	2.2	2.4	2.7	3.0	4.1	6.8	8.7	0.4
7		0.4	0.5	0.6	0.8	1.0	1.1	1.3	1.5	1.5	1.9	2.2	2.2	2.4	2.7	3.0	3.6	6.2	8.0	0.4
8		0.4	0.5	0.6	0.8	0.9	1.1	1.3	1.5	1.5	1.9	2.1	2.1	2.4	2.6	2.9	3.5	5.6	7.4	0.4
9		0.4	0.5	0.6	0.8	0.9	1.1	1.3	1.4	1.4	1.9	2.1	2.1	2.4	2.6	2.9	3.5	5.1	6.8	0.4
10		0.4	0.5	0.6	0.8	0.9	1.1	1.2	1.4	1.4	1.8	2.1	2.1	2.3	2.6	2.8	3.4	4.6	6.3	0.4
11		0.4	0.5	0.6	0.8	0.9	1.1	1.2	1.4	1.4	1.8	2.0	2.0	2.3	2.5	2.8	3.4	4.1	5.8	0.4
12		0.4	0.5	0.6	0.7	0.9	1.0	1.2	1.4	1.4	1.8	2.0	2.0	2.3	2.5	2.8	3.3	4.1	5.4	F _{MIN} 0.4

B-type Hinge Ø40


For wood doors

For Door Thickness up to 40mm




- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system


93°
40mm
14.5mm
slide-on



Cranking
18mm



Interaxis
52mm



Cup type Item number

249-7303-050

Drilling patterns for hinge cups → see page 3.15

200 Pcs

Made of steel

Cranking

22mm



249-7304-650

Drilling patterns for hinge cups → see page 3.15

200 Pcs


Made of steel

Mounting plates



Steel mounting plate
→ see page 3.143

Hinge cup screws
If not pre-mounted



820-6308-050


10000 Pcs

Legend of hinge cup symbols

Screw-on ready ← screws




Door adjustment

Side
adjustment
+2/-1mmHeight
adjustment
+2/-2mmDepth
adjustment
+4/-0mm

For further explanation → see pages 3.20-3.23


Mounting details



Mounting plate thickness table

For further explanation → see page 3.11

	x	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
K	3	8	7	6	5	4	3	2	1	0								
4		8	7	6	5	4	3	2	1	0								
5			8	7	6	5	4	3	2	1	0							
6				8	7	6	5	4	3	2	1	0						
7					8	7	6	5	4	3	2	1	0					
8						8	7	6	5	4	3	2	1	0				
9							8	7	6	5	4	3	2	1	0			
10								8	7	6	5	4	3	2	1	0		
11									8	7	6	5	4	3	2	1	0	
12										8	7	6	5	4	3	2	1	
																	D	





	x	-2	-1	0	1	2	3	4	5	6	7	8	9	10	11	12
K	3	6	5	4	3	2	1	0								
4		7	6	5	4	3	2	1	0							
5			8	7	6	5	4	3	2	1	0					
6				8	7	6	5	4	3	2	1	0				
7					8	7	6	5	4	3	2	1	0			
8						8	7	6	5	4	3	2	1	0		
9							8	7	6	5	4	3	2	1	0	
10								8	7	6	5	4	3	2	1	0
11									8	7	6	5	4	3	2	1
12										8	7	6	5	4	3	2
																D

Door clearance (Fmin)	x	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	38	40	Z
K	3	0.4	0.6	0.7	0.8	1.0	1.2	1.4	1.6	1.6	2.0	2.3	2.3	2.6	2.8	3.2	6.1	9.0	10.9	0.4
4		0.4	0.6	0.7	0.8	1.0	1.2	1.4	1.6	1.6	2.0	2.3	2.3	2.5	2.8	3.1	5.3	8.2	10.2	0.4
5		0.4	0.5	0.7	0.8	1.0	1.2	1.3	1.5	1.5	2.0	2.2	2.2	2.5	2.8	3.1	4.7	7.5	9.4	0.4
6		0.4	0.5	0.7	0.8	1.0	1.1	1.3	1.5	1.5	2.0	2.2	2.2	2.4	2.7	3.0	4.1	6.8	8.7	0.4
7		0.4	0.5	0.6	0.8	1.0	1.1	1.3	1.5	1.5	1.9	2.2	2.2	2.4	2.7	3.0	3.6	6.2	8.0	0.4
8		0.4	0.5	0.6	0.8	0.9	1.1	1.3	1.5	1.5	1.9	2.1	2.1	2.4	2.6	2.9	3.5	5.6	7.4	0.4
9		0.4	0.5	0.6	0.8	0.9	1.1	1.3	1.4	1.4	1.9	2.1	2.1	2.4	2.6	2.9	3.5	5.1	6.8	0.4
10		0.4	0.5	0.6	0.8	0.9	1.1	1.2	1.4	1.4	1.8	2.1	2.1	2.3	2.6	2.8	3.4	4.6	6.3	0.4
11		0.4	0.5	0.6	0.8	0.9	1.1	1.2	1.4	1.4	1.8	2.0	2.0	2.3	2.5	2.8	3.4	4.1	5.8	0.4
12		0.4	0.5	0.6	0.7	0.9	1.0	1.2	1.4	1.4	1.8	2.0	2.0	2.3	2.5	2.8	3.3	4.1	5.4	F _{MIN} 0.4

B-type Mounting Plates


For Hinge Ø40

Slide-on hinge to plate mounting




Drilling pattern

Steel mounting plates




Fixing screws for mounting plates
If not pre-mounted



Euro screws
821-6323-050 L=13
821-6332-050 L=15

10000 Pcs



Chipboard screws
820-6328-050

10000 Pcs




Mounting plate thickness

Height adjustment +/- 2mm



Mounting plate type		14	
Mounting plate thickness (D)			
4mm	244-7324-050	244-7314-050	
5mm	244-7325-050	244-7315-050	
6mm	244-7326-050	244-7316-050	
8mm	244-7328-050	244-7318-050	

Legend of mounting plate type symbols

Screw-on ready for
chipboard screwsPre-mounted
14mm euro screws

Wide Angle Hinge

For wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

270°
35mm
12.5mm
key-hole



Nickel plated

Technical details

Cup type

With spring



241-0043-650



241-0050-650

200 Pcs

Made of zinc

Mounting plate
Nickel plated



D=0mm



244-0907-650



244-0848-650



244-0D99-650



244-0E02-650

D=2mm



244-0D47-650



244-0D46-650

200 Pcs


Made of zinc

Mounting plates



This mounting plate can be used only with Wide angle hinge. Information about mounting plate symbols → see page 3.135

Hinge cup screws
If not pre-mounted



820-6308-050


10000 Pcs

Legend of hinge cup symbols


Screw-on ready
← screws

Machine insertion ready


Pre-mounted euro screws





Door adjustment

Side
adjustment
+3/-0mmHeight
adjustment
+2/-2mmDepth
adjustment
+4/-0mm

For further explanation → see pages 3.20-3.23




With spring

Mounting
detailsDrawings show application on D=0
mounting plate and S=18 side panel.Mounting plate
drilling distance

Mounting plate thickness table

For further explanation → see page 3.11


	16	17	18	19	20	21	22	23	24
S	2	0							
P		2	0						
0	2	0							
1		2	0						
2			2	0					
3				2	0				
4	6			2	0				
5		6			2	0			
6			6			2	0		
7				6			2		
8					6				2
9						6			
10							6		
11								6	
12									6
D									D

Drawings show application on
D=6mm thick mounting plate

Door thickness

For correct opening the
door thickness should
not exceed (VMAX) 21mm

Refrigerator Cabinet Door Hinge




- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

110°
35mm
11.5mm
key-hole


Technical details	Cup type	Interaxis 45mm	Interaxis 48mm
		Item number	Item number
Cranking 0mm		248-0R09-050	248-0K10-050
			248-0M41-050
<i>Drilling patterns for hinge cups → see page 3.15</i>			
	200 Pcs	Cup made of steel, arm made of zinc	
Steel mounting plates	D=0mm		244-0655-050
			244-0846-050
<i>Information about mounting plate symbols → see page 3.135</i>			
	500 Pcs	Made of steel	
Mounting plates	Hinge cup screws <i>If not pre-mounted</i>	Legend of hinge cup symbols	
	This hinge can be mounted only with key-hole mounting plates.		Screw-on ready screws
	6.9 15 3.5		Machine insertion ready
			Pre-mounted euro screws
	820-6308-050 10000 Pcs		

- Flat hinge arm allows minimal required gap between refrigerator and cabinet side.




For further explanation → see pages 3.20-3.23

Mounting details




Drawings show application on
D=0mm thick mounting plate

Mounting plate
drilling distance



Door clearance
For further explanation → see page 3.12




V	16	17	18	19	20	21	22
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5
4	0.3	0.5	0.7	0.9	1.2	1.6	2.1
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0

Gap Z_{MIN}=0 F_{MIN}

Push Latch

For wood doors and drawers



Push latch



Push latch



Cross mounting plate


Linear mounting plate



200 Pcs


Made of steel and plastic

Fixing screws for mounting plates



Euro screws
821-6323-050


10000 Pcs




Chipboard screws

- Works with standard concealed hinges and drawers
- Effortless opening with just a light touch
- Depth adjustment ensures reliable closing and consistent performance in cases of inaccurate drilling
- 'Safety click' feature for easy detachment of the mechanism from the mounting plate


Drilling pattern




Dimensions




Positioning



Close to the 'touch opening point'
on the side opposite to hinges



On the cabinet side; gap between
drawer and cabinet side = min 12mm



On the drawer bottom; in
the middle of drawer

Push latch works with standard hinges.

Push latch works on drawer; the gap between
the drawer and the cabinet side = min. 12 mm

Cover Caps

For hinge arms

**Titus
recommends!**

To improve appearance Titus recommends the use of hinge arm cover plates with all compatible concealed hinges.


		Technical details	Plate type	Material/surface	Item number	Nickel plated
S-type			Titus	steel	248-1646 ↗	050
B-type			neutral	steel	248-1712 ↗	050
 4000 Pcs	Made of steel					
T-type			Titus	steel	728-1286 ↗	054
			neutral	steel	728-1283 ↗	054
			For T-type 110 0mm, 110/45 17mm, 110/90 17mm			
T-type			Titus	steel	728-1287 ↗	054
			neutral	steel	728-1284 ↗	054
			For T-type 110 5mm, 9mm, 17mm			

Other Functional Fittings

Drawer Solutions

17mm Drawer Slide

- Runners are paired in one piece moulding
- The guide rail steers the drawer and reduces jamming risk
- Integral drawer stop and hole plugs
- Manufactured in HDPE to provide a smooth glide action



17mm slide pair





C			
C-length	Item number	Neutral	Powder grey
192	05179 →	846	886
260	05364 →		886
288	05184 →	846	
288	*05201 →	846	

*American market only

One set consists of:

- 2 pcs slides
- 2 pcs stops








100 Sets

Made of plastic

Drawer Solutions


Drawer Front Adjuster (DFA)

- Multi-direction adjustment
- Locking screw to fasten
- Independent of drawer system
- One piece housing



Technical and mounting details		Item number	Dark brown	Black	Nickel	White
		06308 →	831		877	
						
2500 Pcs	Made of plastic					
DFA housing		*06310 →	831		877	
		*06309 →	831		877	
		*00033 →			847	
		*American market only				
		*06309 does not include screw				
2500 Pcs	Made of zinc, plastic					
Runner wheel		00900 →	831	835		877
						
4000 Pcs	Made of plastic					

Adjustable Cabinet Leg Range

Leg Top Fixes

	Technical and mounting details	Item number	Black
Rivet fix	 	regular 02560 →	835
		heavy duty *02630 →	835
		* American market only	
 200 Pcs	Made of plastic		
Socket fix (knock in)		02558 →	835
 200 Pcs	Made of plastic		
Socket fix (screw on)		02559 →	835
 200 Pcs	Made of plastic		

- Lip provides additional support to end panel and gives extra strength
- The side fix has twin dowel mounting for positive location
- Rivet fix design gives quick fastening of socket
- Choice of dowel or screw on sockets
- Invert second clip for corner plinth fixing



Technical and mounting details

Leg top

100 Pcs



Made of plastic


(4 screws) screw on

(4 dowels + lip) dowel/lip

(4 screws + lip) screw/lip

2 dowels/2 screws

screw on
dowels




	A	D	B1		
	Drilling diameter	Drilling depth	Drilling distance	Item number	Black
Leg top	3	6	64 x 64	02575 →	835
	10	12.5	64 x 64	02582 →	835
	3	6	64 x 64	02579 →	835
	10/3	12.5/6	64 x 64	* 02669 →	835
	3	6	64 x 64	* 02671 →	835
	10	12.5	64 x 64	* 02672 →	835
<small>* Asian market only When using leg top, you must use foot with 01373 clip → see page 4.6</small>					

Rivet fix/skid

200 Pcs



Made of plastic



				02663 →	835
Rivet fix/skid				* 02642 →	835


* Asian market only

Rivet fix/ no rivet

200 Pcs



Made of plastic



Adjustable Cabinet

Leg Range

Adjustable Leg, Extension and Foot




- Legs are supplied assembled at a pre-set height
- Wide adjustment range to fit all common plinth heights
- Jacking point adjustment feature
- Simple push on design to sockets

Technical and mounting details				B1	H		
				Drilling distance	Fitting height adjustment	Item number	Black
Adjustable leg				24	60-90	02570 →	835
				24	92-152	02549 →	835
				24	92.5-150	* 02666 →	835
				24	92-150	* 02648 →	835
				24	125-185	* 02653 →	835
				big foot	38	92-150	* 02699 →
				big foot	38	125-185	* 02706 →
							835
* Asian market only							
	100 Pcs (02570)	Made of plastic					
	200 Pcs	Made of plastic					
Leg extension						02571 →	835
	200 Pcs	Made of plastic					
Fixed foot						02569 →	835
						* 02574 →	835
* American market only							
	200 Pcs	Made of plastic					

Adjustable Cabinet Leg Range

Plinth Clips and Fox Clip

- Spring design eliminates the need for drilling and fits into any position on plinth
- The screw in version can sit in variable plinth positions
- When taking plinth around the corner, the fitting is reversible.

	Technical and mounting details	Item number	Natural	Black
Fox clip		01373 →	846	
 1000 Pcs	Made of plastic			
Plinth clip 38 screw		02578 →	835	
 500 Pcs	Made of plastic	*02710 →	835	
<i>* Asian market only</i>				
Plinth clip 24 knock on		02523 →	835	
 600 Pcs	Made of plastic			
Plinth clip 24 screw on		02634 →	835	
 600 Pcs	Made of plastic			










Shelf Supports

- Shelf supports are made of zinc, steel or plastic
- Teeth on mounting pin prevent rotation and fall-out of the fitting
- Screw-on and glass shelf versions are available

	Technical and mounting details	Item number	Nickel plated	Zinc
Without pin (rock-in)		336-3553 →	650	
1000 Pcs	Made of zinc			
Structural shelf support		*01851 →	847	885
		* American market only		
3000 Pcs	Made of zinc			
2 pins (rock-in)		336-3552 →	650	
1000 Pcs	Made of zinc			
Pin Ø5x8 (rock-in)		336-3174 →	650	
1000 Pcs	Made of zinc			


Shelf Supports







- Hold down feature traps the shelf in place for security
- Folding design allows the shelf to be post mounted in an assembled cabinet
- To suit a wide range of shelf thicknesses
- Pad for metal shelf support when using glass

		B	Clear	Nickel	Zinc	White	Silver
	Item number						
	01825 →		847	885			
							
							
							
2000 Pcs	Made of zinc						
	01852 →		847				
							
							
2000 Pcs	Made of zinc						
	01822 →						861
							
							
12000 Pcs	Made of plastic						
	15 01837 →						877
							
							
4000 Pcs							
5000 Pcs (01837)	Made of plastic						
* American market only Other colours on request							





Shelf Supports

Mounting procedure:




Technical and mounting details	Item number	Zinc plated blue	Nickel plated
Pin Ø5x10 (screw-on)   	338-3687 →		650
 1000 Pcs For glass shelves (rock-in)   	338-9721 →		860
 1000 Pcs Pin Ø5x10 (rock-in)   	338-3686 →		650
 1000 Pcs Made of zinc			

Shelf Supports

	Technical and mounting details	Item number	Zinc plated blue	Nickel plated	Antique brass plated
Shelf support with pin	 	01910 →		847	
Shelf support	 	01911 →		847	
Pin	 	334-6073 →	040	050	
Pin	 	335-6076 →	040		080


No-Tools Backfix and Trimfix™

- Push Backfix into panel
- No tools required to lock the Backfix panels together
- The handle on Backfix acts as a stop during locking, providing greater accuracy and speed of insertion
- Barbs on the Backfix provide a quality fastener for rigid cabinet construction



Technical and mounting details

Hardboard Backfix




1000 Pcs

Made of zinc

Item number	Zinc	Corrosil	Phosphate	Zinc plated
02154 →	885	897		

Trimfix™



Item number			852
01370 →			

2000 Pcs

Made of various material

Screw panhead
No 8 x 17.6









Item number				883
01709 →				

15000 Pcs

Made of zinc

Glass Clip

Rear Wall Connectors


				
		Pin length	Item number	Nickel plated Transparent
	Drawing shows glass clips mounting example.			
	Technical and mounting details			
Glass clip	   		3.3 359-4201 →	340
		6	359-4302 →	340
		9.5	359-4223 →	340
 25000 Pcs	Made of plastic		353-3649 →	650
Rear wall connector long	  			
 500 Pcs	Made of zinc		353-3650 →	650
Rear wall connector short	  			
 500 Pcs	Made of zinc			

Panel Brackets

- To be used to fix face frames to carcases without additional drilling to cabinet
- Designed for carcase side panel of 18mm thickness
- Edge to hole centre = 28mm
- Easier fixing of frames due to parts that remain in holes once inserted

		Nickel plated	Zinc
	Item number		
90° Bracket (screw-in/rock-in peg)	02111 →	847	885
Technical and mounting details			
1000 Pcs	Made of zinc		
90° Bracket (screw-in)	02110 →	847	885
1000 Pcs	Made of zinc		
Corner bracket (rock-in)	02133 →		885
1000 Pcs	Made of zinc		

Wardrobe Rail Rail Supports



	Technical and mounting details	Item number	Chrome plated	Nickel plated
Rail		339-7047 → 060		


10 Pcs	Made of chrome plated steel		Standard length 3m Standard length is 3m. Other lengths available upon special request → see page 0.3	
--------	-----------------------------	--	---	--



200 Pcs	Made of zinc			337-3710 → 650
---------	--------------	--	--	-------------------

200 Pcs	Made of zinc			337-3711 → 650
---------	--------------	--	--	-------------------

200 Pcs	Made of zinc			337-3709 → 650
---------	--------------	--	--	-------------------

Wardrobe Rail Ø18



	Technical details	Item number	Chrome plated	Nickel plated
Rail		339-7041 →	060	
	 			
			Standard length is 3m. Other lengths available upon special request → see page 0.3	
10 Pcs	Made of steel, chrome plated			
Screw-on under a shelf	 	337-1398 →	050	
300 Pcs	Made of steel		M6 screw supplied separately: 815-6354-040	
			 1000 Pcs	


The Titus Group Profile

Titus Group

Titus focuses on the design, manufacture and distribution of connectors, concealed hinges, drawers and soft closing mechanisms in furniture and household appliances.

Titus Group is owned and managed from its headquarters in United Kingdom. We are able to provide products and services to every customer around the world based on manufacturing facilities in Europe, North America, China, SE Asia, Australia and New Zealand.

Quickfit technology makes Titus the World leader in connectors for RTA furniture



Vision


The world's best engineering for precision components

Mission

To provide manufacturers with components' solutions that improve competitiveness

Titus Business Philosophies and Principles

- Gain total knowledge of our customers and their markets
- Focus on identifying and creating high volume component niches
- Meet our customers' expectations with global consistency
- Build long term associations with customers, suppliers, colleagues and shareholders
- Invest in the abilities of individuals at every level
- Continuously enhance input efficiency and sustainability



Furniture Hardware

- Cabinet connectors
- Concealed hinges
- Soft closing systems
- Drawers and drawer systems
- Kitchen accessories
- Furniture locks
- Decorative

Components

- Dampers
- Precision components

Technologies

- Automation systems
- Precision castings
- Die cast technologies
- Tooling
- Ultrasound fastening technology
- FastFit technology

'Totally Integrated Engineering'

Product Design


Design and engineering of unique components
Consistent and repeatable product quality

Manufacturing Technologies

to improve productivity and product quality

Manufacturing Operations

A wide array of technologies and services required for high volume production of precision components available in-house



Fittings for purpose

Unique product advantages for better value for money and lower 'total installed cost'

Innovations that improve

with less parts, less different parts, less preparation actions, faster assembly

Fast time-to-market

Quality

Continuous Improvement

The Titus Group Mission, to improve the competitiveness of our customers, encourages us to continuously improve our products, services, processes and competencies of our employees.

Quality

We believe that the Titus Mission is achieved most effectively through the management of our design, manufacturing and service activities in conformance with the ISO 9001 standard for quality management. Quality has a broad meaning for us: it is our guide to the selection of materials, work, processes, internal relations and cooperation with partners.


Products

Our integrated quality system produces technically optimized products of high quality. They are assessed regularly in our own test labs as well as by internationally renowned institutions, such as LGA from Germany, CTBA from Frawnce, FIRA from United Kingdom, CATAS from Italy, AIDIMA from Spain, and others.



Global player

Worldwide design, manufacturing and distribution capabilities



Europe

TitusPlus d.o.o.

Dekani 5
SI-6271 Dekani
Slovenia
+386 566 90 213
+386 566 90 205 Fax
info@titusplus.com

Titus d.o.o. Dekani

Dekani 5
SI-6271 Dekani
Slovenia
+386 566 90 213
+386 566 90 205 Fax
info@titusplus.com

Titus Technologies Lama Avtomatizacija d.o.o.

Dekani 5
SI-6271 Dekani
Slovenia
+386 566 90 432
+386 566 90 431 Fax
titustechnologies@titusplus.com

Titus Tool Company Ltd.

10 Blackburn Industrial Estate
Enterprise Way
Sherburn in Elmet
LS256NA
United Kingdom
+44 1977682 582
+44 1977680 481 Fax
uk@titusplus.com

CRO-Lama

Rakitska 10a
Rakitje
HR-10437 Bestovje
Croatia
+385 1 3323 033
+385 1 3323 233 Fax
croatia@titusplus.com

Titus Polska Sp. z o.o.

ul. Stefana 17 A
PL-62-002 Suchy Las/Poznań
Poland
+4861 811 5402 Phone/Fax
+4861 811 5684 Phone/Fax
+4861 821 9362
poland@titusplus.com

TitusPlus Italia Srl

Via Aquileia 9
Frazione Olmi
31048 San Biagio di Callalta (TV)
+39 04 221 650 120
+39 04 221 650 136 Fax
italia@titusplus.com

TitusPlus Iberia SLU

C/ Gran Bretanya 34
08520 Les Franqueses del Valles
(Barcelona)
+34 938 715 404
+34 938 605 498 Fax
iberia@titusplus.com
www.titusplusiberia.com

America

Titus Tool Co. Inc.

2800 156th Avenue SE
Suite 135
Bellevue, WA 98007, USA
800 762 1616 toll free
+1 253 872 2829
+1 253 872 2827 Fax
usa@titusplus.com

Titus Tool Co. Inc.

220 Messner Drive
US-60090 Wheeling, USA
800 762 1616 toll free
+1 253 872 2829
+1 253 872 2827 Fax
usa@titusplus.com

Australia

Titus Tekform Pty Ltd

Unit 1, 41-43 Whyalla Place
Prestons NSW 2170
Australia
+61 2 9286 0007
+61 2 9826 0074 Fax
www.titustekform.com.au
info@titustekform.com.au

NZ Hardware Enterprises Ltd

34 Waipareira Avenue
Henderson
Auckland, New Zealand
+64 9 837 0886
+64 9 837 8003 Fax

Asia

Titus Tool Co. Pte. Ltd.

5004 Ang Mo Kio Ave 5
Techplace II #04-01
Singapore 569872
+656383 3922
+656383 3178 Fax
singapore@titusplus.com

Titus SZ Components limited

1st Floor, Building No.2,
Hengchangrong Hi-tech Industrial Park
128 Shangnan East Road
Hongtian, Shajing, Baoan District
Shenzhen, Guangdong Province
PRC 518125
china@titusplus.com

Titus Tekform Indonesia, PT

Taman Tekno Blok L2 / 7
BSD Sektor XI - Tangerang 15314
Indonesia
T. +62 21 75873578
F. +62 21 75873574
Indonesia@titusplus.com

Headquarters

Titus International Ltd
325 Euston Road
London
NW1 3AD, United Kingdom
info@titusplus.com

www.titusplus.com
info@titusplus.com

Index

Item number	Page						
00021	1.19	02560	4.5	05576	1.44	06385	1.54
00022	1.19	02569	4.7	05578	1.44	06387	1.54
00033	4.4	02570	4.7	05579	1.44	06395	1.52
00062	1.9	02571	4.7	05580	1.44	06397	1.52
00068	1.9	02574	4.7	05586	1.43	06401	1.48
00071	1.9	02575	4.6	05587	1.43	06402	1.48
00072	1.9	02578	4.8	05592	1.37	06403	1.48
00171	1.9	02579	4.6	05608	1.39	06405	1.48
00177	1.9	02582	4.6	05609	1.39	06406	1.48
00180	1.8	02630	4.5	05610	1.39	06408	1.47
00900	4.4	02634	4.8	05611	1.39	06410	1.47
01020	1.9	02648	4.7	05644	1.43	06411	1.50
01029	1.63	02653	4.7	05652	1.43	06412	1.50
01042	1.9	02663	4.6	05653	1.43	06413	1.49
01056	1.9	02663	4.6	05654	1.43	06414	1.49
01370	4.13	02666	4.7	05656	1.43	06415	1.50
01373	4.8	02669	4.6	05657	1.43	06416	1.49
01709	1.12	02671	4.6	05658	1.43	06431	1.51
01709	4.13	02672	4.6	05659	1.43	06433	1.51
01732	1.12	02699	4.7	05675	1.43	06435	1.51
01822	4.10	02706	4.7	05676	1.43	06437	1.51
01823	4.10	02710	4.8	05677	1.43	06439	1.52
01825	4.10	02985	1.12	05678	1.43	06441	1.52
01828	4.10	03090	1.16	05679	1.43	06443	1.52
01829	4.10	03118	1.16	05685	1.33	06445	1.52
01837	4.10	03121	1.16	05714	1.33	06447	1.51
01838	4.10	03150	1.16	05751	1.37	06449	1.51
01843	4.10	03168	1.16	05752	1.37	06451	1.51
01851	4.9	03180	1.16	05753	1.37	06453	1.51
01852	4.10	03181	1.16	05757	1.37	06455	1.52
01910	4.12	05129	1.33	05772	1.37	06457	1.52
01911	4.12	05137	1.33	05774	1.37	06459	1.52
02046	1.12	05179	4.3	05775	1.37	06461	1.52
02075	1.13	05184	4.3	05778	1.37	06464	1.53
02077	1.13	05201	4.3	05786	1.39	06465	1.53
02107	1.20	05314	1.32	05787	1.39	06470	1.53
02110	4.15	05364	4.3	05857	1.37	06471	1.53
02111	4.15	05380	1.37	05858	1.37	06472	1.53
02120	1.20	05388	1.32	05859	1.37	06473	1.53
02130	1.20	05409	1.57	05860	1.38	06479	1.47
02133	4.15	05410	1.57	05917	1.60	06495	1.48
02139	1.20	05414	1.34	05929	1.37	06803	1.18
02141	1.20	05441	1.32	05960	1.60	06806	1.18
02144	1.20	05453	1.32	05971	1.60	06813	1.18
02154	4.13	05474	1.32	06073	1.13	06839	1.18
02161	1.19	05503	1.32	06074	1.9	06947	1.56
02182	1.62	05552	1.33	06077	1.9	06949	1.55
02190	1.19	05554	1.33	06080	1.9	06951	1.56
02193	1.19	05556	1.33	06308	4.4	06953	1.55
02523	4.8	05563	1.33	06309	4.4	09406	1.42
02549	4.7	05570	1.33	06310	4.4	09423	1.35
02558	4.5	05574	1.44	06381	1.54	09424	1.35
02559	4.5	05575	1.44	06383	1.54	09430	1.36

Index

Item number	Page						
09435	1.35	244-0342-050	3.98	244-0P41-650	3.136	248-0308-050	3.95
09443	1.35	244-0343-050	3.98	244-0S65-050	3.136	248-0327-050	3.73
09456	1.35	244-0344-050	3.98	244-0S66-050	3.136	248-0328-050	3.73
09491	1.42	244-0561-050	3.100	244-0S67-050	3.136	248-0366-050	3.73
09495	1.41	244-0562-050	3.100	244-0S68-050	3.136	248-0377-050	3.69
09533	1.41	244-0565-050	3.100	244-0T14-650	3.136	248-0400-050	3.73
09536	1.41	244-0566-050	3.100	244-0T28-050	3.136	248-0401-050	3.73
09537	1.41	244-0567-050	3.100	244-0T40-050	3.136	248-0402-050	3.73
09583	1.35	244-0568-050	3.100	244-0V19-050	3.100	248-0431-050	3.83
09588	1.35	244-0655-050	3.147	244-0V50-050	3.138	248-0433-050	3.83
09592	1.35	244-0810-650	3.113	244-0V64-050	3.136	248-0482-050	3.73
09594	1.35	244-0810-650	3.113	244-0Z26-050	3.100	248-0487-050	3.73
09597	1.36	244-0810-650	3.123	244-0Z51-050	3.100	248-0518-050	3.83
09631	1.42	244-0813-650	3.123	244-0Z63-050	3.100	248-0532-050	3.73
09651	1.31	244-0846-050	3.147	244-1136-050	3.100	248-0533-050	3.73
09652	1.31	244-0848-650	3.145	244-1138-050	3.100	248-0534-050	3.73
09690	1.40	244-0866-050	3.136	244-1139-050	3.100	248-0535-050	3.73
09692	1.40	244-0867-050	3.136	244-1228-050	3.100	248-0536-050	3.73
09695	1.40	244-0907-650	3.145	244-1229-050	3.100	248-0537-050	3.73
09699	1.40	244-0914-650	3.136	244-1233-050	3.100	248-0538-050	3.73
244-0260-050	3.144	244-0929-050	3.136	244-1234-050	3.100	248-0539-050	3.73
241-0043-650	3.145	244-0930-050	3.136	244-1645-050	3.100	248-0540-050	3.73
241-0050-650	3.145	244-0965-050	3.136	244-3016-650	3.100	248-0545-050	3.73
244-0036-650	3.138	244-0B12-650	3.136	244-3651-650	3.100	248-0547-050	3.73
244-0062-650	3.136	244-0C32-650	3.123	244-3653-650	3.102	248-0549-050	3.73
244-0063-650	3.136	244-0D46-650	3.145	244-3654-650	3.102	248-0551-050	3.73
244-0067-650	3.136	244-0D47-650	3.145	244-3655-650	3.102	248-0665-050	3.81
244-0068-650	3.136	244-0D99-650	3.145	244-7314-050	3.144	248-0675-050	3.81
244-0085-650	3.100	244-0E02-650	3.145	244-7315-050	3.144	248-0677-050	3.81
244-0095-650	3.100	244-0G19-050	3.136	244-7316-050	3.144	248-0742-050	3.87
244-0118-050	3.100	244-0H64-050	3.136	244-7318-050	3.144	248-0745-050	3.87
244-0119-050	3.100	244-0H65-050	3.136	244-7324-050	3.144	248-0748-050	3.87
244-0120-050	3.100	244-0K95-050	3.136	244-7325-050	3.144	248-0C66-050	3.77
244-0134-050	3.100	244-0K96-050	3.136	244-7326-050	3.144	248-0G49-050	3.115
244-0135-050	3.100	244-0K97-650	3.136	244-7328-050	3.144	248-0G50-050	3.115
244-0136-050	3.100	244-0K98-650	3.136	248-0080-050	3.77	248-0G51-050	3.115
244-0137-050	3.100	244-0L26-050	3.136	248-0160-050	3.129	248-0G52-050	3.117
244-0166-050	3.100	244-0L29-050	3.136	248-0161-050	3.129	248-0G53-050	3.123
244-0167-050	3.100	244-0L37-650	3.136	248-0162-050	3.93	248-0G54-050	3.115
244-0175-650	3.136	244-0L38-650	3.136	248-0163-050	3.93	248-0G55-050	3.115
244-0232-650	3.136	244-0L39-050	3.136	248-0171-050	3.73	248-0G56-050	3.115
244-0258-050	3.98	244-0L40-050	3.136	248-0172-050	3.73	248-0G57-050	3.117
244-0259-050	3.98	244-0L50-050	3.136	248-0186-050	3.73	248-0G58-050	3.123
244-0260-050	3.98	244-0L98-050	3.136	248-0188-050	3.73	248-0G59-050	3.115
244-0261-050	3.98	244-0M28-650	3.136	248-0197-050	3.73	248-0G60-050	3.115
244-0262-050	3.98	244-0M29-650	3.136	248-0198-050	3.91	248-0G61-050	3.115
244-0263-050	3.98	244-0M33-650	3.100	248-0255-050	3.123	248-0G62-050	3.117
244-0264-050	3.98	244-0P24-050	3.136	248-0274-050	3.69	248-0G63-050	3.123
244-0265-050	3.98	244-0P25-050	3.136	248-0279-050	3.73	248-0G79-050	3.115
244-0266-050	3.98	244-0P26-050	3.100	248-0280-050	3.73	248-0G80-050	3.115
244-0270-050	3.98	244-0P27-050	3.100	248-0283-050	3.85	248-0G81-050	3.115
244-0271-050	3.98	244-0P28-650	3.123	248-0285-050	3.85	248-0G82-050	3.117
244-0272-050	3.98	244-0P29-650	3.100	248-0291-050	3.85	248-0G83-050	3.123

Index

Item number	Page	Item number	Page	Item number	Page	Item number	Page
248-0K10-050	3.147	248-0T13-050	3.69	275-2030	1.58	700-0KB4-054	3.52
248-0K40-050	3.115	248-0T69-050	3.69	275-2057	1.59	700-0KC0-054	3.52
248-0K76-050	3.115	248-0T70-050	3.69	275-2058	1.59	700-0KC1-054	3.52
248-0L04-050	3.115	248-0T71-050	3.69	275-2146	1.59	700-0KC2-054	3.52
248-0L27-650	3.119	248-0T72-050	3.69	275-2209	1.58	700-0KC3-054	3.52
248-0L28-050	3.121	248-0T80-050	3.131	275-3096	1.58	700-0KC4-054	3.52
248-0L32-650	3.119	248-0T81-050	3.131	275-4034	1.63	700-0KE0-054	3.52
248-0L33-050	3.121	248-0T93-050	3.69	275-4035	1.62	700-0KE1-054	3.52
248-0L46-050	3.121	248-0T94-050	3.69	275-4058	1.62	700-0KE2-054	3.52
248-0L51-050	3.127	248-0T95-050	3.69	276-4036	1.62	700-0KE3-054	3.52
248-0L61-050	3.87	248-0U13-050	3.131	277-4225	1.63	700-0KF0-054	3.52
248-0L63-050	3.115	248-0U14-050	3.131	277-4355	1.63	700-0KF1-054	3.52
248-0L70-050	3.121	248-0U16-050	3.95	278-4129	1.21	700-0KF2-054	3.52
248-0L71-050	3.119	248-0U21-050	3.95	279-9187	1.22	700-0KF3-054	3.52
248-0L72-050	3.117	248-0U22-050	3.95	279-9465	1.22	700-0KF4-054	3.52
248-0L73-050	3.123	248-0V14-050	3.75	334-6073	4.12	700-0LB0-650	3.52
248-0M41-050	3.147	248-0V15-050	3.95	335-6076	4.12	700-0LB2-650	3.52
248-0M73-050	3.91	248-0V18-050	3.79	336-3174	4.9	700-0LB3-650	3.52
248-0M74-050	3.91	248-0V39-050	3.75	336-3552	4.9	700-0LC0-650	3.52
248-0M83-050	3.119	248-0V40-050	3.75	336-3553	4.9	700-0LC2-650	3.52
248-0M84-050	3.121	248-0V41-050	3.75	337-1398	4.17	700-0LC3-650	3.52
248-0N12-050	3.81	248-0V42-050	3.75	337-3709	4.16	700-0LF0-650	3.52
248-0N13-050	3.81	248-0V43-050	3.75	337-3710	4.16	700-0LF2-650	3.52
248-0N14-050	3.81	248-0V45-050	3.79	337-3711	4.16	700-0LF3-650	3.52
248-0N16-050	3.83	248-0V47-050	3.79	338-3686	4.11	700-0NA0-054	3.54
248-0N17-050	3.83	248-0V48-050	3.79	338-3687	4.11	700-0NA1-054	3.54
248-0N18-050	3.83	248-0V49-050	3.79	338-9721	4.11	700-0NA2-054	3.54
248-0N20-050	3.85	248-0V53-050	3.123	339-7041	4.17	700-0NA3-054	3.54
248-0N21-050	3.85	248-0V56-050	3.69	339-7047	4.16	700-0NA4-054	3.54
248-0N22-050	3.85	248-0V62-050	3.77	353-3649	4.14	700-0NB0-054	3.54
248-0N24-050	3.87	248-0V65-050	3.91	353-3650	4.14	700-0NB1-054	3.54
248-0N25-050	3.87	248-0V66-050	3.123	359-4201	4.14	700-0NB2-054	3.54
248-0N26-050	3.87	248-0V69-050	3.69	359-4223	4.14	700-0NB3-054	3.54
248-0N38-050	3.119	248-0V70-050	3.69	359-4302	4.14	700-0NB4-054	3.54
248-0N62-050	3.87	248-0V71-050	3.69	408-3166	1.61	700-0NC0-054	3.54
248-0P43-050	3.127	248-0V72-050	3.69	408-3391	1.61	700-0NC1-054	3.54
248-0R09-050	3.147	248-0Z20-050	3.95	408-3423	1.61	700-0NC2-054	3.54
248-0R10-050	3.127	248-0Z29-050	3.79	408-3424	1.61	700-0NC3-054	3.54
248-0R11-050	3.127	248-0Z81-050	3.87	44-1137-050	3.100	700-0NC4-054	3.54
248-0R12-050	3.127	248-1646	3.151	700-0KE4-054	3.52	700-0NE0-054	3.54
248-0R13-050	3.91	248-1712	3.151	700-0KA0-054	3.52	700-0NE1-054	3.54
248-0R14-050	3.91	248-3600-650	3.102	700-0KA1-054	3.52	700-0NE2-054	3.54
248-0R15-050	3.91	248-3603-650	3.102	700-0KA2-054	3.52	700-0NE3-054	3.54
248-0R17-050	3.91	249-7301-050	3.139	700-0KA3-054	3.52	700-0NE4-054	3.54
248-0R18-050	3.91	249-7302-050	3.139	700-0KA4-054	3.52	700-0NF0-054	3.54
248-0S05-050	3.127	249-7303-050	3.141	700-0KB0-054	3.52	700-0NF1-054	3.54
248-0S06-050	3.127	249-7304-650	3.141	700-0KB1-054	3.52	700-0NF2-054	3.54
248-0S69-050	3.91	275-0103	1.59	700-0KB2-054	3.52	700-0NF3-054	3.54
248-0T10-050	3.69	275-0106	1.59	700-0KB3-054	3.52	700-0NF4-054	3.54

Index

Item number	Page	Item number	Page	Item number	Page	Item number	Page
700-0NR0-054	3.54	701-0VS0-054	3.31	702-0FK1-054	3.47	950-0T27-050	3.89
700-0NR1-054	3.54	701-0VS1-054	3.31	702-0FK4-054	3.47	951-0F15-650	2.17
700-0NR2-054	3.54	701-0VS4-054	3.31	702-0FL0-054	3.47	951-0P59-050	2.15
700-0NR3-054	3.54	701-0VT0-054	3.31	702-0FL1-054	3.47	951-0P63-050	2.15
700-0NR4-054	3.54	701-0VT1-054	3.31	702-0FL4-054	3.47	951-0X94-050	2.15
700-0NW0-054	3.54	701-0VT4-054	3.31	702-0GK0-054	3.49	954-0147-650	3.107
700-0NW3-054	3.54	702-0A95-054	3.45	702-0GK1-054	3.49	954-0148-650	3.109
701-0A96-054	3.35	702-0A97-054	3.45	702-0GK4-054	3.49	954-0149-650	3.113
701-0A98-054	3.35	702-0AK0-054	3.37	702-0GL0-054	3.49	954-0153-650	3.107
701-0AS0-054	3.27	702-0AK1-054	3.37	702-0GL1-054	3.49	954-0154-650	3.109
701-0AS1-054	3.27	702-0AK4-054	3.37	702-0GL4-054	3.49	954-0158-650	3.111
701-0AS4-054	3.27	702-0AL0-054	3.37	702-0UK0-054	3.41	954-0159-650	3.113
701-0AT0-054	3.27	702-0AL1-054	3.37	702-0UK1-054	3.41	954-0164-650	3.61
701-0AT1-054	3.27	702-0AL4-054	3.37	702-0UK4-054	3.41	954-0165-650	3.63
701-0AT4-054	3.27	702-0B07-054	3.43	702-0UL0-054	3.41	954-0168-650	3.111
701-0B08-054	3.33	702-0B09-054	3.43	702-0UL1-054	3.41	954-0226-050	3.59
701-0B10-054	3.33	702-0BK0-054	3.37	702-0UL4-054	3.41	954-0227-050	3.59
701-0BS0-054	3.27	702-0BK1-054	3.37	702-0VK0-054	3.41	954-0228-050	3.57
701-0BS1-054	3.27	702-0BK4-054	3.37	702-0VK1-054	3.41	954-0229-050	3.57
701-0BS4-054	3.27	702-0BL0-054	3.37	702-0VK4-054	3.41	954-0230-050	3.59
701-0BT0-054	3.27	702-0BL1-054	3.37	702-0VL0-054	3.41	954-0B97-050	3.105
701-0BT1-054	3.27	702-0BL4-054	3.37	702-0VL1-054	3.41	954-0B98-050	3.105
701-0BT4-054	3.27	702-0C53-054	3.43	702-0VL4-054	3.41	954-0B99-050	3.105
701-0C54-054	3.33	702-0C55-054	3.43	728-1283	3.151	954-0C01-050	3.105
701-0C56-054	3.33	702-0C77-054	3.43	728-1284	3.151	954-0C02-050	3.105
701-0C78-054	3.33	702-0C79-054	3.43	728-1286	3.151	954-0C03-050	3.105
701-0C80-054	3.33	702-0CK0-054	3.39	728-1287	3.151	954-0E05-050	3.59
701-0CS0-054	3.29	702-0CK1-054	3.39	729-0K71-054	2.15	954-0E09-650	3.61
701-0CS1-054	3.29	702-0CK4-054	3.39	825-7561	1.21	954-0E10-650	3.63
701-0CS4-054	3.29	702-0CL0-054	3.39	827-4013	1.10	954-0E11-650	3.65
701-0CT0-054	3.29	702-0CL1-054	3.39	827-4130	1.10	954-0E12-650	3.67
701-0CT1-054	3.29	702-0CL4-054	3.39	827-6201	1.10	954-0E13-050	3.59
701-0CT4-054	3.29	702-0D29-054	3.45	827-6202	1.10	954-0E14-650	3.65
701-0D30-054	3.35	702-0D31-054	3.45	915-0007-050	3.71	954-0E15-650	3.67
701-0D32-054	3.35	702-0D35-054	3.45	915-0012-050	3.71	954-0E16-050	3.57
701-0D36-054	3.35	702-0D37-054	3.45	915-0032-050	3.71	954-0E17-050	3.57
701-0D38-054	3.35	702-0DK0-054	3.39	915-0320	3.149	954-0U81-050	3.59
701-0DS0-054	3.29	702-0DK1-054	3.39	915-0X59	3.149	972-0X19	2.19
701-0DS1-054	3.29	702-0DK4-054	3.39	915-0Z85-050	3.71	972-0X34	2.19
701-0DS4-054	3.29	702-0DL0-054	3.39	915-0Z96-050	3.71	973-0M99	2.23
701-0DT0-054	3.29	702-0DL1-054	3.39	915-4175	3.149	973-0X35	2.21
701-0DT1-054	3.29	702-0DL4-054	3.39	915-4183	3.149	973-0X39	2.25
701-0DT4-054	3.29	702-0EK0-054	3.47	915-7016-380	3.71	973-0X95	2.25
701-0US0-054	3.31	702-0EK1-054	3.47	915-7022-380	3.71	973-4125	2.25
701-0US1-054	3.31	702-0EK4-054	3.47	915-7105-050	3.71	973-4126	2.25
701-0US4-054	3.31	702-0EL0-054	3.47	915-7109-050	3.71	973-4451	2.21, 2.23
701-0UT0-054	3.31	702-0EL1-054	3.47	926-0A26-050	3.133	973-9018	2.27
701-0UT1-054	3.31	702-0EL4-054	3.47	926-0A27-050	3.133		
701-0UT4-054	3.31	702-0FK0-054	3.47	950-0T26-050	3.125		

Your authorized dealer